



ARR05B104KGA Information

Heisener.com

Part Number ARR05B104KGA

Manufacturer KEMET Category Capacitors

Ceramic Capacitors

Description CAP CER 0.1UF 50V X7R RADIAL

Package Radia

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com





Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ARR05B104KGA	Specifications
AKKU3D1U4KGA	Specifications

Manufacturer Part Number ARR05B104KGA Manufacturer KEMET Category Capacitors Package Radial Series ARR Capacitance 0.1µF Tolerance ±10% Voltage - Rated 50V Temperature Coefficient X7R Operating Temperature -55°C ~ 200°C Features High Temperature Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.200" L x 0.100" W (5.08mm x 2.54mm) Height - Seated (Max) 0.200" (5.08mm) Thickness (Max) - Lead Spacing 0.200" (5.08mm) Lead Style Formed Leads		
Category Capacitors Package Radial Series ARR Capacitance 0.1µF Tolerance ±10% Voltage - Rated 50V Temperature Coefficient X7R Operating Temperature -55°C ~ 200°C Features High Temperature Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.200" L x 0.100" W (5.08mm x 2.54mm) Height - Seated (Max) 0.200" (5.08mm) Thickness (Max) - Lead Spacing 0.200" (5.08mm) Lead Style Formed Leads	Manufacturer Part Number	ARR05B104KGA
Package Radial Series ARR Capacitance 0.1μF Tolerance ±10% Voltage - Rated 50V Temperature Coefficient X7R Operating Temperature -55°C ~ 200°C Features High Temperature Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.200" L x 0.100" W (5.08mm x 2.54mm) Height - Seated (Max) 0.200" (5.08mm) Thickness (Max) - Lead Spacing 0.200" (5.08mm) Lead Style Formed Leads	Manufacturer	KEMET
Package Radial Series ARR Capacitance 0.1µF Tolerance ±10% Voltage - Rated 50V Temperature Coefficient X7R Operating Temperature -55°C ~ 200°C Features High Temperature Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.200" L x 0.100" W (5.08mm x 2.54mm) Height - Seated (Max) 0.200" (5.08mm) Thickness (Max) - Lead Spacing 0.200" (5.08mm) Lead Style Formed Leads	Category	Capacitors
Series ARR Capacitance 0.1μF Tolerance ±10% Voltage - Rated 50V Temperature Coefficient X7R Operating Temperature -55°C ~ 200°C Features High Temperature Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.200" L x 0.100" W (5.08mm x 2.54mm) Height - Seated (Max) 0.200" (5.08mm) Thickness (Max) - Lead Spacing 0.200" (5.08mm) Lead Style Formed Leads		Ceramic Capacitors
Capacitance 0.1μF Tolerance ±10% Voltage - Rated 50V Temperature Coefficient X7R Operating Temperature -55°C ~ 200°C Features High Temperature Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.200" L x 0.100" W (5.08mm x 2.54mm) Height - Seated (Max) 0.200" (5.08mm) Thickness (Max) - Lead Spacing 0.200" (5.08mm) Lead Style Formed Leads	Package	Radial
Tolerance ±10% Voltage - Rated 50V Temperature Coefficient X7R Operating Temperature -55°C ~ 200°C Features High Temperature Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.200" L x 0.100" W (5.08mm x 2.54mm) Height - Seated (Max) 0.200" (5.08mm) Thickness (Max) - Lead Spacing 0.200" (5.08mm) Lead Style Formed Leads	Series	ARR
Voltage - Rated Temperature Coefficient X7R Operating Temperature -55°C ~ 200°C Features High Temperature Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.200" L x 0.100" W (5.08mm x 2.54mm) Height - Seated (Max) Thickness (Max) - Lead Spacing 0.200" (5.08mm) Lead Style Formed Leads	Capacitance	0.1μF
Temperature Coefficient X7R Operating Temperature -55°C ~ 200°C Features High Temperature Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.200" L x 0.100" W (5.08mm x 2.54mm) Height - Seated (Max) Thickness (Max) - Lead Spacing 0.200" (5.08mm) Lead Style Formed Leads	Tolerance	±10%
Operating Temperature-55°C ~ 200°CFeaturesHigh TemperatureRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.100" W (5.08mm x 2.54mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads	Voltage - Rated	50V
Features High Temperature Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.200" L x 0.100" W (5.08mm x 2.54mm) Height - Seated (Max) 0.200" (5.08mm) Thickness (Max) - Lead Spacing 0.200" (5.08mm) Lead Style Formed Leads	Temperature Coefficient	X7R
Ratings - General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.200" L x 0.100" W (5.08mm x 2.54mm) Height - Seated (Max) 0.200" (5.08mm) Thickness (Max) - Lead Spacing 0.200" (5.08mm) Lead Style Formed Leads	Operating Temperature	-55°C ~ 200°C
Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.200" L x 0.100" W (5.08mm x 2.54mm) Height - Seated (Max) 0.200" (5.08mm) Thickness (Max) - Lead Spacing 0.200" (5.08mm) Lead Style Formed Leads	Features	High Temperature
Failure Rate Mounting Type Through Hole Package / Case Radial Size / Dimension 0.200" L x 0.100" W (5.08mm x 2.54mm) Height - Seated (Max) 0.200" (5.08mm) Thickness (Max) - Lead Spacing 0.200" (5.08mm) Lead Style Formed Leads	Ratings	-
Mounting Type Through Hole Package / Case Radial Size / Dimension 0.200" L x 0.100" W (5.08mm x 2.54mm) Height - Seated (Max) 0.200" (5.08mm) Thickness (Max) - Lead Spacing 0.200" (5.08mm) Lead Style Formed Leads	Applications	General Purpose
Package / Case Radial Size / Dimension 0.200" L x 0.100" W (5.08mm x 2.54mm) Height - Seated (Max) 0.200" (5.08mm) Thickness (Max) - Lead Spacing 0.200" (5.08mm) Lead Style Formed Leads	Failure Rate	-
Size / Dimension 0.200" L x 0.100" W (5.08mm x 2.54mm) Height - Seated (Max) 0.200" (5.08mm) Thickness (Max) - Lead Spacing 0.200" (5.08mm) Lead Style Formed Leads	Mounting Type	Through Hole
Height - Seated (Max) Thickness (Max) Lead Spacing 0.200" (5.08mm) Lead Style Formed Leads	Package / Case	Radial
Thickness (Max) Lead Spacing 0.200" (5.08mm) Lead Style Formed Leads	Size / Dimension	0.200" L x 0.100" W (5.08mm x 2.54mm)
Lead Spacing 0.200" (5.08mm) Lead Style Formed Leads	Height - Seated (Max)	0.200" (5.08mm)
Lead Style Formed Leads	Thickness (Max)	-
·	Lead Spacing	0.200" (5.08mm)
Report errors?	Lead Style	Formed Leads
		Report errors?

ARR05B104KGA Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ARR05B104KGA Payment Methods



















ARR05B104KGA Shipping Methods













If you have any question about ARR05B104KGA, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com