



ARS34Y12 Information



For Reference Only

Part Number ARS34Y12

Manufacturer Panasonic Electric Works

Category Relays

Signal Relays, Up to 2 Amps

Description RELAY RF SPDT 500MA 12V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ARS34Y12 Specifications

Manufacturer ARS34Y12 Manufacturer Panasonic Electric Works Category Relays Signal Relays, Up to 2 Amps Package - Series ARS Relay Type RF Coil Type Non Latching Coil Current 16.7mA Coil Voltage 12VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 500mA Switching Voltage 30VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 10ms Release Time 6ms Features - Mounting Type Surface Mount Termination Style Gull Wing		
CategoryRelaysPackage-SeriesARSRelay TypeRFCoil TypeNon LatchingCoil Current16.7mACoil Voltage12VDCContact FormSPDT (1 Form C)Contact Rating (Current)500mASwitching Voltage30VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)1.2 VDCOperate Time10msRelease Time6msFeatures-Mounting TypeSurface MountTermination StyleGull Wing	Manufacturer Part Number	ARS34Y12
Package-SeriesARSRelay TypeRFCoil TypeNon LatchingCoil Current16.7mACoil Voltage12VDCContact FormSPDT (1 Form C)Contact Rating (Current)500mASwitching Voltage30VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)1.2 VDCOperate Time10msRelease Time6msFeatures-Mounting TypeSurface MountTermination StyleGull Wing	Manufacturer	Panasonic Electric Works
Package-SeriesARSRelay TypeRFCoil TypeNon LatchingCoil Current16.7mACoil Voltage12VDCContact FormSPDT (1 Form C)Contact Rating (Current)500mASwitching Voltage30VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)1.2 VDCOperate Time10msRelease Time6msFeatures-Mounting TypeSurface MountTermination StyleGull Wing	Category	Relays
SeriesARSRelay TypeRFCoil TypeNon LatchingCoil Current16.7mACoil Voltage12VDCContact FormSPDT (1 Form C)Contact Rating (Current)500mASwitching Voltage30VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)1.2 VDCOperate Time10msRelease Time6msFeatures-Mounting TypeSurface MountTermination StyleGull Wing		Signal Relays, Up to 2 Amps
Relay TypeRFCoil TypeNon LatchingCoil Current16.7mACoil Voltage12VDCContact FormSPDT (1 Form C)Contact Rating (Current)500mASwitching Voltage30VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)1.2 VDCOperate Time10msRelease Time6msFeatures-Mounting TypeSurface MountTermination StyleGull Wing	Package	-
Coil TypeNon LatchingCoil Current16.7mACoil Voltage12VDCContact FormSPDT (1 Form C)Contact Rating (Current)500mASwitching Voltage30VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)1.2 VDCOperate Time10msRelease Time6msFeatures-Mounting TypeSurface MountTermination StyleGull Wing	Series	ARS
Coil Current Coil Voltage 12VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 500mA Switching Voltage 30VDC - Max Turn On Voltage (Max) 7 Unrn Off Voltage (Min) 1.2 VDC Operate Time 10ms Release Time 6ms Features - Mounting Type Surface Mount Termination Style 16.7mA 12VDC 500mA 500mA 1.2 VDC 1.2 VDC 500mA 50	Relay Type	RF
Coil Voltage Contact Form SPDT (1 Form C) Contact Rating (Current) 500mA Switching Voltage 30VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 10ms Release Time 6ms Features - Mounting Type Surface Mount Termination Style Gull Wing	Coil Type	Non Latching
Contact Form SPDT (1 Form C) Contact Rating (Current) 500mA Switching Voltage 30VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 10ms Release Time 6ms Features - Mounting Type Surface Mount Termination Style Gull Wing	Coil Current	16.7mA
Contact Rating (Current) Switching Voltage 30VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 10ms Release Time 6ms Features - Mounting Type Surface Mount Termination Style	Coil Voltage	12VDC
Switching Voltage 30VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 10ms Release Time 6ms Features - Mounting Type Surface Mount Termination Style Gull Wing	Contact Form	SPDT (1 Form C)
Turn On Voltage (Max) 7 Turn Off Voltage (Min) 1.2 VDC Operate Time 10ms Release Time 6ms Features - Mounting Type Surface Mount Termination Style Gull Wing	Contact Rating (Current)	500mA
Turn Off Voltage (Min) Operate Time 10ms Release Time 6ms Features - Mounting Type Surface Mount Termination Style Gull Wing	Switching Voltage	30VDC - Max
Operate Time 10ms Release Time 6ms Features - Mounting Type Surface Mount Termination Style Gull Wing	Turn On Voltage (Max)	9 VDC
Release Time 6ms Features - Mounting Type Surface Mount Termination Style Gull Wing	Turn Off Voltage (Min)	1.2 VDC
Features - Mounting Type Surface Mount Termination Style Gull Wing	Operate Time	10ms
Mounting Type Surface Mount Termination Style Gull Wing	Release Time	6ms
Termination Style Gull Wing	Features	-
	Mounting Type	Surface Mount
Report errors?	Termination Style	Gull Wing
		Report errors?

ARS34Y12 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ARS34Y12 Payment Methods



















ARS34Y12 Shipping Methods













If you have any question about ARS34Y12, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com