



### **ARXP1106 Information**

Heisener.com

Part Number ARXP1106

Manufacturer Panasonic Electric Works

Category Relays

Signal Relays, Up to 2 Amps

**Description** RELAY RF SPDT 500MA 6V

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **ARXP1106 Specifications**

Manufacturer Part Number       ARXP1106         Manufacturer       Panasonic Electric Works         Category       Relays         Signal Relays, Up to 2 Amps         Package       -         Series       ARXP         Relay Type       RF         Coil Type       Latching, Single Coil         Coil Current       33.3mA         Coil Voltage       6VDC         Contact Form       SPDT (1 Form C)         Contact Rating (Current)       500mA         Switching Voltage       30VDC - Max         Turn On Voltage (Max)       4.5 VDC         Turn Off Voltage (Min)       -         Operate Time       10ms         Release Time       10ms         Features       -         Mounting Type       Through Hole         Termination Style       PC Pin		
CategoryRelaysPackage-SeriesARXPRelay TypeRFCoil TypeLatching, Single CoilCoil Current33.3mACoil Voltage6VDCContact FormSPDT (1 Form C)Contact Rating (Current)500mASwitching Voltage30VDC - MaxTurn On Voltage (Max)4.5 VDCTurn Off Voltage (Min)-Operate Time10msRelease Time10msFeatures-Mounting TypeThrough Hole	Manufacturer Part Number	ARXP1106
Package - Series ARXP Relay Type RF Coil Type Latching, Single Coil Coil Current 33.3mA Coil Voltage 6VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 500mA Switching Voltage 30VDC - Max Turn On Voltage (Max) 4.5 VDC Turn Off Voltage (Min) - Operate Time 10ms Release Time 10ms Features - Mounting Type Trhrough Hole	Manufacturer	Panasonic Electric Works
Package - Series ARXP Relay Type RF Coil Type Latching, Single Coil Coil Current 33.3mA Coil Voltage 6VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 500mA Switching Voltage 30VDC - Max Turn On Voltage (Max) 4.5 VDC Turn Off Voltage (Min) - Operate Time 10ms Release Time 10ms Features - Mounting Type Through Hole	Category	Relays
Series ARXP Relay Type RF Coil Type Latching, Single Coil Coil Current 33.3mA Coil Voltage 6VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 500mA Switching Voltage 30VDC - Max Turn On Voltage (Max) 4.5 VDC Turn Off Voltage (Min) - Operate Time 10ms Release Time 10ms Features - Mounting Type Through Hole		Signal Relays, Up to 2 Amps
Relay Type RF Coil Type Latching, Single Coil Coil Current 33.3mA Coil Voltage 6VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 500mA Switching Voltage 30VDC - Max Turn On Voltage (Max) 4.5 VDC Turn Off Voltage (Min) - Operate Time 10ms Release Time 10ms Release Time 10ms Features - Mounting Type Through Hole	Package	-
Coil Type Latching, Single Coil Coil Current 33.3mA  Coil Voltage 6VDC  Contact Form SPDT (1 Form C) Contact Rating (Current) 500mA  Switching Voltage 30VDC - Max Turn On Voltage (Max) 4.5 VDC  Turn Off Voltage (Min) - Operate Time 10ms  Release Time 10ms  Features - Mounting Type Through Hole	Series	ARXP
Coil Current 33.3mA  Coil Voltage 6VDC  Contact Form SPDT (1 Form C)  Contact Rating (Current) 500mA  Switching Voltage 30VDC - Max  Turn On Voltage (Max) 4.5 VDC  Turn Off Voltage (Min) -  Operate Time 10ms  Release Time 10ms  Features -  Mounting Type Through Hole	Relay Type	RF
Coil Voltage 6VDC  Contact Form SPDT (1 Form C)  Contact Rating (Current) 500mA  Switching Voltage 30VDC - Max  Turn On Voltage (Max) 4.5 VDC  Turn Off Voltage (Min) -  Operate Time 10ms  Release Time 10ms  Features  Mounting Type Through Hole	Coil Type	Latching, Single Coil
Contact Form SPDT (1 Form C)  Contact Rating (Current) 500mA  Switching Voltage 30VDC - Max  Turn On Voltage (Max) 4.5 VDC  Turn Off Voltage (Min) -  Operate Time 10ms  Release Time 10ms  Features -  Mounting Type Through Hole	Coil Current	33.3mA
Contact Rating (Current)  Switching Voltage  30VDC - Max  Turn On Voltage (Max)  4.5 VDC  Turn Off Voltage (Min)  Operate Time  10ms  Release Time  10ms  Features  Mounting Type  Through Hole	Coil Voltage	6VDC
Switching Voltage 30VDC - Max Turn On Voltage (Max) 4.5 VDC Turn Off Voltage (Min) - Operate Time 10ms Release Time 10ms Features - Mounting Type Through Hole	Contact Form	SPDT (1 Form C)
Turn On Voltage (Max)  Turn Off Voltage (Min)  Operate Time  10ms  Release Time  10ms  Features  - Mounting Type  Through Hole	Contact Rating (Current)	500mA
Turn Off Voltage (Min) Operate Time 10ms Release Time 10ms Features - Mounting Type Through Hole	Switching Voltage	30VDC - Max
Operate Time 10ms Release Time 10ms Features - Mounting Type Through Hole	Turn On Voltage (Max)	4.5 VDC
Release Time 10ms Features - Mounting Type Through Hole	Turn Off Voltage (Min)	-
Features - Mounting Type Through Hole	Operate Time	10ms
Mounting Type Through Hole	Release Time	10ms
	Features	-
Termination Style PC Pin	Mounting Type	Through Hole
·	Termination Style	PC Pin
Report errors?		Report errors?

#### **ARXP1106 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **ARXP1106 Payment Methods**



















### **ARXP1106 Shipping Methods**













If you have any question about ARXP1106, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com