



ARXP1124 Information

Heisener.com

Part Number ARXP1124

Manufacturer Panasonic Electric Works

Category Relays

Signal Relays, Up to 2 Amps

Description RELAY RF SPDT 500MA 24V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ARXP1124 Specifications

Manufacturer Part NumberARXP1124ManufacturerPanasonic Electric WorksCategoryRelaysSignal Relays, Up to 2 AmpsPackage-SeriesARXPRelay TypeRFCoil TypeLatching, Single CoilCoil Current8.3mACoil Voltage24VDCContact FormSPDT (1 Form C)Contact Rating (Current)500mASwitching Voltage30VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)-Operate Time10msRelease Time10msFeatures-Mounting TypeThrough HoleTermination StylePC Pin		
Category Relays Signal Relays, Up to 2 Amps Package - Series ARXP Relay Type RF Coil Type Latching, Single Coil Coil Current 8.3mA Coil Voltage 24VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 500mA Switching Voltage 30VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) Operate Time 10ms Release Time 10ms Features Mounting Type Through Hole	Manufacturer Part Number	ARXP1124
Package Series ARXP Relay Type RF Coil Type Latching, Single Coil Coil Current 8.3mA Coil Voltage 24VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 500mA Switching Voltage 30VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) Operate Time 10ms Release Time 10ms Features Mounting Type Trhrough Hole	Manufacturer	Panasonic Electric Works
Package - Series ARXP Relay Type RF Coil Type Latching, Single Coil Coil Current 8.3mA Coil Voltage 24VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 500mA Switching Voltage 30VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) - Operate Time 10ms Release Time 10ms Features - Mounting Type Through Hole	Category	Relays
SeriesARXPRelay TypeRFCoil TypeLatching, Single CoilCoil Current8.3mACoil Voltage24VDCContact FormSPDT (1 Form C)Contact Rating (Current)500mASwitching Voltage30VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)-Operate Time10msRelease Time10msFeatures-Mounting TypeThrough Hole		Signal Relays, Up to 2 Amps
Relay Type RF Coil Type Latching, Single Coil Coil Current 8.3mA Coil Voltage 24VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 500mA Switching Voltage 30VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) - Operate Time 10ms Release Time 10ms Release Time 10ms Features - Mounting Type Through Hole	Package	-
Coil Type	Series	ARXP
Coil Current Coil Voltage 24VDC Contact Form SPDT (1 Form C) Contact Rating (Current) Switching Voltage 30VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) Operate Time 10ms Release Time 10ms Features Mounting Type Through Hole	Relay Type	RF
Coil Voltage 24VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 500mA Switching Voltage 30VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) - Operate Time 10ms Release Time 10ms Features Mounting Type Through Hole	Coil Type	Latching, Single Coil
Contact Form SPDT (1 Form C) Contact Rating (Current) 500mA Switching Voltage 30VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) - Operate Time 10ms Release Time 10ms Features - Mounting Type Through Hole	Coil Current	8.3mA
Contact Rating (Current) Switching Voltage 30VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) Operate Time 10ms Release Time 10ms Features Mounting Type Through Hole	Coil Voltage	24VDC
Switching Voltage 30VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) - Operate Time 10ms Release Time 10ms Features - Mounting Type Through Hole	Contact Form	SPDT (1 Form C)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 10ms Release Time 10ms Features - Mounting Type Through Hole	Contact Rating (Current)	500mA
Turn Off Voltage (Min) Operate Time 10ms Release Time 10ms Features - Mounting Type Through Hole	Switching Voltage	30VDC - Max
Operate Time 10ms Release Time 10ms Features - Mounting Type Through Hole	Turn On Voltage (Max)	18 VDC
Release Time 10ms Features - Mounting Type Through Hole	Turn Off Voltage (Min)	-
Features - Mounting Type Through Hole	Operate Time	10ms
Mounting Type Through Hole	Release Time	10ms
	Features	-
Termination Style PC Pin	Mounting Type	Through Hole
	Termination Style	PC Pin
Report errors?		Report errors?

ARXP1124 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ARXP1124 Payment Methods



















ARXP1124 Shipping Methods













If you have any question about ARXP1124, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com