



### **ASB110PS48 Information**

**Part Number** ASB110PS48 **Manufacturer** XP Power

**Category** Power Supplies - Board Mount

AC DC Converters

**Description** AC/DC CONVERTER 48V 110W

Package 5-DIP Module

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **ASB110PS48 Specifications**

Manufacturer         XP Power           Category         Power Supplies - Board Mount           AC DC Converters           Package         5-DIP Module           Series         ASB110           Type         Enclosed           Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         48V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         2.29A           Power (Watts)         110W           Applications         ITE (Commercial)           Features         OCP, OTP, OVP           Operating Temperature         -40°C ~ 85°C (With Derating)           Efficiency         90.5%           Mounting Type         Through Hole           Package / Case         5-DIP Module		
Category         Power Supplies - Board Mount           AC DC Converters           Package         5-DIP Module           Series         ASB110           Type         Enclosed           Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         48V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         2.29A           Power (Watts)         110W           Applications         ITE (Commercial)           Features         OCP, OTP, OVP           Operating Temperature         -40°C ~ 85°C (With Derating)           Efficiency         90.5%           Mounting Type         Through Hole           Package / Case         5-DIP Module	Manufacturer Part Number	ASB110PS48
AC DC Converters           Package         5-DIP Module           Series         ASB110           Type         Enclosed           Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         48V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         2.29A           Power (Watts)         110W           Applications         ITE (Commercial)           Features         OCP, OTP, OVP           Operating Temperature         -40°C ~ 85°C (With Derating)           Efficiency         90.5%           Mounting Type         Through Hole           Package / Case         5-DIP Module	Manufacturer	XP Power
Package         5-DIP Module           Series         ASB110           Type         Enclosed           Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         48V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         2.29A           Power (Watts)         110W           Applications         ITE (Commercial)           Features         OCP, OTP, OVP           Operating Temperature         -40°C ~ 85°C (With Derating)           Efficiency         90.5%           Mounting Type         Through Hole           Package / Case         5-DIP Module	Category	Power Supplies - Board Mount
Series         ASB110           Type         Enclosed           Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         48V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         2.29A           Power (Watts)         110W           Applications         ITE (Commercial)           Features         OCP, OTP, OVP           Operating Temperature         -40°C ~ 85°C (With Derating)           Efficiency         90.5%           Mounting Type         Through Hole           Package / Case         5-DIP Module		AC DC Converters
Type         Enclosed           Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         48V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         2.29A           Power (Watts)         110W           Applications         ITE (Commercial)           Features         OCP, OTP, OVP           Operating Temperature         -40°C ~ 85°C (With Derating)           Efficiency         90.5%           Mounting Type         Through Hole           Package / Case         5-DIP Module	Package	5-DIP Module
Number of Outputs       1         Voltage - Input       85 ~ 264 VAC         Voltage - Output 1       48V         Voltage - Output 2       -         Voltage - Output 3       -         Voltage - Output 4       -         Current - Output (Max)       2.29A         Power (Watts)       110W         Applications       ITE (Commercial)         Features       OCP, OTP, OVP         Operating Temperature       -40°C ~ 85°C (With Derating)         Efficiency       90.5%         Mounting Type       Through Hole         Package / Case       5-DIP Module	Series	ASB110
Voltage - Input  85 ~ 264 VAC  Voltage - Output 1  48V  Voltage - Output 2  - Voltage - Output 3  - Current - Output (Max)  Power (Watts)  Applications  ITE (Commercial)  Features  OCP, OTP, OVP  Operating Temperature  -40°C ~ 85°C (With Derating)  Efficiency  Mounting Type  Through Hole  Package / Case  5-DIP Module	Type	Enclosed
Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2.29A Power (Watts) 110W Applications ITE (Commercial) Features OCP, OTP, OVP Operating Temperature -40°C ~ 85°C (With Derating) Efficiency 90.5% Mounting Type Through Hole Package / Case 5-DIP Module	Number of Outputs	1
Voltage - Output 2  Voltage - Output 3  - Voltage - Output 4  - Current - Output (Max)  Power (Watts)  Applications  ITE (Commercial)  Features  OCP, OTP, OVP  Operating Temperature  -40°C ~ 85°C (With Derating)  Efficiency  Mounting Type  Package / Case  5-DIP Module	Voltage - Input	85 ~ 264 VAC
Voltage - Output 3  Voltage - Output 4  - Current - Output (Max)  Power (Watts)  Applications  ITE (Commercial)  Features  OCP, OTP, OVP  Operating Temperature  -40°C ~ 85°C (With Derating)  Efficiency  Mounting Type  Through Hole  Package / Case  5-DIP Module	Voltage - Output 1	48V
Voltage - Output 4  Current - Output (Max)  Power (Watts)  Applications  ITE (Commercial)  Features  OCP, OTP, OVP  Operating Temperature  -40°C ~ 85°C (With Derating)  Efficiency  Mounting Type  Through Hole  Package / Case  5-DIP Module	Voltage - Output 2	-
Current - Output (Max)  Power (Watts)  Applications  ITE (Commercial)  OCP, OTP, OVP  Operating Temperature  -40°C ~ 85°C (With Derating)  Efficiency  Mounting Type  Through Hole  Package / Case  2.29A  110W  OCP, OTP, OVP  OCP, OTP, OVP  -40°C ~ 85°C (With Derating)  Through Hole	Voltage - Output 3	-
Power (Watts)  Applications  ITE (Commercial)  Features  OCP, OTP, OVP  Operating Temperature  -40°C ~ 85°C (With Derating)  Efficiency  90.5%  Mounting Type  Through Hole  Package / Case  5-DIP Module	Voltage - Output 4	-
Applications ITE (Commercial)  Features OCP, OTP, OVP  Operating Temperature -40°C ~ 85°C (With Derating)  Efficiency 90.5%  Mounting Type Through Hole  Package / Case 5-DIP Module	Current - Output (Max)	2.29A
Features OCP, OTP, OVP Operating Temperature -40°C ~ 85°C (With Derating)  Efficiency 90.5%  Mounting Type Through Hole Package / Case 5-DIP Module	Power (Watts)	110W
Operating Temperature -40°C ~ 85°C (With Derating)  Efficiency 90.5%  Mounting Type Through Hole  Package / Case 5-DIP Module	Applications	ITE (Commercial)
Efficiency 90.5%  Mounting Type Through Hole  Package / Case 5-DIP Module	Features	OCP, OTP, OVP
Mounting Type Through Hole Package / Case 5-DIP Module	Operating Temperature	$-40^{\circ}$ C ~ $85^{\circ}$ C (With Derating)
Package / Case 5-DIP Module	Efficiency	90.5%
	Mounting Type	Through Hole
Size / Dimension 4.60" L x 2.40" W x 0.67" H (116.8mm x 61.0mm x 17.0mm)	Package / Case	5-DIP Module
	Size / Dimension	4.60" L x 2.40" W x 0.67" H (116.8mm x 61.0mm x 17.0mm)
Report errors?		Report errors?

#### **ASB110PS48 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **ASB110PS48 Payment Methods**



















## **ASB110PS48 Shipping Methods**













If you have any question about ASB110PS48, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com