



ASBM21BR Information

Heisener.com

Part Number ASBM21BR
Manufacturer Amphenol PCD

Category Connectors, Interconnects

Terminal Blocks - Din Rail, Channel

Description CONN TERM BLK FEED THRU 14-22AWG

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ASBM21BR Specifications

Manufacturer Part Number ASBM21BR Manufacturer Amphenol PCD Category Connectors, Interconnects Ferminal Blocks - Din Rail, Channel Terminal Blocks - Din Rail, Channel Package - Series ASBM Type Feed Through Disconnect Type - Number of Positions 3 Number of Levels 1 Terminal - Width 5.0mm Termination Style Push In, Spring Current - IEC 24A Voltage - IEC 800V Current - UL 20A Voltage - UL 600V Wire Gauge or Range - AWG 14-22 AWG Wire Gauge or Range - mm² 0.5-2.5mm² Features - Color Brown		
Category Connectors, Interconnects Terminal Blocks - Din Rail, Channel Package - Series ASBM Type Feed Through Disconnect Type - Number of Positions 3 Number of Levels 1 Terminal - Width 5.0mm Termination Style Push In, Spring Current - IEC 24A Voltage - IEC 800V Current - UL 20A Voltage - UL 600V Wire Gauge or Range - AWG 14-22 AWG Wire Gauge or Range - mm² 0.5-2.5mm² Features - Color Brown	Manufacturer Part Number	ASBM21BR
Package - Series ASBM Type Feed Through Disconnect Type - Number of Positions 3 Number of Levels 1 Terminal - Width 5.0mm Termination Style Push In, Spring Current - IEC 24A Voltage - IEC 800V Current - UL 20A Voltage - UL 600V Wire Gauge or Range - AWG 14-22 AWG Wire Gauge or Range - mm² 0.5-2.5mm² Features - Color Brown	Manufacturer	Amphenol PCD
Package - Series ASBM Type Feed Through Disconnect Type - Number of Positions 3 Number of Levels 1 Terminal - Width 5.0mm Termination Style Push In, Spring Current - IEC 24A Voltage - IEC 800V Current - UL 20A Voltage - UL 600V Wire Gauge or Range - AWG 14-22 AWG Wire Gauge or Range - mm² 0.5-2.5mm² Features - Color Brown	Category	Connectors, Interconnects
Series ASBM Type Feed Through Disconnect Type - Number of Positions 3 Number of Levels 1 Terminal - Width 5.0mm Termination Style Push In, Spring Current - IEC 24A Voltage - IEC 800V Current - UL 20A Voltage - UL 600V Wire Gauge or Range - AWG 14-22 AWG Wire Gauge or Range - mm² 0.5-2.5mm² Features - Color Brown		Terminal Blocks - Din Rail, Channel
Type Feed Through Disconnect Type - Number of Positions 3 Number of Levels 1 Terminal - Width 5.0mm Termination Style Push In, Spring Current - IEC 24A Voltage - IEC 800V Current - UL 20A Voltage - UL 600V Wire Gauge or Range - AWG 14-22 AWG Wire Gauge or Range - mm² 0.5-2.5mm² Features - Color Brown	Package	-
Disconnect Type Number of Positions 3 Number of Levels 1 Terminal - Width 5.0mm Termination Style Push In, Spring Current - IEC 24A Voltage - IEC 800V Current - UL 20A Voltage - UL 600V Wire Gauge or Range - AWG Wire Gauge or Range - mm² 0.5-2.5mm² Features Color Brown	Series	ASBM
Number of Positions3Number of Levels1Terminal - Width5.0mmTermination StylePush In, SpringCurrent - IEC24AVoltage - IEC800VCurrent - UL20AVoltage - UL600VWire Gauge or Range - AWG14-22 AWGWire Gauge or Range - mm²0.5-2.5mm²Features-ColorBrown	Туре	Feed Through
Number of Levels 1 Terminal - Width 5.0mm Termination Style Push In, Spring Current - IEC 24A Voltage - IEC 800V Current - UL 20A Voltage - UL 600V Wire Gauge or Range - AWG 14-22 AWG Wire Gauge or Range - mm² 0.5-2.5mm² Features - Color Brown	Disconnect Type	-
Terminal - Width Termination Style Push In, Spring Current - IEC 24A Voltage - IEC 800V Current - UL 20A Voltage - UL 600V Wire Gauge or Range - AWG Wire Gauge or Range - mm² Features - Color Brown	Number of Positions	3
Termination Style Current - IEC 24A Voltage - IEC 800V Current - UL 20A Voltage - UL 600V Wire Gauge or Range - AWG Wire Gauge or Range - mm² Features - Color Push In, Spring 24A 800V 800V 800V 900 800V 600V 600V Brown	Number of Levels	1
Current - IEC 24A Voltage - IEC 800V Current - UL 20A Voltage - UL 600V Wire Gauge or Range - AWG 14-22 AWG Wire Gauge or Range - mm² 0.5-2.5mm² Features - Color Brown	Terminal - Width	5.0mm
Voltage - IEC800VCurrent - UL20AVoltage - UL600VWire Gauge or Range - AWG14-22 AWGWire Gauge or Range - mm²0.5-2.5mm²Features-ColorBrown	Termination Style	Push In, Spring
Current - UL 20A Voltage - UL 600V Wire Gauge or Range - AWG 14-22 AWG Wire Gauge or Range - mm² 0.5-2.5mm² Features - Color Brown	Current - IEC	24A
Voltage - UL600VWire Gauge or Range - AWG14-22 AWGWire Gauge or Range - mm²0.5-2.5mm²Features-ColorBrown	Voltage - IEC	800V
Wire Gauge or Range - AWG Wire Gauge or Range - mm² O.5-2.5mm² Features Color Brown	Current - UL	20A
Wire Gauge or Range - mm ² Features Color Brown	Voltage - UL	600V
Features - Color Brown	Wire Gauge or Range - AWG	14-22 AWG
Color Brown	Wire Gauge or Range - mm ²	0.5-2.5mm ²
	Features	-
Poport orrors?	Color	Brown
Report errors?		Report errors?

ASBM21BR Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ASBM21BR Payment Methods





















ASBM21BR Shipping Methods













If you have any question about ASBM21BR, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com