



### **ASBM41BR Information**

Heisener.com

Part Number ASBM41BR
Manufacturer Amphenol PCD

Category Connectors, Interconnects

Terminal Blocks - Din Rail, Channel

**Description** CONN TERM BLK FEED THRU 12-22AWG

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com

Request a Quote



### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **ASBM41BR Specifications**

Manufacturer Part Number         ASBM41BR           Manufacturer         Amphenol PCD           Category         Connectors, Interconnects           Package         -           Series         ASBM           Type         Feed Through           Disconnect Type         -           Number of Positions         3           Number of Levels         1           Terminal - Width         6.0mm           Termination Style         Push In, Spring           Current - IEC         32A           Voltage - IEC         800V           Current - UL         25A           Voltage - UL         600V           Wire Gauge or Range - AWG         12-22 AWG           Wire Gauge or Range - mm²         0.5-4mm²           Features         -           Color         Brown		
Category         Connectors, Interconnects           Terminal Blocks - Din Rail, Channel           Package         -           Series         ASBM           Type         Feed Through           Disconnect Type         -           Number of Positions         3           Number of Levels         1           Terminal - Width         6.0mm           Termination Style         Push In, Spring           Current - IEC         32A           Voltage - IEC         800V           Current - UL         25A           Voltage - UL         600V           Wire Gauge or Range - AWG         12-22 AWG           Wire Gauge or Range - mm²         0.5-4mm²           Features         -           Color         Brown	Manufacturer Part Number	ASBM41BR
Package         -           Series         ASBM           Type         Feed Through           Disconnect Type         -           Number of Positions         3           Number of Levels         1           Terminal - Width         6.0mm           Termination Style         Push In, Spring           Current - IEC         32A           Voltage - IEC         800V           Current - UL         25A           Voltage - UL         600V           Wire Gauge or Range - AWG         12-22 AWG           Wire Gauge or Range - mm²         0.5-4mm²           Features         -           Color         Brown	Manufacturer	Amphenol PCD
Package         -           Series         ASBM           Type         Feed Through           Disconnect Type         -           Number of Positions         3           Number of Levels         1           Terminal - Width         6.0mm           Termination Style         Push In, Spring           Current - IEC         32A           Voltage - IEC         800V           Current - UL         25A           Voltage - UL         600V           Wire Gauge or Range - AWG         12-22 AWG           Wire Gauge or Range - mm²         0.5-4mm²           Features         -           Color         Brown	Category	Connectors, Interconnects
Series         ASBM           Type         Feed Through           Disconnect Type         -           Number of Positions         3           Number of Levels         1           Terminal - Width         6.0mm           Termination Style         Push In, Spring           Current - IEC         32A           Voltage - IEC         800V           Current - UL         25A           Voltage - UL         600V           Wire Gauge or Range - AWG         12-22 AWG           Wire Gauge or Range - mm²         0.5-4mm²           Features         -           Color         Brown		Terminal Blocks - Din Rail, Channel
Type Feed Through  Disconnect Type - Number of Positions 3 Number of Levels 1 Terminal - Width 6.0mm  Termination Style Push In, Spring  Current - IEC 32A  Voltage - IEC 800V  Current - UL 25A  Voltage - UL 600V  Wire Gauge or Range - AWG 12-22 AWG  Wire Gauge or Range - mm² 0.5-4mm²  Features - Color Brown	Package	-
Disconnect Type         -           Number of Positions         3           Number of Levels         1           Terminal - Width         6.0mm           Termination Style         Push In, Spring           Current - IEC         32A           Voltage - IEC         800V           Current - UL         25A           Voltage - UL         600V           Wire Gauge or Range - AWG         12-22 AWG           Wire Gauge or Range - mm²         0.5-4mm²           Features         -           Color         Brown	Series	ASBM
Number of Positions3Number of Levels1Terminal - Width6.0mmTermination StylePush In, SpringCurrent - IEC32AVoltage - IEC800VCurrent - UL25AVoltage - UL600VWire Gauge or Range - AWG12-22 AWGWire Gauge or Range - mm²0.5-4mm²Features-ColorBrown	Туре	Feed Through
Number of Levels         1           Terminal - Width         6.0mm           Termination Style         Push In, Spring           Current - IEC         32A           Voltage - IEC         800V           Current - UL         25A           Voltage - UL         600V           Wire Gauge or Range - AWG         12-22 AWG           Wire Gauge or Range - mm²         0.5-4mm²           Features         -           Color         Brown	Disconnect Type	-
Terminal - Width  Termination Style  Push In, Spring  Current - IEC  32A  Voltage - IEC  800V  Current - UL  25A  Voltage - UL  600V  Wire Gauge or Range - AWG  Wire Gauge or Range - mm²  Features  Color  Brown	Number of Positions	3
Termination Style  Current - IEC  32A  Voltage - IEC  800V  Current - UL  25A  Voltage - UL  600V  Wire Gauge or Range - AWG  Wire Gauge or Range - mm²  Features  -  Color  Push In, Spring  800V  800V  800V  800V  600V  600V  Brown	Number of Levels	1
Current - IEC       32A         Voltage - IEC       800V         Current - UL       25A         Voltage - UL       600V         Wire Gauge or Range - AWG       12-22 AWG         Wire Gauge or Range - mm²       0.5-4mm²         Features       -         Color       Brown	Terminal - Width	6.0mm
Voltage - IEC 800V  Current - UL 25A  Voltage - UL 600V  Wire Gauge or Range - AWG 12-22 AWG  Wire Gauge or Range - mm² 0.5-4mm²  Features - Color Brown	Termination Style	Push In, Spring
Current - UL 25A  Voltage - UL 600V  Wire Gauge or Range - AWG 12-22 AWG  Wire Gauge or Range - mm² 0.5-4mm²  Features - Color Brown	Current - IEC	32A
Voltage - UL600VWire Gauge or Range - AWG12-22 AWGWire Gauge or Range - mm²0.5-4mm²Features-ColorBrown	Voltage - IEC	800V
Wire Gauge or Range - AWG  Wire Gauge or Range - mm²  O.5-4mm²  Features  Color  Brown	Current - UL	25A
Wire Gauge or Range - mm²  Features  Color  Brown	Voltage - UL	600V
Features - Color Brown	Wire Gauge or Range - AWG	12-22 AWG
Color Brown	Wire Gauge or Range - mm <sup>2</sup>	0.5-4mm <sup>2</sup>
	Features	-
Report errors?	Color	Brown
		Report errors?

#### **ASBM41BR Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **ASBM41BR Payment Methods**



















## **ASBM41BR Shipping Methods**













If you have any question about ASBM41BR, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com