



ASBM41F Information

Heisener.com

Part Number ASBM41F
Manufacturer Amphenol PCD

Category Connectors, Interconnects

Terminal Blocks - Din Rail, Channel

Description CONN TERM BLK FEED THRU 12-22AWG

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ASBM41F Specifications

Manufacturer Part Number Manufacturer Amphenol PCD Category Connectors, Interconnects Terminal Blocks - Din Rail, Channel Package - Series ASBM Type Feed Through Disconnect Type - Number of Positions 3 Number of Levels 1 Terminal - Width 6.0mm Termination Style Push In, Spring Current - IEC 32A Voltage - IEC Voltage - IEC Current - UL Voltage - UL Wire Gauge or Range - AWG Wire Gauge or Range - AWG Wire Gauge or Range - mm² Features Color Papert agrees?		
Category Connectors, Interconnects Terminal Blocks - Din Rail, Channel Package - Series ASBM Type Feed Through Disconnect Type - Number of Positions 3 Number of Levels 1 Terminal - Width 6.0mm Termination Style Push In, Spring Current - IEC 32A Voltage - IEC 800V Current - UL 25A Voltage - UL 600V Wire Gauge or Range - AWG 12-22 AWG Wire Gauge or Range - mm² 0.5-4mm² Features - Color Orange	Manufacturer Part Number	ASBM41F
Package - Series ASBM Type Feed Through Disconnect Type - Number of Positions 3 Number of Levels 1 Terminal - Width 6.0mm Termination Style Push In, Spring Current - IEC 32A Voltage - IEC 800V Current - UL 25A Voltage - UL 600V Wire Gauge or Range - AWG 12-22 AWG Wire Gauge or Range - mm² 0.5-4mm² Features - Color Orange	Manufacturer	Amphenol PCD
Package - Series ASBM Type Feed Through Disconnect Type - Number of Positions 3 Number of Levels 1 Terminal - Width 6.0mm Termination Style Push In, Spring Current - IEC 32A Voltage - IEC 800V Current - UL 25A Voltage - UL 600V Wire Gauge or Range - AWG 12-22 AWG Wire Gauge or Range - mm² 0.5-4mm² Features - Color Orange	Category	Connectors, Interconnects
Series ASBM Type Feed Through Disconnect Type - Number of Positions 3 Number of Levels 1 Terminal - Width 6.0mm Termination Style Push In, Spring Current - IEC 32A Voltage - IEC 800V Current - UL 25A Voltage - UL 600V Wire Gauge or Range - AWG 12-22 AWG Wire Gauge or Range - mm² 0.5-4mm² Features - Color Orange		Terminal Blocks - Din Rail, Channel
Type Feed Through Disconnect Type - Number of Positions 3 Number of Levels 1 Terminal - Width 6.0mm Termination Style Push In, Spring Current - IEC 32A Voltage - IEC 800V Current - UL 25A Voltage - UL 600V Wire Gauge or Range - AWG 12-22 AWG Wire Gauge or Range - mm² 0.5-4mm² Features - Color Orange	Package	-
Disconnect Type - Number of Positions 3 Number of Levels 1 Terminal - Width 6.0mm Termination Style Push In, Spring Current - IEC 32A Voltage - IEC 800V Current - UL 25A Voltage - UL 600V Wire Gauge or Range - AWG 12-22 AWG Wire Gauge or Range - mm² 0.5-4mm² Features - Color Orange	Series	ASBM
Number of Positions3Number of Levels1Terminal - Width6.0mmTermination StylePush In, SpringCurrent - IEC32AVoltage - IEC800VCurrent - UL25AVoltage - UL600VWire Gauge or Range - AWG12-22 AWGWire Gauge or Range - mm²0.5-4mm²Features-ColorOrange	Туре	Feed Through
Number of Levels 1 Terminal - Width 6.0mm Termination Style Push In, Spring Current - IEC 32A Voltage - IEC 800V Current - UL 25A Voltage - UL 600V Wire Gauge or Range - AWG 12-22 AWG Wire Gauge or Range - mm² 0.5-4mm² Features - Color Orange	Disconnect Type	-
Terminal - Width Termination Style Push In, Spring Current - IEC 32A Voltage - IEC 800V Current - UL 25A Voltage - UL 600V Wire Gauge or Range - AWG Wire Gauge or Range - mm² Features Color Orange	Number of Positions	3
Termination Style Current - IEC 32A Voltage - IEC 800V Current - UL 25A Voltage - UL 600V Wire Gauge or Range - AWG Wire Gauge or Range - mm² Features - Color Push In, Spring 80A 800V 800V 800V 800V 600V 600V 600V 700 700	Number of Levels	1
Current - IEC 32A Voltage - IEC 800V Current - UL 25A Voltage - UL 600V Wire Gauge or Range - AWG 12-22 AWG Wire Gauge or Range - mm² 0.5-4mm² Features - Color Orange	Terminal - Width	6.0mm
Voltage - IEC800VCurrent - UL25AVoltage - UL600VWire Gauge or Range - AWG12-22 AWGWire Gauge or Range - mm²0.5-4mm²Features-ColorOrange	Termination Style	Push In, Spring
Current - UL 25A Voltage - UL 600V Wire Gauge or Range - AWG 12-22 AWG Wire Gauge or Range - mm² 0.5-4mm² Features - Color Orange	Current - IEC	32A
Voltage - UL600VWire Gauge or Range - AWG12-22 AWGWire Gauge or Range - mm²0.5-4mm²Features-ColorOrange	Voltage - IEC	800V
Wire Gauge or Range - AWG Wire Gauge or Range - mm² O.5-4mm² Features Color Orange	Current - UL	25A
Wire Gauge or Range - mm ² Features Color Orange	Voltage - UL	600V
Features - Color Orange	Wire Gauge or Range - AWG	12-22 AWG
Color Orange	Wire Gauge or Range - mm ²	0.5-4mm ²
-	Features	-
Penort errors?	Color	Orange
Report errors:		Report errors?

ASBM41F Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ASBM41F Payment Methods





















ASBM41F Shipping Methods













If you have any question about ASBM41F, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com