



ASBM62R Information

Heisener.com

Manufac

Part Number ASBM62R Manufacturer Amphenol PCD

Category Connectors, Interconnects

Terminal Blocks - Din Rail, Channel

Description CONN TERM BLK FEED THRU 8-22AWG

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ASBM62R Specifications

Manufacturer Part Number ASBM62R Manufacturer Amphenol PCD Category Connectors, Interconnects Terminal Blocks - Din Rail, Channel Package - Series ASBM Type Feed Through Disconnect Type - Number of Positions 3 Number of Levels 1 Terminal - Width 8.0mm Termination Style Push In, Spring Current - IEC 41A Voltage - IEC 800V Current - UL 50A Voltage - UL 600V Wire Gauge or Range - AWG 8-22 AWG Wire Gauge or Range - mm² 0.5-6mm² Features - Color Red		
Category Connectors, Interconnects Terminal Blocks - Din Rail, Channel Package - Series ASBM Type Feed Through Disconnect Type - Number of Positions 3 Number of Levels 1 Terminal - Width 8.0mm Termination Style Push In, Spring Current - IEC 41A Voltage - IEC 800V Current - UL 50A Voltage - UL 600V Wire Gauge or Range - AWG 8-22 AWG Wire Gauge or Range - mm² 0.5-6mm² Features - Color Red	Manufacturer Part Number	ASBM62R
Package - Series ASBM Type Feed Through Disconnect Type - Number of Positions 3 Number of Levels 1 Terminal - Width 8.0mm Termination Style Push In, Spring Current - IEC 41A Voltage - IEC 800V Current - UL 50A Voltage - UL 600V Wire Gauge or Range - AWG 8-22 AWG Wire Gauge or Range - mm² 0.5-6mm² Features - Color Red	Manufacturer	Amphenol PCD
Package - Series ASBM Type Feed Through Disconnect Type - Number of Positions 3 Number of Levels 1 Terminal - Width 8.0mm Termination Style Push In, Spring Current - IEC 41A Voltage - IEC 800V Current - UL 50A Voltage - UL 600V Wire Gauge or Range - AWG 8-22 AWG Wire Gauge or Range - mm² 0.5-6mm² Features - Color Red	Category	Connectors, Interconnects
Series ASBM Type Feed Through Disconnect Type - Number of Positions 3 Number of Levels 1 Terminal - Width 8.0mm Termination Style Push In, Spring Current - IEC 41A Voltage - IEC 800V Current - UL 50A Voltage - UL 600V Wire Gauge or Range - AWG 8-22 AWG Wire Gauge or Range - mm² 0.5-6mm² Features - Color Red		Terminal Blocks - Din Rail, Channel
Type Feed Through Disconnect Type - Number of Positions 3 Number of Levels 1 Terminal - Width 8.0mm Termination Style Push In, Spring Current - IEC 41A Voltage - IEC 800V Current - UL 50A Voltage - UL 600V Wire Gauge or Range - AWG 8-22 AWG Wire Gauge or Range - mm² 0.5-6mm² Features - Color Red	Package	-
Disconnect Type - Number of Positions 3 Number of Levels 1 Terminal - Width 8.0mm Termination Style Push In, Spring Current - IEC 41A Voltage - IEC 800V Current - UL 50A Voltage - UL 600V Wire Gauge or Range - AWG 8-22 AWG Wire Gauge or Range - mm² 0.5-6mm² Features - Color Red	Series	ASBM
Number of Positions3Number of Levels1Terminal - Width8.0mmTermination StylePush In, SpringCurrent - IEC41AVoltage - IEC800VCurrent - UL50AVoltage - UL600VWire Gauge or Range - AWG8-22 AWGWire Gauge or Range - mm²0.5-6mm²Features-ColorRed	Туре	Feed Through
Number of Levels Terminal - Width 8.0mm Termination Style Push In, Spring Current - IEC 41A Voltage - IEC 800V Current - UL 50A Voltage - UL 600V Wire Gauge or Range - AWG Wire Gauge or Range - mm² Features Color Red	Disconnect Type	-
Terminal - Width Termination Style Push In, Spring Current - IEC 41A Voltage - IEC 800V Current - UL 50A Voltage - UL 600V Wire Gauge or Range - AWG Wire Gauge or Range - mm² Features - Color Red	Number of Positions	3
Termination Style Current - IEC 41A Voltage - IEC 800V Current - UL 50A Voltage - UL 600V Wire Gauge or Range - AWG Wire Gauge or Range - mm² Features - Color Push In, Spring 41A 40A 41A 800V 800V 50A 600V 600V 8-22 AWG 8-22 AWG 8-22 AWG Red	Number of Levels	1
Current - IEC 41A Voltage - IEC 800V Current - UL 50A Voltage - UL 600V Wire Gauge or Range - AWG 8-22 AWG Wire Gauge or Range - mm² 0.5-6mm² Features - Color Red	Terminal - Width	8.0mm
Voltage - IEC 800V Current - UL 50A Voltage - UL 600V Wire Gauge or Range - AWG 8-22 AWG Wire Gauge or Range - mm² 0.5-6mm² Features - Color Red	Termination Style	Push In, Spring
Current - UL 50A Voltage - UL 600V Wire Gauge or Range - AWG 8-22 AWG Wire Gauge or Range - mm² 0.5-6mm² Features - Red	Current - IEC	41A
Voltage - UL600VWire Gauge or Range - AWG8-22 AWGWire Gauge or Range - mm²0.5-6mm²Features-ColorRed	Voltage - IEC	800V
Wire Gauge or Range - AWG Wire Gauge or Range - mm² Peatures Color Red 8-22 AWG 0.5-6mm² - Red	Current - UL	50A
Wire Gauge or Range - mm² Features Color Red 0.5-6mm² Red	Voltage - UL	600V
Features - Color Red	Wire Gauge or Range - AWG	8-22 AWG
Color Red	Wire Gauge or Range - mm ²	0.5-6mm ²
	Features	-
Report errors?	Color	Red
		Report errors?

ASBM62R Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ASBM62R Payment Methods



















ASBM62R Shipping Methods













If you have any question about ASBM62R, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com