



ASC17DRTN-S93 Information

Heisener.com

Part Number ASC17DRTN-S93

ManufacturerSullins Connector SolutionsCategoryConnectors, Interconnects

Card Edge Connectors - Edgeboard Connectors

Description CONN EDGE DUAL FMALE 34POS 0.100

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ASC17DRTN-S93 Specifications

Manufacturer Part Number ASC17DRTN-S93 Manufacturer Sullins Connector Solutions Category Connectors, Interconnects Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 17 Number of Positions 34 Card Thickness 0.093" (2.36mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Through Hole Termination Solder Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 10μin (0.25μm) Contact Type Full Bellows Color Green Flange Feature - Operating Temperature -65°C ~ 150°C	ı	
Category Connectors, Interconnects Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 17 Number of Positions 34 Card Thickness 0.093" (2.36mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Through Hole Termination Solder Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 10μin (0.25μm) Contact Type Full Bellows Color Green Flange Feature - Operating Temperature -65°C ~150°C	Manufacturer Part Number	ASC17DRTN-S93
Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 17 Number of Positions 34 Card Thickness 0.093" (2.36mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Through Hole Termination Solder Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 10μin (0.25μm) Contact Type Full Bellows Color Green Flange Feature - Operating Temperature -65°C ~ 150°C	Manufacturer	Sullins Connector Solutions
Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 17 Number of Positions 34 Card Thickness 0.093" (2.36mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Through Hole Termination Solder Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 10µin (0.25µm) Contact Type Full Bellows Color Green Flange Feature - Operating Temperature -65°C ~ 150°C	Category	Connectors, Interconnects
Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 17 Number of Positions 34 Card Thickness 0.093" (2.36mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Through Hole Termination Solder Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 10μin (0.25μm) Contact Type Full Bellows Color Green Flange Feature - Operating Temperature -65°C ~ 150°C		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row17Number of Positions34Card Thickness0.093" (2.36mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeFull BellowsColorGreenFlange Feature-Operating Temperature-65°C ~ 150°C	Package	-
Gender Female Number of Positions/Bay/Row 17 Number of Positions 34 Card Thickness 0.093" (2.36mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Through Hole Termination Solder Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 10μin (0.25μm) Cotact Type Full Bellows Color Green Flange Feature - Operating Temperature -65°C ~ 150°C	Series	-
Number of Positions/Bay/Row17Number of Positions34Card Thickness0.093" (2.36mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorGreenFlange Feature-Operating Temperature-65°C ~ 150°C	Card Type	Non Specified - Dual Edge
Number of Positions34Card Thickness0.093" (2.36mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeFull BellowsColorGreenFlange Feature-Operating Temperature-65°C ~ 150°C	Gender	Female
Card Thickness 0.093" (2.36mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Through Hole Termination Solder Contact Material Beryllium Copper Contact Finish Thickness 10µin (0.25µm) Contact Type Full Bellows Color Green Flange Feature - Operating Temperature -65°C ~ 150°C	Number of Positions/Bay/Row	17
Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeFull BellowsColorGreenFlange Feature-Operating Temperature-65°C ~ 150°C	Number of Positions	34
Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeFull BellowsColorGreenFlange Feature-Operating Temperature-65°C ~ 150°C	Card Thickness	0.093" (2.36mm)
Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeFull BellowsColorGreenFlange Feature-Operating Temperature-65°C ~ 150°C	Number of Rows	2
Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeFull BellowsColorGreenFlange Feature-Operating Temperature-65°C ~ 150°C	Pitch	0.100" (2.54mm)
TerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness $10μin (0.25μm)$ Contact TypeFull BellowsColorGreenFlange Feature-Operating Temperature -65 °C ~ 150 °C	Features	-
Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeFull BellowsColorGreenFlange Feature-Operating Temperature-65°C ~ 150°C	Mounting Type	Through Hole
Contact Finish Contact Finish Thickness $10\mu in (0.25\mu m)$ Contact Type Full Bellows Color Green Flange Feature Operating Temperature Gold $10\mu in (0.25\mu m)$ Full Bellows $-65^{\circ}C \sim 150^{\circ}C$	Termination	Solder
Contact Finish Thickness $10\mu in (0.25\mu m)$ Contact Type Full Bellows Color Green Flange Feature - 65°C ~ 150°C	Contact Material	Beryllium Copper
Contact Type Full Bellows Color Green Flange Feature Operating Temperature -65°C ~ 150°C	Contact Finish	Gold
Color Green Flange Feature -65°C ~ 150°C	Contact Finish Thickness	10μin (0.25μm)
Flange Feature - Gerating Temperature - $65^{\circ}\text{C} \sim 150^{\circ}\text{C}$	Contact Type	Full Bellows
Operating Temperature $-65^{\circ}\text{C} \sim 150^{\circ}\text{C}$	Color	Green
	Flange Feature	-
	Operating Temperature	-65°C ~ 150°C
Report errors?		Report errors?

ASC17DRTN-S93 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ASC17DRTN-S93 Payment Methods



















ASC17DRTN-S93 Shipping Methods













If you have any question about ASC17DRTN-S93, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com