

ASC26DREI-S13

ASC26DREI-S13 Information

Heisener.com	 ASC26DREI-S13 Sullins Connector Solutions Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors CONN EDGE DUAL FMALE 52POS 0.100 - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



ASC26DREI-S13 Specifications

ManufacturerSullins Connector SolutionsCardegerConnectors, InterconnectsPackage-Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row26Number of Positions0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolder Eyelet(s)Contact Finish ThicknessIojui (0.25µm)Contact Finish ThicknessIojui (0.25µm)Contact TypeFull BellowsContact TypeGoldContact TypeIojui (0.25µm)Contact Finish ThicknessIojui (0.25µm)Contact TypeFull BellowsContact TypeFull BellowsContact TypeIojui (0.25µm)Contact TypeFull BellowsContact TypeFull BellowsContact TypeIojui (0.25µm)Contact TypeFull BellowsContact TypeIojui (0.25µm)Contact TypeIojui (0.25µm)Contact TypeIojui (0.25µm)Contact TypeIojui (0.25µm)Contact TypeIojui (0.25µm)Contact TypeIojui (0.25µ		
CategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row26Number of Positions0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolder Eyelet(s)Contact Finish ThicknessIoyin (0.25µm)Contact Finish ThicknessIoyin (0.25µm)Contact TypeFull BellowsContact TypeGoldContact TypeFull BellowsContact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 150°C	Manufacturer Part Number	ASC26DREI-S13
Card Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row26Number of Positions52Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolder Eyelet(s)Contact Finish Thickness10µin (0.25µm)Contact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 150°C	Manufacturer	Sullins Connector Solutions
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row26Number of Positions52Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolder Eyelet(s)Contact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-55°C ~ 150°C	Category	Connectors, Interconnects
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row26Number of Positions52Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolder Eyelet(s)Contact Finish ThicknessGoldContact Finish ThicknessIupin (0.25µm)Contact TypeFeil BellowsContact TypeGoldContact TypeTop Mount Opening, Threaded Insert, 4-40Flange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-55°C ~ 150°C		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row26Number of Positions52Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolder Eyelet(s)Contact FinishGoldContact Finish ThicknessIupin (0.25µm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 150°C	Package	-
GenderFemaleNumber of Positions/Bay/Row26Number of Positions52Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolder Eyelet(s)Contact FinishGoldContact TypeJupin (0.25µm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 150°C	Series	-
Number of Positions/Bay/Row26Number of Positions52Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolder Eyelet(s)Contact FinishGoldContact Finish Thickness0µin (0.25µm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-55°C ~ 150°C	Card Type	Non Specified - Dual Edge
Number of Positions 52 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features Card Extender Mounting Type Board Edge, Straddle Mount Termination Solder Eyelet(s) Contact Material Gold Contact Finish Thickness Ioµin (0.25µm) Contact Type Full Bellows Color Green Flange Feature Top Mount Opening, Threaded Insert, 4-40 Operating Temperature -65°C ~ 150°C	Gender	Female
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolder Eyelet(s)Contact MaterialBoryllium CopperContact Finish ThicknessGoldContact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 150°C	Number of Positions/Bay/Row	26
Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolder Eyelet(s)Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 150°C	Number of Positions	52
Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolder Eyelet(s)Contact MaterialBeryllium CopperContact Finish ThicknessGoldContact Finish Thickness10µin (0.25µm)ColorFull BellowsColorGreenFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 150°C	Card Thickness	0.062" (1.57mm)
FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolder Eyelet(s)Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 150°C	Number of Rows	2
Mounting TypeBoard Edge, Straddle MountTerminationSolder Eyelet(s)Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 150°C	Pitch	0.100" (2.54mm)
TerminationSolder Eyelet(s)Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 150°C	Features	Card Extender
Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 150°C	Mounting Type	Board Edge, Straddle Mount
Contact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 150°C	Termination	Solder Eyelet(s)
Contact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 150°C	Contact Material	Beryllium Copper
Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 150°C	Contact Finish	Gold
Color Green Flange Feature Top Mount Opening, Threaded Insert, 4-40 Operating Temperature -65°C ~ 150°C	Contact Finish Thickness	10µin (0.25µm)
Flange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 150°C	Contact Type	Full Bellows
Operating Temperature $-65^{\circ}\text{C} \sim 150^{\circ}\text{C}$	Color	Green
	Flange Feature	Top Mount Opening, Threaded Insert, 4-40
Report errors?	Operating Temperature	-65°C ~ 150°C
		Report errors?

ASC26DREI-S13 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

ASC26DREI-S13 Payment Methods



ASC26DREI-S13 Shipping Methods



If you have any question about ASC26DREI-S13, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com