

# ASC65DRTN-S734

Quote

#### **ASC65DRTN-S734 Information**

	Part Number	ASC65DRTN-S734	
	Manufacturer	Sullins Connector Solutions	<b>E</b> 15 <b>2</b> 5
Heisener.com	Category	Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors	11000000000000000000000000000000000000
	Description	CONN EDGE DUAL FMALE 130POS .100	
	Package	-	
		For the pricing/inventory/lead time, please contact	E17782
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



### **ASC65DRTN-S734 Specifications**

Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row65Number of Positions130Card Thickness0.031" (0.79mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact Finish ThicknessIojui (0.25µm)Contact Finish ThicknessFeallewsContact TypeGoldContact TypeIojui (0.25µm)Contact TypeSille BellowsColorGreenFlange Feature-Operating Temperature-65°C ~ 150°C	-	
CategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row65Number of Positions130Card Thickness0.031" (0.79mm)Number of Rows2Pitch0.100" (2.54mm)Features-Nounting TypeThrough HoleContact MaterialSolderContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsContact TypeGuldContact TypeSolderContact TypeSol	Manufacturer Part Number	ASC65DRTN-S734
Card Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row65Number of Positions130Card Thickness0.031" (0.79mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact Finish Thickness10/uin (0.25µm)Contact Finish Thickness10/uin (0.25µm)Contact TypeFull BellowsColorGreenFlange Feature-Operating Temperature-65°C ~ 150°C	Manufacturer	Sullins Connector Solutions
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row65Number of Positions130Card Thickness0.031" (0.79mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact Finish Thickness10/uin (0.25µm)Contact TypeFull BellowsContact Type5Flange Feature-Folge Feature-Folge Feature-SolderGreenFlange Feature-Solder	Category	Connectors, Interconnects
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row65Number of Positions130Card Thickness0.031" (0.79mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact Finish ThicknessIojui (0.25µm)Contact Finish ThicknessFeallewsContact TypeGoldContact TypeIojui (0.25µm)Contact TypeSille BellowsColorGreenFlange Feature-Operating Temperature-65°C ~ 150°C		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row65Number of Positions130Card Thickness0.031" (0.79mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact Finish ThicknessGoldContact Finish ThicknessFull BellowsContact TypeFull BellowsColorGreenFlange Feature-Operating Temperature65°C ~ 15°C	Package	-
GenderFemaleNumber of Positions/Bay/Row65Number of Positions130Card Thickness0.031°(0.79mm)Number of Rows2Pitch0.100°(2.54mm)Features-Mounting Type010°(2.54mm)Contact FinishSolderContact FinishGoldContact Finish ThicknessGoldContact TypeFull BellowsColorGreenFlange Feature-Operating Temperature65°C~150°C	Series	-
Number of Positions/Bay/Row65Number of Positions130Card Thickness0.031" (0.79mm)Card Thickness2Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialGoldContact Finish ThicknessIujin (0.25µm)Contact Finish ThicknessFull BellowsColorGreenFlange Feature-Operating Temperature-5°C ~ 150°C	Card Type	Non Specified - Dual Edge
Number of Positions 130   Card Thickness 0.031" (0.79mm)   Number of Rows 2   Pitch 0.100" (2.54mm)   Features -   Mounting Type Through Hole   Termination Solder   Contact Material Beryllium Copper   Contact Finish Gold   Contact Type Full Bellows   Color Green   Flange Feature -   Operating Temperature -	Gender	Female
Card Thickness0.031" (0.79mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact Finish ThicknessGoldContact TypeFull BellowsColorGreenFlange Feature-Operating Temperature65°C ~ 150°C	Number of Positions/Bay/Row	65
Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish ThicknessJujin (0.25µm)Contact TypeFull BellowsColorGreenFlange Feature-Operating Temperature-65°C ~ 150°C	Number of Positions	130
Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact Finish ThicknessGoldContact TypeIupin (0.25µm)ColorFull BellowsColorGreenFlange Feature-Operating Temperature65°C ~ 150°C	Card Thickness	0.031" (0.79mm)
Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish ThicknessI/lµin (0.25µm)Contact TypeFul BellowsColorGreenFlange Feature-Operating Tomperatures-Solder- <td>Number of Rows</td> <td>2</td>	Number of Rows	2
Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorGreenFlange Feature-Operating Temperature-55°C ~ 150°C	Pitch	0.100" (2.54mm)
TerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorGreenFlange Feature-Operating Temperature-65°C ~ 150°C	Features	-
Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorGreenFlange Feature-Operating Temperature-65°C ~ 150°C	Mounting Type	Through Hole
Contact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorGreenFlange Feature-Operating Temperature-65°C ~ 150°C	Termination	Solder
Contact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorGreenFlange Feature-Operating Temperature-65°C ~ 150°C	Contact Material	Beryllium Copper
Contact TypeFull BellowsColorGreenFlange Feature-Operating Temperature-65°C ~ 150°C	Contact Finish	Gold
ColorGreenFlange Feature-Operating Temperature-65°C ~ 150°C	Contact Finish Thickness	10µin (0.25µm)
Flange Feature-Operating Temperature-65°C ~ 150°C	Contact Type	Full Bellows
Operating Temperature $-65^{\circ}\text{C} \sim 150^{\circ}\text{C}$	Color	Green
	Flange Feature	-
Report errors?	Operating Temperature	-65°C ~ 150°C
		Report errors?

#### ASC65DRTN-S734 Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE BUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### ASC65DRTN-S734 Payment Methods





If you have any question about ASC65DRTN-S734, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com