

ASD1-11.0592MHZ-EC-T

ASD1-11.0592MHZ-EC-T Information



Part Number	ASD1-11.0592MHZ-EC-T	
Manufacturer	Abracon LLC	
Category	Crystals, Oscillators, Resonators Oscillators	
Description	OSC XO 11.0592MHZ CMOS SMD	
Package	age 4-SMD, No Lead For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



ASD1-11.0592MHZ-EC-T Specifications

ManufacturerAbracon LLCCategoryCrystals, Oscillators, ResonatorsOscillatorsOscillatorsPackage4-SMD, No LeadSeriesASDTypeXO (Standard)Frequency11.0592MHzFunctionEnable/DisableOutputHCMOSVoltage - Supply3VFrequency Stability5.5mACurrent - Supply (Max)5.5mARatings-AddataSurface MountPackage / Case4.SMD, No LeadSize / Dimension0.098" L x 0.079" W (2.50mm x 2.00mm)		
CategoryCrystals, Oscillators, ResonatorsOscillatorsPackage4-SMD, No LeadSeriesASDTypeXO (Standard)Frequency11.0592MHzFunctionEnable/DisableOutputHCMOSVoltage - Supply3VFrequency Stability±50ppmOperating Temperature-20°C ~ 70°CCurrent - Supply (Max)5.5mARatings-Package / Case4-SMD, No LeadSize / Dimension0.098" L x 0.079" W (2.50mm x 2.00mm)Height - Seated (Max)0.039" (1.00mm)	Manufacturer Part Number	ASD1-11.0592MHZ-EC-T
OscillatorsPackage4-SMD, No LeadPackageASDSpriesASDTypeXO (Standard)Frequency11.0592MHzFunctionEnable/DisableDutputHCMOSVoltage - Supply3VFrequency Stability-20°C ~ 70°CCurrent - Supply (Max)5.5mARatings-Package / Case4.SMD, No LeadSize / Dimension0.098" L x 0.079" W (2.50mm x 2.00mm)Height - Seated (Max)0.039" (1.00mm)	Manufacturer	Abracon LLC
Package4-SMD, No LeadSeriesASDSoriesASDTypeXO (Standard)Frequency11.0592MHzFunctionEnable/DisableOutputHCMOSVoltage - Supply3VFrequency Stability±50pmOperating Temperature-0°C ~ 70°CCurrent - Supply (Max)5.5mARatings-Mounting TypeSurface MountPackage / Case4.SMD, No LeadSize / Dimension0.098" L x 0.079" W (2.50mm x 2.00mm)Height - Seated (Max)0.039" (1.00mm)	Category	Crystals, Oscillators, Resonators
ASDTypeXO (Standard)Frequency11.0592MHzFunctionEnable/DisableOutputHCMOSVoltage - Supply3VFrequency Stability±50ppmOperating Temperature-20°C ~ 70°CCurrent - Supply (Max)Surface MountRatings-Package / Case4-SMD, No LeadSize / Dimension0.039" (1.00mm)		Oscillators
TypeXO (Standard)Frequency11.0592MHzFunctionEnable/DisableOutputHCMOSVoltage - Supply3VFrequency Stability±50ppmOperating Temperature-0°C ~ 70°CCurrent - Supply (Max)5.5mARatings-Mounting TypeSurface MountPackage / Case4.SMD, No LeadSize / Dimension0.098" L x 0.079" W (2.50mm x 2.00mm)Height - Seated (Max)0.039" (1.00mm)	Package	4-SMD, No Lead
Frequency 11.0592MHz Function Enable/Disable Output HCMOS Voltage - Supply 3V Frequency Stability ±50ppm Operating Temperature -20°C ~ 70°C Current - Supply (Max) 5.5mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.098" L x 0.079" W (2.50mm x 2.00mm) Height - Seated (Max) 0.039" (1.00mm)	Series	ASD
FunctionEnable/DisableFunctionHCMOSOutput3VVoltage - Supply±50ppmFrequency Stability±50ppmOperating Temperature-20°C ~ 70°CCurrent - Supply (Max)5.5mARatings-Mounting TypeSurface MountPackage / Case4-SMD, No LeadSize / Dimension0.098" L x 0.079" W (2.50mm x 2.00mm)	Туре	XO (Standard)
OutputHCMOSVoltage - Supply3VFrequency Stability±50pmOperating Temperature-20°C ~ 70°CCurrent - Supply (Max)5.5mARatings-Mounting TypeSurface MountPackage / Case4.SMD, No LeadSize / Dimension0.098" L x 0.079" W (2.50mm x 2.00mm)Height - Seated (Max)0.039" (1.00mm)	Frequency	11.0592MHz
Voltage - Supply3VFrequency Stability±50ppmOperating Temperature-20°C ~ 70°CCurrent - Supply (Max)5.5mARatings-Mounting TypeSurface MountPackage / Case4-SMD, No LeadSize / Dimension0.098" L x 0.079" W (2.50mm x 2.00mm)Height - Seated (Max)0.039" (1.00mm)	Function	Enable/Disable
Frequency Stability±50ppmOperating Temperature-20°C ~ 70°CCurrent - Supply (Max)5.5mARatings-Mounting TypeSurface MountPackage / Case4-SMD, No LeadSize / Dimension0.098" L x 0.079" W (2.50mm x 2.00mm)Height - Seated (Max)0.039" (1.00mm)	Output	HCMOS
Operating Temperature-20°C ~ 70°CCurrent - Supply (Max)5.5mARatings-Mounting TypeSurface MountPackage / Case4-SMD, No LeadSize / Dimension0.098" L x 0.079" W (2.50mm x 2.00mm)Height - Seated (Max)0.039" (1.00mm)	Voltage - Supply	3V
Current - Supply (Max)5.5mARatings-Mounting TypeSurface MountPackage / Case4-SMD, No LeadSize / Dimension0.098" L x 0.079" W (2.50mm x 2.00mm)Height - Seated (Max)0.039" (1.00mm)	Frequency Stability	±50ppm
Ratings-Mounting TypeSurface MountPackage / Case4-SMD, No LeadSize / Dimension0.098" L x 0.079" W (2.50mm x 2.00mm)Height - Seated (Max)0.039" (1.00mm)	Operating Temperature	-20°C ~ 70°C
Mounting TypeSurface MountPackage / Case4-SMD, No LeadSize / Dimension0.098" L x 0.079" W (2.50mm x 2.00mm)Height - Seated (Max)0.039" (1.00mm)	Current - Supply (Max)	5.5mA
Package / Case 4-SMD, No Lead Size / Dimension 0.098" L x 0.079" W (2.50mm x 2.00mm) Height - Seated (Max) 0.039" (1.00mm)	Ratings	-
Size / Dimension 0.098" L x 0.079" W (2.50mm x 2.00mm) Height - Seated (Max) 0.039" (1.00mm)	Mounting Type	Surface Mount
Height - Seated (Max) 0.039" (1.00mm)	Package / Case	4-SMD, No Lead
-	Size / Dimension	0.098" L x 0.079" W (2.50mm x 2.00mm)
Report errors?	Height - Seated (Max)	0.039" (1.00mm)
		Report errors?

ASD1-11.0592MHZ-EC-T Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

ASD1-11.0592MHZ-EC-T Payment Methods



If you have any question about ASD1-11.0592MHZ-EC-T, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com