

ASDXRRX005PD7A5

ASDXRRX005PD7A5 Information

Heisener.com

Part Number ASDXRRX005PD7A5

Manufacturer Honeywell Sensing and Productivity Solutions

Category Sensors, Transducers

Pressure Sensors, Transducers

Description SENSOR PRESS 5PSID ANALOG

Package 8-DIP Module

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ASDXRRX005PD7A5 Specifications

Manufacturer Part Number ASDXRRX005PD7A5 Manufacturer Honeywell Sensing and Productivity Solutions Category Sensors, Transducers Package 8-DIP Module Series ASDX Pressure Type Differential Operating Pressure ±5 PSI (±34.47 kPa) Output Type I2C Output 12 b Accuracy ±2% Voltage - Supply 4.75 V ~ 5.25 V Port Size Male - 0.09" (2.31mm) Tube, Dual Port Style Barbless Features Temperature Compensated Termination Style PCB Maximum Pressure ±10 PSI (±68.95 kPa) Operating Temperature -20°C ~ 105°C Package / Case 8-DIP Module Supplier Device Package - Report errors?		
Category Sensors, Transducers Pressure Sensors, Transducers Package 8-DIP Module Series ASDX Pressure Type Differential Operating Pressure ±5 PSI (±34.47 kPa) Output Type 12C Output 12 b Accuracy ±2% Voltage - Supply 4.75 V ~ 5.25 V Port Size Male - 0.09" (2.31mm) Tube, Dual Port Style Barbless Features Temmination Style Maximum Pressure ±10 PSI (±68.95 kPa) Operating Temperature Package / Case 8-DIP Module Supplier Device Package	Manufacturer Part Number	ASDXRRX005PD7A5
Package 8-DIP Module Series ASDX Pressure Type Differential Operating Pressure ±5 PSI (±34.47 kPa) Output Type 12C Output 12 b Accuracy ±2% Voltage - Supply 4.75 V ~ 5.25 V Port Size Male - 0.09" (2.31mm) Tube, Dual Port Style Barbless Features Temperature Compensated Termination Style PCB Maximum Pressure ±10 PSI (±68.95 kPa) Operating Temperature -20°C ~ 105°C Package / Case 8-DIP Module Supplier Device Package -	Manufacturer	Honeywell Sensing and Productivity Solutions
Package 8-DIP Module Series ASDX Pressure Type Differential Operating Pressure ±5 PSI (±34.47 kPa) Output Type I2C Output 12 b Accuracy ±2% Voltage - Supply 4.75 V ~ 5.25 V Port Size Male - 0.09" (2.31mm) Tube, Dual Port Style Barbless Features Temperature Compensated Termination Style PCB Maximum Pressure ±10 PSI (±68.95 kPa) Operating Temperature -20°C ~ 105°C Package / Case 8-DIP Module Supplier Device Package -	Category	Sensors, Transducers
Series ASDX Pressure Type Differential Operating Pressure		Pressure Sensors, Transducers
Pressure Type Differential Operating Pressure ±5 PSI (±34.47 kPa) Output Type 12C Output 12 b Accuracy ±2% Voltage - Supply 4.75 V ~ 5.25 V Port Size Male - 0.09" (2.31mm) Tube, Dual Port Style Barbless Features Temperature Compensated Termination Style PCB Maximum Pressure ±10 PSI (±68.95 kPa) Operating Temperature Package Supplier Device Package	Package	8-DIP Module
Operating Pressure ±5 PSI (±34.47 kPa) Output Type 12C Output 12 b Accuracy ±2% Voltage - Supply 4.75 V ~ 5.25 V Port Size Male - 0.09" (2.31mm) Tube, Dual Port Style Barbless Features Temperature Compensated Termination Style PCB Maximum Pressure ±10 PSI (±68.95 kPa) Operating Temperature -20°C ~ 105°C Package / Case 8-DIP Module Supplier Device Package -	Series	ASDX
Output TypeI2COutput12 bAccuracy±2%Voltage - Supply4.75 V ~ 5.25 VPort SizeMale - 0.09" (2.31mm) Tube, DualPort StyleBarblessFeaturesTemperature CompensatedTermination StylePCBMaximum Pressure±10 PSI (±68.95 kPa)Operating Temperature-20°C ~ 105°CPackage / Case8-DIP ModuleSupplier Device Package-	Pressure Type	Differential
Output Accuracy ±2% Voltage - Supply A.75 V ~ 5.25 V Port Size Male - 0.09" (2.31mm) Tube, Dual Port Style Barbless Features Temperature Compensated Termination Style PCB Maximum Pressure ±10 PSI (±68.95 kPa) Operating Temperature -20°C ~ 105°C Package / Case 8-DIP Module Supplier Device Package -	Operating Pressure	±5 PSI (±34.47 kPa)
Accuracy ±2% Voltage - Supply 4.75 V ~ 5.25 V Port Size Male - 0.09" (2.31mm) Tube, Dual Port Style Barbless Features Temperature Compensated Termination Style PCB Maximum Pressure ±10 PSI (±68.95 kPa) Operating Temperature -20°C ~ 105°C Package / Case 8-DIP Module Supplier Device Package	Output Type	12C
Voltage - Supply 4.75 V ~ 5.25 V Port Size Male - 0.09" (2.31mm) Tube, Dual Port Style Barbless Features Temperature Compensated Termination Style PCB Maximum Pressure ±10 PSI (±68.95 kPa) Operating Temperature -20°C ~ 105°C Package / Case 8-DIP Module Supplier Device Package	Output	12 b
Port Size Male - 0.09" (2.31mm) Tube, Dual Port Style Barbless Features Temperature Compensated Termination Style PCB Maximum Pressure ±10 PSI (±68.95 kPa) Operating Temperature -20°C ~ 105°C Package / Case 8-DIP Module Supplier Device Package -	Accuracy	±2%
Port Style Barbless Features Temperature Compensated Termination Style PCB Maximum Pressure ±10 PSI (±68.95 kPa) Operating Temperature -20°C ~ 105°C Package / Case 8-DIP Module Supplier Device Package -	Voltage - Supply	4.75 V ~ 5.25 V
FeaturesTemperature CompensatedTermination StylePCBMaximum Pressure ± 10 PSI (± 68.95 kPa)Operating Temperature $-20^{\circ}\text{C} \sim 105^{\circ}\text{C}$ Package / Case8-DIP ModuleSupplier Device Package-	Port Size	Male - 0.09" (2.31mm) Tube, Dual
Termination Style PCB Maximum Pressure ± 10 PSI (± 68.95 kPa) Operating Temperature $-20^{\circ}\text{C} \sim 105^{\circ}\text{C}$ Package / Case 8-DIP Module Supplier Device Package -	Port Style	Barbless
Maximum Pressure ± 10 PSI (± 68.95 kPa) Operating Temperature $-20^{\circ}\text{C} \sim 105^{\circ}\text{C}$ Package / Case 8-DIP Module Supplier Device Package -	Features	Temperature Compensated
Operating Temperature -20°C ~ 105°C Package / Case 8-DIP Module Supplier Device Package -	Termination Style	PCB
Package / Case 8-DIP Module Supplier Device Package -	Maximum Pressure	±10 PSI (±68.95 kPa)
Supplier Device Package -	Operating Temperature	-20°C ~ 105°C
	Package / Case	8-DIP Module
Report errors?	Supplier Device Package	-
		Report errors?

ASDXRRX005PD7A5 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ASDXRRX005PD7A5 Payment Methods



















ASDXRRX005PD7A5 Shipping Methods













If you have any question about ASDXRRX005PD7A5, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com