

ASEMPHC-BLANK-LR-T

ASEMPHC-BLANK-LR-T Information



For Reference Only

Part Number ASEMPHC-BLANK-LR-T

Manufacturer Abracon LLC

Category Crystals, Oscillators, Resonators

Programmable Oscillators

Description OSC MEMS 3.2X2.5 HCSL BLANK

Package 6-SMD, No Lead

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ASEMPHC-BLANK-LR-T Specifications

Manufacturer Part Number ASEMPHC-BLANK-LR-T Manufacturer Abracon LLC Category Crystals, Oscillators, Resonators Package 6-SMD, No Lead Series Pure Silicon? ASEMP Type MEMS (Silicon) Programmable Type Blank (User Must Program) Available Frequency Range 2.3MHz ~ 460MHz Function Enable/Disable Output HCSL Voltage - Supply 2.25 V ~ 3.6 V Frequency Stability - Frequency Stability (Total) ±25ppm Operating Temperature 40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) 42mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height 0.035" (0.90mm)		
Category Crystals, Oscillators, Resonators Package 6-SMD, No Lead Series Pure Silicon? ASEMP Type MEMS (Silicon) Programmable Type Blank (User Must Program) Available Frequency Range 2.3MHz ~ 460MHz Function Enable/Disable Output HCSL Voltage - Supply 2.25 V ~ 3.6 V Frequency Stability - Frequency Stability (Total) ±25ppm Operating Temperature -40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) 42mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height 0.035" (0.90mm)	Manufacturer Part Number	ASEMPHC-BLANK-LR-T
Package 6-SMD, No Lead Series Pure Silicon? ASEMP Type MEMS (Silicon) Programmable Type Blank (User Must Program) Available Frequency Range 2.3MHz ~ 460MHz Function Enable/Disable Output HCSL Voltage - Supply 2.25 V ~ 3.6 V Frequency Stability - Frequency Stability (Total) ±25ppm Operating Temperature -40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) 42mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height 0.035" (0.90mm)	Manufacturer	Abracon LLC
Package 6-SMD, No Lead Series Pure Silicon? ASEMP Type MEMS (Silicon) Programmable Type Blank (User Must Program) Available Frequency Range 2.3MHz ~ 460MHz Function Enable/Disable Output HCSL Voltage - Supply 2.25 V ~ 3.6 V Frequency Stability - Frequency Stability (Total) ±25ppm Operating Temperature -40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) 42mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height 0.035" (0.90mm)	Category	Crystals, Oscillators, Resonators
Series Pure Silicon? ASEMP Type MEMS (Silicon) Programmable Type Blank (User Must Program) Available Frequency Range 2.3MHz ~ 460MHz Function Enable/Disable Output HCSL Voltage - Supply 2.25 V ~ 3.6 V Frequency Stability - Frequency Stability (Total) ±25ppm Operating Temperature -40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) 42mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height 0.035" (0.90mm)		Programmable Oscillators
Type MEMS (Silicon) Programmable Type Blank (User Must Program) Available Frequency Range 2.3MHz ~ 460MHz Function Enable/Disable Output HCSL Voltage - Supply 2.25 V ~ 3.6 V Frequency Stability - Frequency Stability (Total) ±25ppm Operating Temperature 4.0°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) 42mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height 0.035" (0.90mm)	Package	6-SMD, No Lead
Programmable Type Available Frequency Range 2.3MHz ~ 460MHz Function Enable/Disable Output HCSL Voltage - Supply 2.25 V ~ 3.6 V Frequency Stability - Frequency Stability (Total) Operating Temperature -40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.035" (0.90mm)	Series	Pure Silicon? ASEMP
Available Frequency Range 2.3MHz ~ 460MHz Function Enable/Disable Output HCSL Voltage - Supply 2.25 V ~ 3.6 V Frequency Stability - Frequency Stability (Total) 425ppm Operating Temperature -40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height	Туре	MEMS (Silicon)
Function Enable/Disable Output HCSL Voltage - Supply 2.25 V ~ 3.6 V Frequency Stability - Frequency Stability (Total) ±25ppm Operating Temperature -40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) 42mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height 0.005" (0.90mm)	Programmable Type	Blank (User Must Program)
Output HCSL Voltage - Supply 2.25 V ~ 3.6 V Frequency Stability - Frequency Stability (Total) ±25ppm Operating Temperature -40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) 42mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height 0.035" (0.90mm)	Available Frequency Range	2.3MHz ~ 460MHz
Voltage - Supply 2.25 V ~ 3.6 V Frequency Stability	Function	Enable/Disable
Frequency Stability (Total) ±25ppm Operating Temperature -40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) 42mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height 0.035" (0.90mm)	Output	HCSL
Frequency Stability (Total) Operating Temperature -40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height 425ppm -40°C ~ 85°C -40°C ~ 85°C - Surface Mount - Current - Supply (Max) - Current - Supply (Voltage - Supply	2.25 V ~ 3.6 V
Operating Temperature -40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height 0.035" (0.90mm)	Frequency Stability	-
Spread Spectrum Bandwidth Current - Supply (Max) Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height 0.035" (0.90mm)	Frequency Stability (Total)	±25ppm
Current - Supply (Max) Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height 0.035" (0.90mm)	Operating Temperature	-40°C ~ 85°C
Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height 0.035" (0.90mm)	Spread Spectrum Bandwidth	-
Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height 0.035" (0.90mm)	Current - Supply (Max)	42mA
Package / Case 6-SMD, No Lead Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height 0.035" (0.90mm)	Ratings	-
Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height 0.035" (0.90mm)	Mounting Type	Surface Mount
Height 0.035" (0.90mm)	Package / Case	6-SMD, No Lead
, ,	Size / Dimension	0.126" L x 0.098" W (3.20mm x 2.50mm)
Report errors?	Height	0.035" (0.90mm)
		Report errors?

ASEMPHC-BLANK-LR-T Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ASEMPHC-BLANK-LR-T Payment Methods



















ASEMPHC-BLANK-LR-T Shipping Methods













If you have any question about ASEMPHC-BLANK-LR-T, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com