

ASFLMPC-24.000MHZ-Z-T

ASFLMPC-24.000MHZ-Z-T Information

Part Number ASFLMPC-24.000MHZ-Z-T

Manufacturer Abracon LLC

Category Crystals, Oscillators, Resonators

Oscillators

Description OSC MEMS 24.000MHZ CMOS SMD

Package 6-SMD, No Lead

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ASFLMPC-24.000MHZ-Z-T Specifications

Manufacturer Part NumberASFLMPC-24.000MHZ-Z-TManufacturerAbracon LLCCategoryCrystals, Oscillators, ResonatorsPackage6-SMD, No LeadSeriesPure Silicon? ASFLMPTypeMEMS (Silicon)Frequency24MHzFunctionEnable/DisableOutputCMOSVoltage - Supply2.25 V ~ 3.6 VFrequency Stability±50pmOperating Temperature-55°C ~ 125°CCurrent - Supply (Max)35mARatings-Mounting TypeSurface MountPackage / Case6-SMD, No LeadSize / Dimension0.197" L x 0.126" W (5.00mm x 3.20mm)Height - Seated (Max)0.035" (0.90mm)		
Category Crystals, Oscillators, Resonators Oscillators Package 6-SMD, No Lead Series Pure Silicon? ASFLMP Type MEMS (Silicon) Frequency 24MHz Function Enable/Disable Output CMOS Voltage - Supply 2.25 V ~ 3.6 V Frequency Stability ±50ppm Operating Temperature -55°C ~ 125°C Current - Supply (Max) 35mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.035" (0.90mm) Cesillators No Lead Size / Supply Coscillators, Resonators Oscillators Package (Sabe) 6-SMD, No Lead Size / Dimension 0.035" (0.90mm)	Manufacturer Part Number	ASFLMPC-24.000MHZ-Z-T
Package 6-SMD, No Lead Series Pure Silicon? ASFLMP Type MEMS (Silicon) Frequency 24MHz Function Enable/Disable Output CMOS Voltage - Supply 2.25 V ~ 3.6 V Frequency Stability ±50ppm Operating Temperature -55°C ~ 125°C Current - Supply (Max) 35mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height - Seated (Max) 0.035" (0.90mm)	Manufacturer	Abracon LLC
Package 6-SMD, No Lead Series Pure Silicon? ASFLMP Type MEMS (Silicon) Frequency 24MHz Function Enable/Disable Output CMOS Voltage - Supply 2.25 V ~ 3.6 V Frequency Stability ±50ppm Operating Temperature -55°C ~ 125°C Current - Supply (Max) 35mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height - Seated (Max) 0.035" (0.90mm)	Category	Crystals, Oscillators, Resonators
Series Pure Silicon? ASFLMP Type MEMS (Silicon) Frequency 24MHz Function Enable/Disable Output CMOS Voltage - Supply 2.25 V ~ 3.6 V Frequency Stability ±50ppm Operating Temperature -55°C ~ 125°C Current - Supply (Max) 35mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height - Seated (Max) 0.035" (0.90mm)		Oscillators
Type MEMS (Silicon) Frequency 24MHz Function Enable/Disable Output CMOS Voltage - Supply 2.25 V ~ 3.6 V Frequency Stability ±50ppm Operating Temperature -55°C ~ 125°C Current - Supply (Max) 35mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height - Seated (Max) 0.035" (0.90mm)	Package	6-SMD, No Lead
Frequency 24MHz Function Enable/Disable Output CMOS Voltage - Supply 2.25 V ~ 3.6 V Frequency Stability ±50ppm Operating Temperature -55°C ~ 125°C Current - Supply (Max) 35mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height - Seated (Max) 0.035" (0.90mm)	Series	Pure Silicon? ASFLMP
Function CMOS Voltage - Supply Enable/Disable CMOS Voltage - Supply 2.25 V ~ 3.6 V Frequency Stability Departing Temperature -55°C ~ 125°C Current - Supply (Max) Ratings - Mounting Type Surface Mount Package / Case Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height - Seated (Max) 0.035" (0.90mm)	Туре	MEMS (Silicon)
Output CMOS Voltage - Supply 2.25 V ~ 3.6 V Frequency Stability ±50ppm Operating Temperature -55°C ~ 125°C Current - Supply (Max) 35mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height - Seated (Max) 0.035" (0.90mm)	Frequency	24MHz
Voltage - Supply $2.25 \text{ V} \sim 3.6 \text{ V}$ Frequency Stability $\pm 50 \text{ppm}$ Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Current - Supply (Max) 35mA Ratings - Mounting Type Surface Mount Package / Case $6-\text{SMD}$, No Lead Size / Dimension $0.197'' \text{ L} \times 0.126'' \text{ W} (5.00 \text{mm} \times 3.20 \text{mm})$ Height - Seated (Max) $0.035'' (0.90 \text{mm})$	Function	Enable/Disable
Frequency Stability ± 50 ppm Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Current - Supply (Max) 35mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD , No Lead Size / Dimension $0.197^{\circ}\text{L} \times 0.126^{\circ}\text{W} (5.00\text{mm} \times 3.20\text{mm})$ Height - Seated (Max) 0.035° (0.90mm)	Output	CMOS
Operating Temperature -55°C ~ 125°C Current - Supply (Max) Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height - Seated (Max) 0.035" (0.90mm)	Voltage - Supply	2.25 V ~ 3.6 V
Current - Supply (Max) 35mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height - Seated (Max) 0.035" (0.90mm)	Frequency Stability	±50ppm
Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height - Seated (Max) 0.035" (0.90mm)	Operating Temperature	-55°C ~ 125°C
Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height - Seated (Max) 0.035" (0.90mm)	Current - Supply (Max)	35mA
Package / Case 6-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height - Seated (Max) 0.035" (0.90mm)	Ratings	-
Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height - Seated (Max) 0.035" (0.90mm)	Mounting Type	Surface Mount
Height - Seated (Max) 0.035" (0.90mm)	Package / Case	6-SMD, No Lead
	Size / Dimension	0.197" L x 0.126" W (5.00mm x 3.20mm)
Report errors?	Height - Seated (Max)	0.035" (0.90mm)
		Report errors?

ASFLMPC-24.000MHZ-Z-T Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ASFLMPC-24.000MHZ-Z-T Payment Methods





















ASFLMPC-24.000MHZ-Z-T Shipping Methods













If you have any question about ASFLMPC-24.000MHZ-Z-T, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com