


ASG2-D-V-A-320.000MHZ-T

ASG2-D-V-A-320.000MHZ-T Information



Part Number	ASG2-D-V-A-320.000MHZ-T	
Manufacturer	Abracon LLC	
Category	Crystals, Oscillators, Resonators Oscillators	
Description	OSC VCXO 320.000MHZ LVDS SMD	
Package	6-SMD, No Lead	
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com	
	E-mail: salesdept@heisener.com	



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



ASG2-D-V-A-320.000MHZ-T Specifications

ManufacturerAbracon LLCCategoryCrystals, Oscillators, ResonatorsOscillatorsOscillatorsPackage6-SMD, No LeadSeriesASG2-DTypeVCXOFrequency320MHzFunctionEnable/DisableDutputJVDSVoltage - Supply3.3VFrequency Stability±50ppmOperating Temperature-Current - Supply (Max)Surface MountRatings-Package / Case6.SMD, No LeadSize / Dimension0.098" L x 0.079" W (2.50mm x 2.00mm)Height - Seated (Max)0.039" (1.00mm)		
CategoryCrystals, Oscillators, ResonatorsOscillatorsPackage6-SMD, No LeadSeriesASG2-DTypeVCXOTrequency320MHzFunctionEnable/DisableDutputLVDSVoltage - Supply3.3VPrequency Stability±50ppmOperating Temperature40°C ~ 85°CCurrent - Supply (Max)Surface MountPackage / Case6-SMD, No LeadPackage / Case0.098" L x 0.079" W (2.50mm x 2.00mm)Height - Seated (Max)0.039" (1.00mm)	Manufacturer Part Number	ASG2-D-V-A-320.000MHZ-T
AckageOscillatorsPackage6-SMD, No LeadSeriesASG2-DTypeVCXOFrequency320MHzFunctionEnable/DisableDutputLVDSVoltage - Supply3.3VFrequency Stability+50ppmOperating Temperature40°C ~ 85°CCurrent - Supply (Max)Surface MountRatings-Package / Case6-SMD, No LeadBize / Dimension0.098" L x 0.079" W (2.50mm x 2.00mm)Height - Seated (Max)0.039" (1.00mm)	Manufacturer	Abracon LLC
Package6-SMD, No LeadSeriesASG2-DTypeVCXOFrequency320MHzFunctionEnable/DisableDutputLVDSVoltage - Supply3.3VPrequency Stability±50pmOperating Temperature-40°C ~ 85°CCurrent - Supply (Max)Surface MountRatings-Package / Case6-SMD, No LeadBize / Dimension0.098" L x 0.079" W (2.50mm x 2.00mm)Height - Seated (Max)0.039" (1.00mm)	Category	Crystals, Oscillators, Resonators
SeriesASG2-DFypeVCXOFrequency320MHzFunctionEnable/DisableDutputLVDSVoltage - Supply3.3VFrequency Stability±50ppmOperating Temperature-40°C ~ 85°CCurrent - Supply (Max)Surface MountRatings-Package / Case6-SMD, No LeadSize / Dimension0.039" (1.00mm)		Oscillators
FypeVCXOFrequency320MHzFunctionEnable/DisableDutputLVDSVoltage - Supply3.3VFrequency Stability±50ppmOperating Temperature-40°C ~ 85°CCurrent - Supply (Max)40mARatings-Package / Case6-SMD, No LeadSize / Dimension0.098" L x 0.079" W (2.50mm x 2.00mm)Height - Seated (Max)0.039" (1.00mm)	Package	6-SMD, No Lead
Arr320MHzFrequency320MHzFunctionEnable/DisableDutputLVDSVoltage - Supply3.3VFrequency Stability±50ppmOperating Temperature-40°C ~ 85°CCurrent - Supply (Max)40mARatings-Mounting TypeSurface MountPackage / Case6-SMD, No LeadSize / Dimension0.098" L x 0.079" W (2.50mm x 2.00mm)Height - Seated (Max)0.039" (1.00mm)	Series	ASG2-D
FunctionEnable/DisableFunctionLVDSOutput3.3VVoltage - Supply3.3VFrequency Stability±50ppmOperating Temperature-40°C ~ 85°CCurrent - Supply (Max)40mARatings-Mounting TypeSurface MountPackage / Case6-SMD, No LeadSize / Dimension0.098" L x 0.079" W (2.50mm x 2.00mm)	Туре	VCXO
DutputLVDSVoltage - Supply3.3VFrequency Stability±50ppmOperating Temperature-40°C ~ 85°CCurrent - Supply (Max)40mARatings-Mounting TypeSurface MountPackage / Case6-SMD, No LeadSize / Dimension0.098" L x 0.079" W (2.50mm x 2.00mm)Height - Seated (Max)0.039" (1.00mm)	Frequency	320MHz
Voltage - Supply 3.3V Frequency Stability ±50ppm Operating Temperature -40°C ~ 85°C Current - Supply (Max) 40mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.098" L x 0.079" W (2.50mm x 2.00mm)	Function	Enable/Disable
Frequency Stability ±50ppm Operating Temperature -40°C ~ 85°C Current - Supply (Max) 40mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.098" L x 0.079" W (2.50mm x 2.00mm)	Output	LVDS
Operating Temperature-40°C ~ 85°CCurrent - Supply (Max)40mARatings-Mounting TypeSurface MountPackage / Case6-SMD, No LeadSize / Dimension0.098" L x 0.079" W (2.50mm x 2.00mm)Height - Seated (Max)0.039" (1.00mm)	Voltage - Supply	3.3V
Current - Supply (Max)40mARatings-Mounting TypeSurface MountPackage / Case6-SMD, No LeadSize / Dimension0.098" L x 0.079" W (2.50mm x 2.00mm)Height - Seated (Max)0.039" (1.00mm)	Frequency Stability	±50ppm
Ratings-Mounting TypeSurface MountPackage / Case6-SMD, No LeadSize / Dimension0.098" L x 0.079" W (2.50mm x 2.00mm)Height - Seated (Max)0.039" (1.00mm)	Operating Temperature	-40°C ~ 85°C
Mounting TypeSurface MountPackage / Case6-SMD, No LeadSize / Dimension0.098" L x 0.079" W (2.50mm x 2.00mm)Height - Seated (Max)0.039" (1.00mm)	Current - Supply (Max)	40mA
Package / Case6-SMD, No LeadSize / Dimension0.098" L x 0.079" W (2.50mm x 2.00mm)Height - Seated (Max)0.039" (1.00mm)	Ratings	-
Size / Dimension 0.098" L x 0.079" W (2.50mm x 2.00mm) Height - Seated (Max) 0.039" (1.00mm)	Mounting Type	Surface Mount
Height - Seated (Max) 0.039" (1.00mm)	Package / Case	6-SMD, No Lead
	Size / Dimension	0.098" L x 0.079" W (2.50mm x 2.00mm)
	Height - Seated (Max)	0.039" (1.00mm)
Report errors?		Report errors?

ASG2-D-V-A-320.000MHZ-T Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE ELARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about ASG2-D-V-A-320.000MHZ-T, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com