



#### **ASM08DRXH Information**

Heisener.com

Part Number ASM08DRXH

ManufacturerSullins Connector SolutionsCategoryConnectors, Interconnects

Card Edge Connectors - Edgeboard Connectors

**Description** CONN EDGE DUAL FMALE 16POS 0.156

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **ASM08DRXH Specifications**

Manufacturer Part Number       ASM08DRXH         Manufacturer       Sullins Connector Solutions         Category       Connectors, Interconnects         Package       -         Series       -         Card Type       Non Specified - Dual Edge         Gender       Female         Number of Positions/Bay/Row       8         Number of Positions       16         Card Thickness       0.062" (1.57mm)         Number of Rows       2         Pitch       0.156" (3.96mm)         Features       -         Mounting Type       Through Hole         Termination       Solder         Contact Material       Beryllium Copper         Contact Finish Thickness       10µin (0.25µm)         Contact Type       Full Bellows         Color       Green         Flange Feature       Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia         Operating Temperature       -65°C ~ 150°C         Report errors?	•	
Category         Connectors, Interconnects           Package         -           Series         -           Card Type         Non Specified - Dual Edge           Gender         Female           Number of Positions/Bay/Row         8           Number of Positions         16           Card Thickness         0.062" (1.57mm)           Number of Rows         2           Pitch         0.156" (3.96mm)           Features         -           Mounting Type         Through Hole           Termination         Solder           Contact Material         Beryllium Copper           Contact Finish         Gold           Contact Finish Thickness         10μin (0.25μm)           Contact Type         Full Bellows           Color         Green           Flange Feature         Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia           Operating Temperature         -65°C ~ 150°C	Manufacturer Part Number	ASM08DRXH
Package         -           Series         -           Card Type         Non Specified - Dual Edge           Gender         Female           Number of Positions/Bay/Row         8           Number of Positions         16           Card Thickness         0.062" (1.57mm)           Number of Rows         2           Pitch         0.156" (3.96mm)           Features         -           Mounting Type         Through Hole           Termination         Solder           Contact Material         Beryllium Copper           Contact Finish         Gold           Contact Type         Full Bellows           Color         Green           Flange Feature         Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia           Operating Temperature         -65°C ~ 150°C	Manufacturer	Sullins Connector Solutions
Package         -           Series         -           Card Type         Non Specified - Dual Edge           Gender         Female           Number of Positions/Bay/Row         8           Number of Positions         16           Card Thickness         0.062" (1.57mm)           Number of Rows         2           Pitch         0.156" (3.96mm)           Features         -           Mounting Type         Through Hole           Termination         Solder           Contact Material         Beryllium Copper           Contact Finish         Gold           Contact Finish Thickness         10µin (0.25µm)           Contact Type         Full Bellows           Color         Green           Flange Feature         Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia           Operating Temperature         -65°C ~ 150°C	Category	Connectors, Interconnects
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row8Number of Positions $16$ Card Thickness $0.062"$ (1.57mm)Number of Rows $2$ Pitch $0.156"$ (3.96mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness $10\mu$ in $(0.25\mu$ m)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, $0.125"$ (3.18mm) DiaOperating Temperature $-65°C \sim 150°C$		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row8Number of Positions16Card Thickness $0.062"$ (1.57mm)Number of Rows2Pitch $0.156"$ (3.96mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness $10\mu$ in $(0.25\mu$ m)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, $0.125"$ (3.18mm) DiaOperating Temperature $-65^{\circ}$ C ~ $150^{\circ}$ C	Package	-
Gender         Female           Number of Positions/Bay/Row         8           Number of Positions         16           Card Thickness         0.062" (1.57mm)           Number of Rows         2           Pitch         0.156" (3.96mm)           Features         -           Mounting Type         Through Hole           Termination         Solder           Contact Material         Beryllium Copper           Contact Finish         Gold           Contact Finish Thickness         10µin (0.25µm)           Contact Type         Full Bellows           Color         Green           Flange Feature         Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia           Operating Temperature         -65°C ~ 150°C	Series	-
Number of Positions/Bay/Row8Number of Positions16Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Card Type	Non Specified - Dual Edge
Number of Positions  16 Card Thickness  0.062" (1.57mm)  Number of Rows  2 Pitch  0.156" (3.96mm)  Features  - Mounting Type  Through Hole  Termination  Solder  Contact Material  Beryllium Copper  Contact Finish  Gold  Contact Finish Thickness  10µin (0.25µm)  Contact Type  Full Bellows  Color  Flange Feature  Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia  Operating Temperature  -65°C ~ 150°C	Gender	Female
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Number of Positions/Bay/Row	8
Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Number of Positions	16
Pitch 0.156" (3.96mm)  Features -  Mounting Type Through Hole  Termination Solder  Contact Material Beryllium Copper  Contact Finish Gold  Contact Finish Thickness 10µin (0.25µm)  Contact Type Full Bellows  Color Green  Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia  Operating Temperature -65°C ~ 150°C	Card Thickness	0.062" (1.57mm)
Features  Mounting Type Through Hole  Termination Solder  Contact Material Beryllium Copper  Contact Finish Contact Finish Thickness 10μin (0.25μm)  Contact Type Full Bellows  Color Green  Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia  Operating Temperature  -65°C ~ 150°C	Number of Rows	2
Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Pitch	0.156" (3.96mm)
TerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Features	-
Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness $10\mu$ in $(0.25\mu$ m)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, $0.125$ " $(3.18$ mm) DiaOperating Temperature $-65$ °C ~ $150$ °C	Mounting Type	Through Hole
Contact Finish  Contact Finish Thickness $10\mu in (0.25\mu m)$ Contact Type  Full Bellows  Color  Green  Flange Feature  Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia  Operating Temperature  -65°C ~ 150°C	Termination	Solder
Contact Finish Thickness $10\mu in (0.25\mu m)$ Contact Type Full Bellows Color Green Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 150°C	Contact Material	Beryllium Copper
Contact Type Full Bellows Color Green Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 150°C	Contact Finish	Gold
Color Green  Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia  Operating Temperature -65°C ~ 150°C	Contact Finish Thickness	10μin (0.25μm)
Flange Feature Top Mount Opening, Unthreaded, $0.125$ " (3.18mm) Dia Operating Temperature $-65$ °C $\sim 150$ °C	Contact Type	Full Bellows
Operating Temperature $-65^{\circ}\text{C} \sim 150^{\circ}\text{C}$	Color	Green
	Flange Feature	Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia
Report errors?	Operating Temperature	-65°C ~ 150°C
		Report errors?

#### **ASM08DRXH Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **ASM08DRXH Payment Methods**





















### **ASM08DRXH Shipping Methods**













If you have any question about ASM08DRXH, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com