



ASM08DTBH Information

Heisener.com

Part Number ASM08DTBH

ManufacturerSullins Connector SolutionsCategoryConnectors, Interconnects

Card Edge Connectors - Edgeboard Connectors

Description CONN EDGE DUAL FMALE 16POS 0.156

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ASM08DTBH Specifications

Manufacturer Part Number ASM08DTBH Manufacturer Sullins Connector Solutions Category Connectors, Interconnects Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 8 Number of Positions 16 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features - Mounting Type Through Hole, Right Angle Termination Solder Contact Material Beryllium Copper Contact Finish Thickness 10µin (0.25µm) Contact Type Loop Bellows Color Green Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 150°C Report errors?	ASMIODIDII Specifications		
Category Connectors, Interconnects Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 8 Number of Positions 16 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features - Mounting Type Through Hole, Right Angle Termination Solder Contact Material Beryllium Copper Contact Finish Gold Contact Type Loop Bellows Color Green Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 150°C	Manufacturer Part Number	ASM08DTBH	
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row8Number of Positions16Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact TypeLoop BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Manufacturer	Sullins Connector Solutions	
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row8Number of Positions16Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeLoop BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Category	Connectors, Interconnects	
Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 8 Number of Positions 16 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features - Mounting Type Through Hole, Right Angle Termination Solder Contact Material Beryllium Copper Contact Finish Thickness 10μin (0.25μm) Contact Type Loop Bellows Color Green Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 150°C		Card Edge Connectors - Edgeboard Connectors	
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row8Number of Positions16Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeLoop BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Package	-	
GenderFemaleNumber of Positions/Bay/Row8Number of Positions16Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeLoop BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Series	-	
Number of Positions/Bay/Row8Number of Positions16Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeLoop BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Card Type	Non Specified - Dual Edge	
Number of Positions 16 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features - Mounting Type Through Hole, Right Angle Termination Solder Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 10μin (0.25μm) Contact Type Loop Bellows Color Green Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 150°C	Gender	Female	
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeLoop BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Number of Positions/Bay/Row	8	
Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeLoop BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Number of Positions	16	
Pitch0.156" (3.96mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeLoop BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Card Thickness	0.062" (1.57mm)	
Features Mounting Type Through Hole, Right Angle Termination Solder Contact Material Beryllium Copper Contact Finish Contact Finish Thickness 10μin (0.25μm) Contact Type Loop Bellows Color Green Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 150°C	Number of Rows	2	
Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeLoop BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Pitch	0.156" (3.96mm)	
Termination Solder Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness $10\mu in (0.25\mu m)$ Contact Type Loop Bellows Color Green Flange Feature Top Mount Opening, Unthreaded, 0.125 " ($3.18mm$) Dia Operating Temperature -65 °C ~ 150 °C	Features	-	
Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness 10μ in $(0.25\mu$ m)Contact TypeLoop BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125 " $(3.18$ mm) DiaOperating Temperature -65 °C ~ 150 °C	Mounting Type	Through Hole, Right Angle	
Contact Finish Contact Finish Thickness 10μ in $(0.25\mu$ m) Contact Type Loop Bellows Color Green Flange Feature Top Mount Opening, Unthreaded, 0.125 " $(3.18$ mm) Dia Operating Temperature -65 °C ~ 150 °C	Termination	Solder	
Contact Finish Thickness $10\mu in (0.25\mu m)$ Contact Type Loop Bellows Color Green Flange Feature Top Mount Opening, Unthreaded, $0.125''$ ($3.18mm$) Dia Operating Temperature $-65^{\circ}\text{C} \sim 150^{\circ}\text{C}$	Contact Material	Beryllium Copper	
Contact Type Loop Bellows Color Green Flange Feature Top Mount Opening, Unthreaded, 0.125 " (3.18 mm) Dia Operating Temperature -65 °C ~ 150 °C	Contact Finish	Gold	
Color Green Flange Feature Top Mount Opening, Unthreaded, 0.125 " (3.18 mm) Dia Operating Temperature -65 °C ~ 150 °C	Contact Finish Thickness	10μin (0.25μm)	
Flange Feature Top Mount Opening, Unthreaded, 0.125 " (3.18 mm) Dia Operating Temperature -65 °C ~ 150 °C	Contact Type	Loop Bellows	
Operating Temperature $-65^{\circ}\text{C} \sim 150^{\circ}\text{C}$	Color	Green	
	Flange Feature	Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	
Report errors?	Operating Temperature	-65°C ~ 150°C	
			Report errors?

ASM08DTBH Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ASM08DTBH Payment Methods



















ASM08DTBH Shipping Methods













If you have any question about ASM08DTBH, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com