

ASM22DSEN-S243

Quote

ASM22DSEN-S243 Information

Heisener.com		ASM22DSEN-S243 Sullins Connector Solutions	
	Category	Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors	
	Description	CONN EDGE DUAL FMALE 44POS 0.156	
	Package	- For the pricing/inventory/lead time, please contact	<u>D</u>
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a (

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



ASM22DSEN-S243 Specifications

ManufacturerSullins Connector SolutionsCategoryConnectors, InterconnectsPackage-Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row22Number of Positions0.062" (1.57mm)Number of Rows0.062" (1.57mm)Features-Features-Mounting TypeFee Hanging (In-Line)Contact FinishSolder Eyelet(s)Contact Finish ThicknessIujin (0.25µm)Contact TypeFull BellowsContact TypeFull Bellows<	-	
CategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row22Number of Positions/Bay/Row0.062" (1.57mm)Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeFree Hanging (In-Line)Contact MaterialGoldContact Finish ThicknessIoµin (0.25µm)Contact TypeFull BellowsContact TypeFull BellowsColorGreenFlange Feature-Coperating Temperature-Coperating Temperature-	Manufacturer Part Number	ASM22DSEN-S243
Card Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row22Number of Positions44Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeFree Hanging (In-Line)Contact MaterialBeryllium CopperContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsContact TypeFull BellowsColorGreenFlange Feature-Operating Temperature-65°C ~ 150°C	Manufacturer	Sullins Connector Solutions
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row22Number of Positions44Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeFree Hanging (In-Line)Contact MaterialGoldContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorGreenFlange Feature-Operating Temperature-65°C ~ 150°C	Category	Connectors, Interconnects
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row22Number of Positions44Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeFree Hanging (In-Line)TerminationSolder Eyelet(s)Contact FinishGoldContact Finish ThicknessIOµin (0.25µm)Contact TypeFreenContact TypeFenellowsColare TypeGoldContact TypeFenellowsColare TypeFenellowsColare TypeFenellowsColare TypeFenellowsColare TypeGoldColare TypeFenellowsColare TypeGreenFlange Feature-Operating Temperature-65°C ~ 150°C		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row22Number of Positions44Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeFree Hanging (In-Line)TerminationSolder Eyelet(s)Contact Finish ThicknessGoldContact TypeFull BellowsContact TypeFull BellowsColorGreenFlange Feature-Operating Temperature-55°C ~ 150°C	Package	-
GenderFemaleNumber of Positions/Bay/Row22Number of Positions44Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeFree Hanging (In-Line)Contact MaterialGoldContact FinishGoldContact TypeFull BellowsColorGreenFlange Feature-Operating Temperature-5°C ~ 150°C	Series	-
Number of Positions/Bay/Row22Number of Positions44Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeFree Hanging (In-Line)Contact MaterialSolder Eyelet(s)Contact FinishGoldContact TypeFull BellowsColorGreenFlange Feature-Operating Temperature65°C ~ 150°C	Card Type	Non Specified - Dual Edge
Number of Positions 44 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features - Mounting Type Free Hanging (In-Line) Termination Solder Eyelet(s) Contact Material Gold Contact Finish Gold Contact Type Full Bellows Color Green Flange Feature - Operating Temperature -	Gender	Female
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeFree Hanging (In-Line)TerminationSolder Eyelet(s)Contact MaterialBeryllium CopperContact Finish ThicknessI0µin (0.25µm)Contact TypeFull BellowsColorGreenFlange Feature-Operating Temperature-65°C ~ 150°C	Number of Positions/Bay/Row	22
Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeFree Hanging (In-Line)Mounting TypeSolder Eyelet(s)Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorGreenFlange Feature-Operating Temperature-65°C ~ 150°C	Number of Positions	44
Pitch0.156" (3.96mm)Features-Mounting TypeFree Hanging (In-Line)TerminationSolder Eyelet(s)Contact MaterialBeryllium CopperContact Finish ThicknessGoldContact Finish Thickness10µin (0.25µm)ColorGreenFlange Feature-Operating Temperature-65°C ~ 150°C	Card Thickness	0.062" (1.57mm)
Features-Mounting TypeFree Hanging (In-Line)TerminationSolder Eyelet(s)Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorGreenFlange Feature-Operating Temperature-55°C ~ 150°C	Number of Rows	2
Mounting TypeFree Hanging (In-Line)TerminationSolder Eyelet(s)Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorGreenFlange Feature-Operating Temperature-55°C ~ 150°C	Pitch	0.156" (3.96mm)
TerminationSolder Eyelet(s)Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorGreenFlange Feature-Operating Temperature-65°C ~ 150°C	Features	-
Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorGreenFlange Feature-Operating Temperature-65°C ~ 150°C	Mounting Type	Free Hanging (In-Line)
Contact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorGreenFlange Feature-Operating Temperature-65°C ~ 150°C	Termination	Solder Eyelet(s)
Contact Finish Thickness10μin (0.25μm)Contact TypeFull BellowsColorGreenFlange Feature-Operating Temperature-65°C ~ 150°C	Contact Material	Beryllium Copper
Contact TypeFull BellowsColorGreenFlange Feature-Operating Temperature-65°C ~ 150°C	Contact Finish	Gold
Color Green Flange Feature - Operating Temperature -65°C ~ 150°C	Contact Finish Thickness	10µin (0.25µm)
Flange Feature-Operating Temperature-65°C ~ 150°C	Contact Type	Full Bellows
Operating Temperature $-65^{\circ}C \sim 150^{\circ}C$	Color	Green
	Flange Feature	-
Report errors?	Operating Temperature	$-65^{\circ}C \sim 150^{\circ}C$
		Report errors?

ASM22DSEN-S243 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

ASM22DSEN-S243 Payment Methods





If you have any question about ASM22DSEN-S243, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com