

# ASM36DRTF

est a Quote

#### **ASM36DRTF** Information

	Part Number	ASM36DRTF
	Manufacturer	Sullins Connector Solutions
(A Heisener.com	Category Heisener.com	Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors
Contraction of the set	Description	CONN EDGE DUAL FMALE 72POS 0.156
	Package	-
		For the pricing/inventory/lead time, please contact
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## **ASM36DRTF Specifications**

ManufacturerSullins Connector SolutionsCade Edge ConnectorsCard Edge ConnectorsPackage-Package-Card TypeNon Specified - Dual EdgeGenderFenaleSumber of Positions/Bay/Row36Number of Positions/Bay/Row062° (1.57mm)Number of Rows0.62° (1.57mm)Features0.156° (3.96mm)FeaturesSolderFeaturesSolderContact FinishGoldContact FinishGoldContact Finish Thickness1001 (0.25µm)Contact TypeSolderContact Finish Thickness1016 (0.25µm)Contact Finish Thickness1016 (0.25µm)Contact TypeFeaturesContact TypeSolderContact				
CategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Package-Series-Card TypeNon Specified - Dual EdgeGenderFenaleNumber of Positions/Bay/Row36Number of Positions/Bay/Row0.062" (1.57mm)Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact Finish Thickness0.014Contact Finish Thickness0.014Contact TypeHull BellowsContact TypeSull BellowsContact TypeGreenFaques FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) DiaOperating Temperature65° ~ 150°C	Manufacturer Part Number	ASM36DRTF		
Card Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row36Number of Positions72Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorGreenFlange Feature-Coperating Temperature-Coperating Temperature-Contact Sector-Contact Temperature-Contact Temperature-Contact Sector-Contact Type-Contact Sector-Contact Sector </td <td>Manufacturer</td> <td colspan="2">Sullins Connector Solutions</td>	Manufacturer	Sullins Connector Solutions		
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row36Number of Positions72Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) DiaOperating Temperature-55°C ~ 150°C	Category	Connectors, Interconnects		
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row36Number of Positions72Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleContact FinishSolderContact Finish Thickness10µin (0.25µm)Contact Finish Thickness10µin (0.25µm)Contact TypeFeallellowsContact TypeGreenFlange Featurecomounting Floating Bobbin, 0.116" (2.95mm) DiaOperating Temperature65°C ~ 150°C		Card Edge Connectors - Edgeboard Connectors		
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row36Number of Positions72Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleContact FinishSolderContact Finish Thickness0jui (0.25µm)Contact TypeFull BellowsContact TypeGreenFlange Feature-Operating Temperature65°C ~ 150°C	Package	-		
GenderFemaleNumber of Positions/Bay/Row36Number of Positions72Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorGreenFlange Feature-Operating Temperature-65°C ~ 150°C	Series	-		
Number of Positions/Bay/Row36Number of Positions72Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact FinishGoldContact TypeIupin (0.25µm)Contact TypeFull BellowsColorGreenFange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) DiaOperating Temperature-65°C ~ 150°C	Card Type	Non Specified - Dual Edge	Non Specified - Dual Edge	
Number of Positions 72   Card Thickness 0.062" (1.57mm)   Number of Rows 2   Pitch 0.156" (3.96mm)   Features -   Mounting Type -   Mounting Type Through Hole   Contact Material Solder   Contact Finish Beryllium Copper   Contact Finish Thickness Ioµin (0.25µm)   Contact Type Full Bellows   Color Green   Flange Feature Top Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia   Operating Temperature -5°°C	Gender	Female	Female	
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleFerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) DiaOperating Temperature-65°C ~ 150°C	Number of Positions/Bay/Row	36		
Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) DiaOperating Temperature-55°C ~ 150°C	Number of Positions	72		
Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) DiaOperating Temperature-65°C ~ 150°C	Card Thickness	0.062" (1.57mm)		
Features-Mounting TypeThrough HoleMounting TypeSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) DiaOpenating Temperature-65°C ~ 150°C	Number of Rows	2		
Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) DiaOperating Temperature-65°C ~ 150°C	Pitch	0.156" (3.96mm)		
TerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) DiaOperating Temperature-65°C ~ 150°C	Features	-		
Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) DiaOperating Temperature-65°C ~ 150°C	Mounting Type	Through Hole		
Contact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) DiaOperating Temperature-65°C ~ 150°C	Termination	Solder		
Contact Finish Thickness10μin (0.25μm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) DiaOperating Temperature-65°C ~ 150°C	Contact Material	Beryllium Copper		
Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) DiaOperating Temperature-65°C ~ 150°C	Contact Finish	Gold		
ColorGreenFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) DiaOperating Temperature-65°C ~ 150°C	Contact Finish Thickness	10µin (0.25µm)		
Flange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) DiaOperating Temperature-65°C ~ 150°C	Contact Type	Full Bellows		
Operating Temperature $-65^{\circ}\text{C} \sim 150^{\circ}\text{C}$	Color	Green		
	Flange Feature	Top Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia		
Report errors?	Operating Temperature	-65°C ~ 150°C		
			Report errors?	

#### **ASM36DRTF** Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE UARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

### **ASM36DRTF** Payment Methods





If you have any question about ASM36DRTF, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com