



ASM40DRSS Information

Heisener.com

Part Number ASM40DRSS

ManufacturerSullins Connector SolutionsCategoryConnectors, Interconnects

Card Edge Connectors - Edgeboard Connectors

Description CONN EDGE DUAL FMALE 80POS 0.156

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ASM40DRSS Specifications

Manufacturer Part Number ASM40DRSS Manufacturer Sullins Connector Solutions Category Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 40 Number of Positions 80 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features - Mounting Type Through Hole Termination Solder Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 10μin (0.25μm)	Montations specifications	
Category Card Edge Connectors - Edgeboard Connectors Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 40 Number of Positions 80 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features - Mounting Type Through Hole Termination Contact Material Beryllium Copper Contact Finish Gold	Manufacturer Part Number	ASM40DRSS
Card Edge Connectors - Edgeboard Connectors Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 40 Number of Positions 80 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features - Mounting Type Through Hole Termination Solder Contact Material Beryllium Copper Contact Finish Gold	Manufacturer	Sullins Connector Solutions
Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 40 Number of Positions 80 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features - Mounting Type Through Hole Termination Solder Contact Material Beryllium Copper Contact Finish Gold	Category	Connectors, Interconnects
Series Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 40 Number of Positions 80 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features - Mounting Type Through Hole Termination Solder Contact Material Beryllium Copper Contact Finish Gold		Card Edge Connectors - Edgeboard Connectors
Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 40 Number of Positions 80 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features - Mounting Type Through Hole Termination Solder Contact Material Beryllium Copper Contact Finish Gold	Package	-
GenderFemaleNumber of Positions/Bay/Row40Number of Positions80Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGold	Series	-
Number of Positions/Bay/Row40Number of Positions80Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGold	Card Type	Non Specified - Dual Edge
Number of Positions80Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGold	Gender	Female
Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features - Mounting Type Through Hole Termination Solder Contact Material Beryllium Copper Contact Finish Gold	Number of Positions/Bay/Row	40
Number of Rows 2 Pitch 0.156" (3.96mm) Features - Mounting Type Through Hole Termination Solder Contact Material Beryllium Copper Contact Finish Gold	Number of Positions	80
Pitch 0.156" (3.96mm) Features - Mounting Type Through Hole Termination Solder Contact Material Beryllium Copper Contact Finish Gold	Card Thickness	0.062" (1.57mm)
Features - Mounting Type Through Hole Termination Solder Contact Material Beryllium Copper Contact Finish Gold	Number of Rows	2
Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGold	Pitch	0.156" (3.96mm)
Termination Solder Contact Material Beryllium Copper Contact Finish Gold	Features	-
Contact Material Beryllium Copper Contact Finish Gold	Mounting Type	Through Hole
Contact Finish Gold	Termination	Solder
	Contact Material	Beryllium Copper
Contact Finish Thickness 10µin (0.25µm)	Contact Finish	Gold
	Contact Finish Thickness	10μin (0.25μm)
Contact Type Loop Bellows	Contact Type	Loop Bellows
Color Green	Color	Green
Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	Flange Feature	Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia
Operating Temperature $-65^{\circ}\text{C} \sim 150^{\circ}\text{C}$	Operating Temperature	-65°C ~ 150°C
Report error		Report errors?

ASM40DRSS Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ASM40DRSS Payment Methods



















ASM40DRSS Shipping Methods













If you have any question about ASM40DRSS, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com