



ASM6668E Information

Heisener.com

Part Number ASM6668E

Manufacturer Ohmite

Category Potentiometers, Variable Resistors Rotary Potentiometers, Rheostats

Description POT 25K OHM 1/2W CARBON LINEAR

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ASM6668E Specifications

Manufacturer Part NumberASM6668EManufacturerOhmiteCategoryPotentiometers, Variable ResistorsRotary Potentiometers, RheostatsPackage-SeriesASMTaperLinearResistance (Ohms)25kTolerance±10%Number of Gangs1Built in SwitchNonePower (Watts)0.5W, 1/2WTemperature Coefficient-	ASWIOOOL SPECIFICATIONS	
Category Potentiometers, Variable Resistors Rotary Potentiometers, Rheostats Package - Series ASM Taper Linear Resistance (Ohms) 25k Tolerance ±10% Number of Gangs 1 Built in Switch None Power (Watts) 0.5W, 1/2W Temperature Coefficient -	facturer Part Number	ASM6668E
Rotary Potentiometers, Rheostats	facturer	Ohmite
Package - Series ASM Taper Linear Resistance (Ohms) 25k Tolerance ±10% Number of Gangs 1 Built in Switch None Power (Watts) 0.5W, 1/2W Temperature Coefficient -	ory	Potentiometers, Variable Resistors
Series ASM Taper Linear Resistance (Ohms) 25k Tolerance ±10% Number of Gangs 1 Built in Switch None Power (Watts) 0.5W, 1/2W Temperature Coefficient -		Rotary Potentiometers, Rheostats
Taper Linear Resistance (Ohms) 25k Tolerance ±10% Number of Gangs 1 Built in Switch None Power (Watts) 0.5W, 1/2W Temperature Coefficient -	ge	-
Resistance (Ohms) 25k Tolerance ±10% Number of Gangs 1 Built in Switch None Power (Watts) 0.5W, 1/2W Temperature Coefficient -		ASM
$ \begin{array}{llllllllllllllllllllllllllllllllllll$		Linear
Number of Gangs 1 Built in Switch None Power (Watts) 0.5W, 1/2W Temperature Coefficient -	ance (Ohms)	25k
Built in Switch None Power (Watts) 0.5W, 1/2W Temperature Coefficient -	nnce	±10%
Power (Watts) 0.5W, 1/2W Temperature Coefficient -	er of Gangs	1
Temperature Coefficient -	n Switch	None
	(Watts)	0.5W, 1/2W
	erature Coefficient	-
Number of Turns 1	er of Turns	1
Rotation 295°	on	295°
Adjustment Type User Defined	tment Type	User Defined
Resistive Material Carbon	ive Material	Carbon
Termination Style Solder Lug	nation Style	Solder Lug
Actuator Type Slotted	tor Type	Slotted
Actuator Length 0.875" (22.23mm)	tor Length	0.875" (22.23mm)
Actuator Diameter 0.125" (3.18mm)	tor Diameter	0.125" (3.18mm)
Bushing Thread 1/4-32	ng Thread	1/4-32
Mounting Type Panel Mount	ting Type	Panel Mount
Report errors		Report errors?

ASM6668E Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ASM6668E Payment Methods





















ASM6668E Shipping Methods













If you have any question about ASM6668E, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com