

ASMA22W Information

Heisener.com

Part Number ASMA22W
Manufacturer Amphenol PCD

Category Connectors, Interconnects

Terminal Blocks - Din Rail, Channel

Description CONN TERM BLK FEED THRU 14-22AWG

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ASMA22W Specifications

Manufacturer Part NumberASMA22WManufacturerAmphenol PCDCategoryConnectors, InterconnectsTerminal Blocks - Din Rail, ChannelPackage-SeriesASMATypeFeed ThroughDisconnect Type-Number of Positions4Number of Levels1Terminal - Width6.0mmTermination StylePush In, SpringCurrent - IEC24AVoltage - IEC800VCurrent - UL20AVoltage - UL600VWire Gauge or Range - AWG14-22 AWGWire Gauge or Range - mm²0.5-2.5mm²	-	
Category Connectors, Interconnects Package - Series ASMA Type Feed Through Disconnect Type - Number of Positions 4 Number of Levels 1 Terminal - Width 6.0mm Termination Style Push In, Spring Current - IEC 24A Voltage - IEC 800V Current - UL 20A Voltage - UL 600V Wire Gauge or Range - AWG 14-22 AWG Wire Gauge or Range - mm² 0.5-2.5mm²	Manufacturer Part Number	ASMA22W
Package - Series ASMA Type Feed Through Disconnect Type - Number of Positions 4 Number of Levels 1 Terminal - Width 6.0mm Termination Style Push In, Spring Current - IEC 24A Voltage - IEC 800V Current - UL 20A Voltage - UL 600V Wire Gauge or Range - AWG 14-22 AWG Wire Gauge or Range - mm² 0.5-2.5mm²	Manufacturer	Amphenol PCD
Package - Series ASMA Type Feed Through Disconnect Type - Number of Positions 4 Number of Levels 1 Terminal - Width 6.0mm Termination Style Push In, Spring Current - IEC 24A Voltage - IEC 800V Current - UL 20A Voltage - UL 600V Wire Gauge or Range - AWG 14-22 AWG Wire Gauge or Range - mm² 0.5-2.5mm²	Category	Connectors, Interconnects
Series ASMA Type Feed Through Disconnect Type - Number of Positions 4 Number of Levels 1 Terminal - Width 6.0mm Termination Style Push In, Spring Current - IEC 24A Voltage - IEC 800V Current - UL 20A Voltage - UL 600V Wire Gauge or Range - AWG Wire Gauge or Range - mm² 0.5-2.5mm²		Terminal Blocks - Din Rail, Channel
Type Feed Through Disconnect Type - Number of Positions 4 Number of Levels 1 Terminal - Width 6.0mm Termination Style Push In, Spring Current - IEC 24A Voltage - IEC 800V Current - UL 20A Voltage - UL 600V Wire Gauge or Range - AWG 14-22 AWG Wire Gauge or Range - mm² 0.5-2.5mm²	Package	-
Disconnect Type - Number of Positions 4 Number of Levels 1 Terminal - Width 6.0mm Termination Style Push In, Spring Current - IEC 24A Voltage - IEC 800V Current - UL 20A Voltage - UL 600V Wire Gauge or Range - AWG 14-22 AWG Wire Gauge or Range - mm² 0.5-2.5mm²	Series	ASMA
Number of Positions4Number of Levels1Terminal - Width6.0mmTermination StylePush In, SpringCurrent - IEC24AVoltage - IEC800VCurrent - UL20AVoltage - UL600VWire Gauge or Range - AWG14-22 AWGWire Gauge or Range - mm²0.5-2.5mm²	Type	Feed Through
Number of Levels Terminal - Width 6.0mm Termination Style Push In, Spring Current - IEC 24A Voltage - IEC 800V Current - UL 20A Voltage - UL 600V Wire Gauge or Range - AWG Wire Gauge or Range - mm² 11 6.0mm 6.0	Disconnect Type	-
Terminal - Width 6.0mm Termination Style Push In, Spring Current - IEC 24A Voltage - IEC 800V Current - UL 20A Voltage - UL 600V Wire Gauge or Range - AWG 14-22 AWG Wire Gauge or Range - mm² 0.5-2.5mm²	Number of Positions	4
Termination Style Current - IEC 24A Voltage - IEC 800V Current - UL 20A Voltage - UL Wire Gauge or Range - AWG Wire Gauge or Range - mm² Push In, Spring 24A 800V 800V 14-22 AWG 0.5-2.5mm²	Number of Levels	1
Current - IEC 24A Voltage - IEC 800V Current - UL 20A Voltage - UL 600V Wire Gauge or Range - AWG 14-22 AWG Wire Gauge or Range - mm² 0.5-2.5mm²	Terminal - Width	6.0mm
Voltage - IEC800VCurrent - UL20AVoltage - UL600VWire Gauge or Range - AWG14-22 AWGWire Gauge or Range - mm²0.5-2.5mm²	Termination Style	Push In, Spring
Current - UL 20A Voltage - UL 600V Wire Gauge or Range - AWG 14-22 AWG Wire Gauge or Range - mm² 0.5-2.5mm²	Current - IEC	24A
Voltage - UL 600V Wire Gauge or Range - AWG 14-22 AWG Wire Gauge or Range - mm² 0.5-2.5mm²	Voltage - IEC	800V
Wire Gauge or Range - AWG Wire Gauge or Range - mm ² 14-22 AWG 0.5-2.5mm ²	Current - UL	20A
Wire Gauge or Range - mm ² 0.5-2.5mm ²	Voltage - UL	600V
	Wire Gauge or Range - AWG	14-22 AWG
	Wire Gauge or Range - mm ²	0.5-2.5mm ²
Features -	Features	-
Color White	Color	White
Report errors?		Report errors?

ASMA22W Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ASMA22W Payment Methods





















ASMA22W Shipping Methods













If you have any question about ASMA22W, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com