

ASMA4 Information

Heisener.com

Part Number ASMA4

Manufacturer Amphenol PCD

Category Connectors, Interconnects

Terminal Blocks - Din Rail, Channel

Description CONN TERM BLK FEED THRU 12-22AWG


Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com





Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ASMA4 Specifications

Manufacturer Part Number ASMA4 Manufacturer Amphenol PCD Category Connectors, Interconnects Terminal Blocks - Din Rail, Channel - Package - Series ASMA Type Feed Through Disconnect Type - Number of Positions 2 Number of Levels 1 Terminal - Width 6.0mm Termination Style Push In, Spring Current - IEC 32A Voltage - IEC 800V Current - UL 25A Voltage - UL 600V Wire Gauge or Range - AWG 12-22 AWG Wire Gauge or Range - mm² 0.5-4mm² Features -		
Category Connectors, Interconnects Terminal Blocks - Din Rail, Channel Package - Series ASMA Type Feed Through Disconnect Type - Number of Positions 2 Number of Levels 1 Terminal - Width 6.0mm Termination Style Push In, Spring Current - IEC 32A Voltage - IEC 800V Current - UL 25A Voltage - UL 600V Wire Gauge or Range - AWG 12-22 AWG Wire Gauge or Range - mm² 0.5-4mm²	Manufacturer Part Number	ASMA4
Terminal Blocks - Din Rail, Channel	Manufacturer	Amphenol PCD
Package - Series ASMA Type Feed Through Disconnect Type - Number of Positions 2 Number of Levels 1 Terminal - Width 6.0mm Termination Style Push In, Spring Current - IEC 32A Voltage - IEC 800V Current - UL 25A Voltage - UL 600V Wire Gauge or Range - AWG 12-22 AWG Wire Gauge or Range - mm² 0.5-4mm²	Category	Connectors, Interconnects
Series ASMA Type Feed Through Disconnect Type - Number of Positions 2 Number of Levels 1 Terminal - Width 6.0mm Termination Style Push In, Spring Current - IEC 32A Voltage - IEC 800V Current - UL 25A Voltage - UL 600V Wire Gauge or Range - AWG 12-22 AWG Wire Gauge or Range - mm² 0.5-4mm²		Terminal Blocks - Din Rail, Channel
Type Feed Through Disconnect Type - Number of Positions 2 Number of Levels 1 Terminal - Width 6.0mm Termination Style Push In, Spring Current - IEC 32A Voltage - IEC 800V Current - UL 25A Voltage - UL 600V Wire Gauge or Range - AWG Wire Gauge or Range - mm² 0.5-4mm²	Package	-
Disconnect Type - Number of Positions 2 Number of Levels 1 Terminal - Width 6.0mm Termination Style Push In, Spring Current - IEC 32A Voltage - IEC 800V Current - UL 25A Voltage - UL 600V Wire Gauge or Range - AWG 12-22 AWG Wire Gauge or Range - mm² 0.5-4mm²	Series	ASMA
Number of Positions 2 Number of Levels 1 Terminal - Width 6.0mm Termination Style Push In, Spring Current - IEC 32A Voltage - IEC 800V Current - UL 25A Voltage - UL 600V Wire Gauge or Range - AWG 12-22 AWG Wire Gauge or Range - mm² 0.5-4mm²	Туре	Feed Through
Number of Levels Terminal - Width 6.0mm Termination Style Push In, Spring Current - IEC 32A Voltage - IEC 800V Current - UL 25A Voltage - UL 600V Wire Gauge or Range - AWG Wire Gauge or Range - mm² 0.5-4mm²	Disconnect Type	-
Terminal - Width Termination Style Push In, Spring Current - IEC 32A Voltage - IEC 800V Current - UL 25A Voltage - UL Wire Gauge or Range - AWG Wire Gauge or Range - mm² 0.5-4mm²	Number of Positions	2
Termination Style Push In, Spring Current - IEC 32A Voltage - IEC 800V Current - UL 25A Voltage - UL 600V Wire Gauge or Range - AWG 12-22 AWG Wire Gauge or Range - mm² 0.5-4mm²	Number of Levels	1
Current - IEC 32A Voltage - IEC 800V Current - UL 25A Voltage - UL 600V Wire Gauge or Range - AWG 12-22 AWG Wire Gauge or Range - mm² 0.5-4mm²	Terminal - Width	6.0mm
Voltage - IEC 800V Current - UL 25A Voltage - UL 600V Wire Gauge or Range - AWG 12-22 AWG Wire Gauge or Range - mm² 0.5-4mm²	Termination Style	Push In, Spring
Current - UL 25A Voltage - UL 600V Wire Gauge or Range - AWG 12-22 AWG Wire Gauge or Range - mm² 0.5-4mm²	Current - IEC	32A
Voltage - UL 600V Wire Gauge or Range - AWG 12-22 AWG Wire Gauge or Range - mm² 0.5-4mm²	Voltage - IEC	800V
Wire Gauge or Range - AWG Wire Gauge or Range - mm ² 12-22 AWG 0.5-4mm ²	Current - UL	25A
Wire Gauge or Range - mm ² 0.5-4mm ²	Voltage - UL	600V
	Wire Gauge or Range - AWG	12-22 AWG
Features -	Wire Gauge or Range - mm ²	0.5-4mm ²
	Features	-
Color Gray	Color	Gray
Report errors?		Report errors?

ASMA4 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ASMA4 Payment Methods





















ASMA4 Shipping Methods













If you have any question about ASMA4, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com