



ASMA4BK Information

Heisener.com

Part Number ASMA4BK
Manufacturer Amphenol PCD

Category Connectors, Interconnects

Terminal Blocks - Din Rail, Channel

Description CONN TERM BLK FEED THRU 12-22AWG

Package -


For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com

Request a Quote



Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ASMA4BK	Specifi	cations
ASMA4BK	Specili	cauons

Manufacturer Part Number ASMA4BK Manufacturer Amphenol PCD Category Connectors, Interconnects Terminal Blocks - Din Rail, Channel Package - Series ASMA Type Feed Through Disconnect Type - Number of Positions 2 Number of Levels 1 Terminal - Width 6.0mm Termination Style Push In, Spring Current - IEC 32A Voltage - IEC 800V Current - UL 25A Voltage - UL 600V Wire Gauge or Range - AWG 12-22 AWG Wire Gauge or Range - mm² 0.5-4mm² Features - Color Black		
Category Connectors, Interconnects Terminal Blocks - Din Rail, Channel Package - Series ASMA Type Feed Through Disconnect Type - Number of Positions 2 Number of Levels 1 Terminal - Width 6.0mm Termination Style Push In, Spring Current - IEC 32A Voltage - IEC 800V Current - UL 25A Voltage - UL 600V Wire Gauge or Range - AWG 12-22 AWG Wire Gauge or Range - mm² 0.5-4mm² Features - Color Black	Manufacturer Part Number	ASMA4BK
Package - Series ASMA Type Feed Through Disconnect Type - Number of Positions 2 Number of Levels 1 Terminal - Width 6.0mm Termination Style Push In, Spring Current - IEC 32A Voltage - IEC 800V Current - UL 25A Voltage - UL 600V Wire Gauge or Range - AWG 12-22 AWG Wire Gauge or Range - mm² 0.5-4mm² Features - Color Black	Manufacturer	Amphenol PCD
Package - Series ASMA Type Feed Through Disconnect Type - Number of Positions 2 Number of Levels 1 Terminal - Width 6.0mm Termination Style Push In, Spring Current - IEC 32A Voltage - IEC 800V Current - UL 25A Voltage - UL 600V Wire Gauge or Range - AWG 12-22 AWG Wire Gauge or Range - mm² 0.5-4mm² Features - Color Black	Category	Connectors, Interconnects
Series ASMA Type Feed Through Disconnect Type - Number of Positions 2 Number of Levels 1 Terminal - Width 6.0mm Termination Style Push In, Spring Current - IEC 32A Voltage - IEC 800V Current - UL 25A Voltage - UL 600V Wire Gauge or Range - AWG 12-22 AWG Wire Gauge or Range - mm² 0.5-4mm² Features - Color Black		Terminal Blocks - Din Rail, Channel
Type Feed Through Disconnect Type - Number of Positions 2 Number of Levels 1 Terminal - Width 6.0mm Termination Style Push In, Spring Current - IEC 32A Voltage - IEC 800V Current - UL 25A Voltage - UL 600V Wire Gauge or Range - AWG 12-22 AWG Wire Gauge or Range - mm² 0.5-4mm² Features - Color Black	Package	-
Disconnect Type - Number of Positions 2 Number of Levels 1 Terminal - Width 6.0mm Termination Style Push In, Spring Current - IEC 32A Voltage - IEC 800V Current - UL 25A Voltage - UL 600V Wire Gauge or Range - AWG 12-22 AWG Wire Gauge or Range - mm² 0.5-4mm² Features - Color Black	Series	ASMA
Number of Positions2Number of Levels1Terminal - Width6.0mmTermination StylePush In, SpringCurrent - IEC32AVoltage - IEC800VCurrent - UL25AVoltage - UL600VWire Gauge or Range - AWG12-22 AWGWire Gauge or Range - mm²0.5-4mm²Features-ColorBlack	Туре	Feed Through
Number of Levels 1 Terminal - Width 6.0mm Termination Style Push In, Spring Current - IEC 32A Voltage - IEC 800V Current - UL 25A Voltage - UL 600V Wire Gauge or Range - AWG 12-22 AWG Wire Gauge or Range - mm² 0.5-4mm² Features - Color Black	Disconnect Type	-
Terminal - Width Termination Style Push In, Spring Current - IEC 32A Voltage - IEC 800V Current - UL 25A Voltage - UL 600V Wire Gauge or Range - AWG Wire Gauge or Range - mm² Features Color Black	Number of Positions	2
Termination Style Current - IEC 32A Voltage - IEC 800V Current - UL 25A Voltage - UL 600V Wire Gauge or Range - AWG Wire Gauge or Range - mm² Features - Color Push In, Spring 800V 800V 800V 800V 600V 600V Black	Number of Levels	1
Current - IEC 32A Voltage - IEC 800V Current - UL 25A Voltage - UL 600V Wire Gauge or Range - AWG 12-22 AWG Wire Gauge or Range - mm² 0.5-4mm² Features - Color Black	Terminal - Width	6.0mm
Voltage - IEC 800V Current - UL 25A Voltage - UL 600V Wire Gauge or Range - AWG 12-22 AWG Wire Gauge or Range - mm² 0.5-4mm² Features - Color Black	Termination Style	Push In, Spring
Current - UL 25A Voltage - UL 600V Wire Gauge or Range - AWG 12-22 AWG Wire Gauge or Range - mm² 0.5-4mm² Features - Color Black	Current - IEC	32A
Voltage - UL600VWire Gauge or Range - AWG12-22 AWGWire Gauge or Range - mm²0.5-4mm²Features-ColorBlack	Voltage - IEC	800V
Wire Gauge or Range - AWG Wire Gauge or Range - mm² O.5-4mm² Features Color Black	Current - UL	25A
Wire Gauge or Range - mm ² Features Color Black	Voltage - UL	600V
Features - Color Black	Wire Gauge or Range - AWG	12-22 AWG
Color Black	Wire Gauge or Range - mm ²	0.5-4mm ²
	Features	-
Report errors?	Color	Black
		Report errors?

ASMA4BK Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ASMA4BK Payment Methods





















ASMA4BK Shipping Methods













If you have any question about ASMA4BK, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com