



ASMB-TTB0-0A3A2 Information



For Reference Only

Part Number ASMB-TTB0-0A3A2
Manufacturer Broadcom Limited
Category Optoelectronics

LED Indication - Discrete

Description LED RGB DIFFUSED 6SMD

Package 6-SMD, J-Lead

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ASMB-TTB0-0A3A2 Specifications

Manufacturer Part Number ASMB-TTB0-0A3A2 Manufacturer Broadcom Limited Category Optoelectronics LED Indication - Discrete Package 6-SMD, J-Lead Series - Color Red, Green, Blue (RGB) Configuration Independent Lens Color - Lens Transparency Diffused Millicandela Rating 790mcd Red, 2400mcd Green, 500mcd Blue Lens Style/Size Round with Flat Top Voltage - Forward (Vf) (Typ) 2.1V Red, 3.1V Green, 3.1V Blue Current - Test 20mA Red, 20mA Green, 20mA Blue Viewing Angle 115° Mounting Type Surface Mount Wavelength - Dominant 621nm Red, 530nm Green, 470nm Blue Wavelength - Peak 635nm Red, 521nm Green, 464nm Blue Features - Package / Case 6-SMD, J-Lead Supplier Device Package 6-PLCC Size / Dimension 3.50mm L x 3.50mm W Height (Max) 2.80mm	•		
Category Optoelectronics LED Indication - Discrete Package 6-SMD, J-Lead Series - Color Red, Green, Blue (RGB) Configuration Independent Lens Color - Lens Transparency Diffused Millicandela Rating 790mcd Red, 2400mcd Green, 500mcd Blue Lens Style/Size Round with Flat Top Voltage - Forward (Vf) (Typ) 2.1V Red, 3.1V Green, 3.1V Blue Current - Test 20mA Red, 20mA Green, 20mA Blue Viewing Angle 115° Mounting Type Surface Mount Wavelength - Dominant 621nm Red, 530nm Green, 470nm Blue Wavelength - Peak 635nm Red, 521nm Green, 464nm Blue Features - Package / Case 6-SMD, J-Lead Supplier Device Package 6-PLCC Size / Dimension 3.50mm L x 3.50mm W Height (Max) 2.80mm	Manufacturer Part Number	ASMB-TTB0-0A3A2	
Package 6-SMD, J-Lead Series - Color Red, Green, Blue (RGB) Configuration Independent Lens Color - Lens Transparency Diffused Millicandela Rating 790mcd Red, 2400mcd Green, 500mcd Blue Lens Style/Size Round with Flat Top Voltage - Forward (Vf) (Typ) 2.1V Red, 3.1V Green, 3.1V Blue Current - Test 20mA Red, 20mA Green, 20mA Blue Viewing Angle 115° Mounting Type Surface Mount Wavelength - Dominant 621nm Red, 530nm Green, 470nm Blue Wavelength - Peak 635nm Red, 521nm Green, 464nm Blue Features - Package / Case 6-SMD, J-Lead Supplier Device Package 6-PLCC Size / Dimension 3.50mm L x 3.50mm W Height (Max) 2.80mm	Manufacturer	Broadcom Limited	
Package 6-SMD, J-Lead Series - Color Red, Green, Blue (RGB) Configuration Independent Lens Color - Lens Transparency Diffused Millicandela Rating 790mcd Red, 2400mcd Green, 500mcd Blue Lens Style/Size Round with Flat Top Voltage - Forward (Vf) (Typ) 2.1V Red, 3.1V Green, 3.1V Blue Current - Test 20mA Red, 20mA Green, 20mA Blue Viewing Angle 115° Mounting Type Surface Mount Wavelength - Dominant 621nm Red, 530nm Green, 470nm Blue Wavelength - Peak 635nm Red, 521nm Green, 464nm Blue Features - Package / Case 6-SMD, J-Lead Supplier Device Package 6-PLCC Size / Dimension 3.50mm L x 3.50mm W Height (Max) 2.80mm	Category	Optoelectronics	
Series - Color Red, Green, Blue (RGB) Configuration Independent Lens Color - Lens Transparency Diffused Millicandela Rating 790mcd Red, 2400mcd Green, 500mcd Blue Lens Style/Size Round with Flat Top Voltage - Forward (Vf) (Typ) 2.1V Red, 3.1V Green, 3.1V Blue Current - Test 20mA Red, 20mA Green, 20mA Blue Viewing Angle 115° Mounting Type Surface Mount Wavelength - Dominant 621nm Red, 530nm Green, 470nm Blue Wavelength - Peak 635nm Red, 521nm Green, 464nm Blue Features - Package / Case 6-SMD, J-Lead Supplier Device Package 6-PLCC Size / Dimension 3.50mm L x 3.50mm W Height (Max) 2.80mm		LED Indication - Discrete	
ColorRed, Green, Blue (RGB)ConfigurationIndependentLens Color-Lens TransparencyDiffusedMillicandela Rating790mcd Red, 2400mcd Green, 500mcd BlueLens Style/SizeRound with Flat TopVoltage - Forward (Vf) (Typ)2.1V Red, 3.1V Green, 3.1V BlueCurrent - Test20mA Red, 20mA Green, 20mA BlueViewing Angle115°Mounting TypeSurface MountWavelength - Dominant621nm Red, 530nm Green, 470nm BlueWavelength - Peak635nm Red, 521nm Green, 464nm BlueFeatures-Package / Case6-SMD, J-LeadSupplier Device Package6-PLCCSize / Dimension3.50mm L x 3.50mm WHeight (Max)2.80mm	Package	6-SMD, J-Lead	
Configuration Independent Lens Color - Lens Transparency Diffused Millicandela Rating 790mcd Red, 2400mcd Green, 500mcd Blue Lens Style/Size Round with Flat Top Voltage - Forward (Vf) (Typ) 2.1V Red, 3.1V Green, 3.1V Blue Current - Test 20mA Red, 20mA Green, 20mA Blue Viewing Angle 115° Mounting Type Surface Mount Wavelength - Dominant 621nm Red, 530nm Green, 470nm Blue Wavelength - Peak 635nm Red, 521nm Green, 464nm Blue Features - Package / Case 6-SMD, J-Lead Supplier Device Package 6-PLCC Size / Dimension 3.50mm L x 3.50mm W Height (Max) 2.80mm	Series	-	
Lens Color Lens Transparency Diffused Millicandela Rating 790mcd Red, 2400mcd Green, 500mcd Blue Lens Style/Size Round with Flat Top Voltage - Forward (Vf) (Typ) 2.1V Red, 3.1V Green, 3.1V Blue Current - Test 20mA Red, 20mA Green, 20mA Blue Viewing Angle 115° Mounting Type Surface Mount Wavelength - Dominant 621nm Red, 530nm Green, 470nm Blue Wavelength - Peak 635nm Red, 521nm Green, 464nm Blue Features - Package / Case 6-SMD, J-Lead Supplier Device Package 6-PLCC Size / Dimension 3.50mm L x 3.50mm W Height (Max) 2.80mm	Color	Red, Green, Blue (RGB)	
Lens TransparencyDiffusedMillicandela Rating790mcd Red, 2400mcd Green, 500mcd BlueLens Style/SizeRound with Flat TopVoltage - Forward (Vf) (Typ)2.1V Red, 3.1V Green, 3.1V BlueCurrent - Test20mA Red, 20mA Green, 20mA BlueViewing Angle115°Mounting TypeSurface MountWavelength - Dominant621nm Red, 530nm Green, 470nm BlueWavelength - Peak635nm Red, 521nm Green, 464nm BlueFeatures-Package / Case6-SMD, J-LeadSupplier Device Package6-PLCCSize / Dimension3.50mm L x 3.50mm WHeight (Max)2.80mm	Configuration	Independent	
Millicandela Rating Tens Style/Size Round with Flat Top Voltage - Forward (Vf) (Typ) 2.1V Red, 3.1V Green, 3.1V Blue Current - Test 20mA Red, 20mA Green, 20mA Blue Viewing Angle 115° Mounting Type Surface Mount Wavelength - Dominant 621nm Red, 530nm Green, 470nm Blue Wavelength - Peak 635nm Red, 521nm Green, 464nm Blue Features - Package / Case 6-SMD, J-Lead Supplier Device Package 6-PLCC Size / Dimension 3.50mm L x 3.50mm W Height (Max) 2.80mm	Lens Color	-	
Lens Style/Size Round with Flat Top Voltage - Forward (Vf) (Typ) 2.1V Red, 3.1V Green, 3.1V Blue Current - Test 20mA Red, 20mA Green, 20mA Blue Viewing Angle 115° Mounting Type Surface Mount Wavelength - Dominant 621nm Red, 530nm Green, 470nm Blue Wavelength - Peak 635nm Red, 521nm Green, 464nm Blue Features - Package / Case 6-SMD, J-Lead Supplier Device Package 6-PLCC Size / Dimension 3.50mm L x 3.50mm W Height (Max) 2.80mm	Lens Transparency	Diffused	
Voltage - Forward (Vf) (Typ) 2.1V Red, 3.1V Green, 3.1V Blue Current - Test 20mA Red, 20mA Green, 20mA Blue Viewing Angle 115° Mounting Type Surface Mount 621nm Red, 530nm Green, 470nm Blue Wavelength - Dominant 635nm Red, 521nm Green, 464nm Blue Features - Package / Case 6-SMD, J-Lead Supplier Device Package 6-PLCC Size / Dimension 3.50mm L x 3.50mm W Height (Max) 2.80mm	Millicandela Rating	790mcd Red, 2400mcd Green, 500mcd Blue	
Current - Test 20mA Red, 20mA Green, 20mA Blue Viewing Angle 115° Mounting Type Surface Mount 621nm Red, 530nm Green, 470nm Blue Wavelength - Dominant 635nm Red, 521nm Green, 464nm Blue Features - Package / Case 6-SMD, J-Lead Supplier Device Package 6-PLCC Size / Dimension 3.50mm L x 3.50mm W Height (Max) 2.80mm	Lens Style/Size	Round with Flat Top	
Viewing Angle115°Mounting TypeSurface MountWavelength - Dominant621nm Red, 530nm Green, 470nm BlueWavelength - Peak635nm Red, 521nm Green, 464nm BlueFeatures-Package / Case6-SMD, J-LeadSupplier Device Package6-PLCCSize / Dimension3.50mm L x 3.50mm WHeight (Max)2.80mm	Voltage - Forward (Vf) (Typ)	2.1V Red, 3.1V Green, 3.1V Blue	
Mounting Type Surface Mount Wavelength - Dominant 621nm Red, 530nm Green, 470nm Blue Wavelength - Peak 635nm Red, 521nm Green, 464nm Blue Features - Package / Case 6-SMD, J-Lead Supplier Device Package 6-PLCC Size / Dimension 3.50mm L x 3.50mm W Height (Max) 2.80mm	Current - Test	20mA Red, 20mA Green, 20mA Blue	
Wavelength - Dominant 621nm Red, 530nm Green, 470nm Blue Wavelength - Peak 635nm Red, 521nm Green, 464nm Blue Features - Package / Case 6-SMD, J-Lead Supplier Device Package 6-PLCC Size / Dimension 3.50mm L x 3.50mm W Height (Max) 2.80mm	Viewing Angle	115°	
Wavelength - Peak 635nm Red, 521nm Green, 464nm Blue Features - Package / Case 6-SMD, J-Lead Supplier Device Package 6-PLCC Size / Dimension 3.50mm L x 3.50mm W Height (Max) 2.80mm	Mounting Type	Surface Mount	
Features - Package / Case 6-SMD, J-Lead Supplier Device Package 6-PLCC Size / Dimension 3.50mm L x 3.50mm W Height (Max) 2.80mm	Wavelength - Dominant	621nm Red, 530nm Green, 470nm Blue	
Package / Case 6-SMD, J-Lead Supplier Device Package 6-PLCC Size / Dimension 3.50mm L x 3.50mm W Height (Max) 2.80mm	Wavelength - Peak	635nm Red, 521nm Green, 464nm Blue	
Supplier Device Package 6-PLCC Size / Dimension 3.50mm L x 3.50mm W Height (Max) 2.80mm	Features	-	
Size / Dimension 3.50mm L x 3.50mm W Height (Max) 2.80mm	Package / Case	6-SMD, J-Lead	
Height (Max) 2.80mm	Supplier Device Package	6-PLCC	
	Size / Dimension	3.50mm L x 3.50mm W	
Report errors?	Height (Max)	2.80mm	
		R	deport errors?

ASMB-TTB0-0A3A2 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ASMB-TTB0-0A3A2 Payment Methods



















ASMB-TTB0-0A3A2 Shipping Methods













If you have any question about ASMB-TTB0-0A3A2, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com