



### **ASMB-TTB2-0C3A2 Information**

Heisener.com

Part NumberASMB-TTB2-0C3A2ManufacturerBroadcom LimitedCategoryOptoelectronics

LED Indication - Discrete

**Description** LED TRICOLOR RGB TALL BLACK 6PLC

Package 6-SMD, J-Lead

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **ASMB-TTB2-0C3A2** Specifications

Manufacturer Part Number         ASMB-TTB2-0C3A2           Manufacturer         Broadcom Limited           Category         Optoelectronics           LED Indication - Discrete           Package         6-SMD, J-Lead           Series         -           Color         Red, Green, Blue (RGB)           Configuration         Independent           Lens Color         -           Lens Transparency         Diffused           Millicandela Rating         790mcd Red, 2000mcd Green, 380mcd Blue           Lens Style/Size         Round with Flat Top           Voltage - Forward (Vf) (Typ)         2.1V Red, 3V Green, 3V Blue           Current - Test         20mA Red, 20mA Green, 20mA Blue           Viewing Angle         115°           Mounting Type         -           Wavelength - Dominant         621nm Red, 529nm Green, 470nm Blue           Wavelength - Peak         635nm Red, 521nm Green, 464nm Blue           Features         IPx6, IPx8           Package / Case         6-SMD, J-Lead           Supplier Device Package         6-PLCC           Size / Dimension         3.50mm L x 3.50mm W           Height (Max)         3.00mm	•		
Category         Optoelectronics           LED Indication - Discrete           Package         6-SMD, J-Lead           Series         -           Color         Red, Green, Blue (RGB)           Configuration         Independent           Lens Color         -           Lens Transparency         Diffused           Millicandela Rating         790mcd Red, 2000mcd Green, 380mcd Blue           Lens Style/Size         Round with Flat Top           Voltage - Forward (Vf) (Typ)         2.1V Red, 3V Green, 3V Blue           Current - Test         20mA Red, 20mA Green, 20mA Blue           Viewing Angle         115°           Mounting Type         -           Wavelength - Dominant         621nm Red, 529nm Green, 470nm Blue           Wavelength - Peak         635nm Red, 521nm Green, 464nm Blue           Features         IPx6, IPx8           Package / Case         6-SMD, J-Lead           Supplier Device Package         6-PLCC           Size / Dimension         3.50mm L x 3.50mm W           Height (Max)         3.00mm	Manufacturer Part Number	ASMB-TTB2-0C3A2	
Package         6-SMD, J-Lead           Series         -           Color         Red, Green, Blue (RGB)           Configuration         Independent           Lens Color         -           Lens Transparency         Diffused           Millicandela Rating         790mcd Red, 2000mcd Green, 380mcd Blue           Lens Style/Size         Round with Flat Top           Voltage - Forward (Vf) (Typ)         2.1V Red, 3V Green, 3V Blue           Current - Test         20mA Red, 20mA Green, 20mA Blue           Viewing Angle         115°           Mounting Type         -           Wavelength - Dominant         621nm Red, 529nm Green, 470nm Blue           Wavelength - Peak         635nm Red, 521nm Green, 464nm Blue           Features         IPx6, IPx8           Package / Case         6-SMD, J-Lead           Supplier Device Package         6-PLCC           Size / Dimension         3.50mm L x 3.50mm W           Height (Max)         3.00mm	Manufacturer	Broadcom Limited	
Package 6-SMD, J-Lead  Series - Color Red, Green, Blue (RGB) Configuration Independent Lens Color - Lens Transparency Diffused Millicandela Rating 790mcd Red, 2000mcd Green, 380mcd Blue Lens Style/Size Round with Flat Top Voltage - Forward (Vf) (Typ) 2.1V Red, 3V Green, 3V Blue Current - Test 20mA Red, 20mA Green, 20mA Blue Viewing Angle 115° Mounting Type - Wavelength - Dominant 621nm Red, 529nm Green, 470nm Blue Wavelength - Peak 635nm Red, 521nm Green, 464nm Blue Features IPx6, IPx8 Package / Case 6-SMD, J-Lead Supplier Device Package 6-PLCC Size / Dimension 3.50mm L x 3.50mm W Height (Max) 3.00mm	Category	Optoelectronics	
Series - Color Red, Green, Blue (RGB) Configuration Independent Lens Color - Lens Transparency Diffused Millicandela Rating 790mcd Red, 2000mcd Green, 380mcd Blue Lens Style/Size Round with Flat Top Voltage - Forward (Vf) (Typ) 2.1V Red, 3V Green, 3V Blue Current - Test 20mA Red, 20mA Green, 20mA Blue Viewing Angle 115° Mounting Type - Wavelength - Dominant 621nm Red, 529nm Green, 470nm Blue Wavelength - Peak 635nm Red, 521nm Green, 464nm Blue Features IPx6, IPx8 Package / Case 6-SMD, J-Lead Supplier Device Package 6-PLCC Size / Dimension 3.50mm L x 3.50mm W Height (Max) 3.00mm		LED Indication - Discrete	
ColorRed, Green, Blue (RGB)ConfigurationIndependentLens Color-Lens TransparencyDiffusedMillicandela Rating790mcd Red, 2000mcd Green, 380mcd BlueLens Style/SizeRound with Flat TopVoltage - Forward (Vf) (Typ)2.1V Red, 3V Green, 3V BlueCurrent - Test20mA Red, 20mA Green, 20mA BlueViewing Angle115°Mounting Type-Wavelength - Dominant621nm Red, 529nm Green, 470nm BlueWavelength - Peak635nm Red, 521nm Green, 464nm BlueFeaturesIPx6, IPx8Package / Case6-SMD, J-LeadSupplier Device Package6-PLCCSize / Dimension3.50mm L x 3.50mm WHeight (Max)3.00mm	Package	6-SMD, J-Lead	
Configuration Independent  Lens Color - Lens Transparency Diffused  Millicandela Rating 790mcd Red, 2000mcd Green, 380mcd Blue Lens Style/Size Round with Flat Top  Voltage - Forward (Vf) (Typ) 2.1V Red, 3V Green, 3V Blue  Current - Test 20mA Red, 20mA Green, 20mA Blue  Viewing Angle 115°  Mounting Type - Wavelength - Dominant 621nm Red, 529nm Green, 470nm Blue  Wavelength - Peak 635nm Red, 521nm Green, 464nm Blue  Features IPx6, IPx8  Package / Case 6-SMD, J-Lead  Supplier Device Package 6-PLCC  Size / Dimension 3.50mm L x 3.50mm W  Height (Max) 3.00mm	Series	-	
Lens Color Lens Transparency Diffused Millicandela Rating 790mcd Red, 2000mcd Green, 380mcd Blue Lens Style/Size Round with Flat Top Voltage - Forward (Vf) (Typ) 2.1V Red, 3V Green, 3V Blue Current - Test 20mA Red, 20mA Green, 20mA Blue Viewing Angle 115° Mounting Type - Wavelength - Dominant 621nm Red, 529nm Green, 470nm Blue Wavelength - Peak 635nm Red, 521nm Green, 464nm Blue Features IPx6, IPx8 Package / Case 6-SMD, J-Lead Supplier Device Package 6-PLCC Size / Dimension 3.50mm L x 3.50mm W Height (Max) 3.00mm	Color	Red, Green, Blue (RGB)	
Lens TransparencyDiffusedMillicandela Rating790mcd Red, 2000mcd Green, 380mcd BlueLens Style/SizeRound with Flat TopVoltage - Forward (Vf) (Typ)2.1V Red, 3V Green, 3V BlueCurrent - Test20mA Red, 20mA Green, 20mA BlueViewing Angle115°Mounting Type-Wavelength - Dominant621nm Red, 529nm Green, 470nm BlueWavelength - Peak635nm Red, 521nm Green, 464nm BlueFeaturesIPx6, IPx8Package / Case6-SMD, J-LeadSupplier Device Package6-PLCCSize / Dimension3.50mm L x 3.50mm WHeight (Max)3.00mm	Configuration	Independent	
Millicandela Rating  Tens Style/Size  Round with Flat Top  Voltage - Forward (Vf) (Typ)  2.1V Red, 3V Green, 3V Blue  Current - Test  20mA Red, 20mA Green, 20mA Blue  Viewing Angle  115°  Mounting Type  - Wavelength - Dominant  621nm Red, 529nm Green, 470nm Blue  Wavelength - Peak  635nm Red, 521nm Green, 464nm Blue  Features  IPx6, IPx8  Package / Case  6-SMD, J-Lead  Supplier Device Package  6-PLCC  Size / Dimension  3.50mm L x 3.50mm W  Height (Max)  3.00mm	Lens Color	-	
Lens Style/Size Round with Flat Top  Voltage - Forward (Vf) (Typ) 2.1V Red, 3V Green, 3V Blue  Current - Test 20mA Red, 20mA Green, 20mA Blue  Viewing Angle 115°  Mounting Type -  Wavelength - Dominant 621nm Red, 529nm Green, 470nm Blue  Wavelength - Peak 635nm Red, 521nm Green, 464nm Blue  Features IPx6, IPx8  Package / Case 6-SMD, J-Lead  Supplier Device Package 6-PLCC  Size / Dimension 3.50mm L x 3.50mm W  Height (Max) 3.00mm	Lens Transparency	Diffused	
Voltage - Forward (Vf) (Typ)  2.1V Red, 3V Green, 3V Blue  Current - Test  20mA Red, 20mA Green, 20mA Blue  Viewing Angle  115°  Mounting Type	Millicandela Rating	790mcd Red, 2000mcd Green, 380mcd Blue	
Current - Test  20mA Red, 20mA Green, 20mA Blue  Viewing Angle  115°  Mounting Type  - Wavelength - Dominant  621nm Red, 529nm Green, 470nm Blue  Wavelength - Peak  635nm Red, 521nm Green, 464nm Blue  Features  IPx6, IPx8  Package / Case  6-SMD, J-Lead  Supplier Device Package  6-PLCC  Size / Dimension  3.50mm L x 3.50mm W  Height (Max)  3.00mm	Lens Style/Size	Round with Flat Top	
Viewing Angle115°Mounting Type-Wavelength - Dominant621nm Red, 529nm Green, 470nm BlueWavelength - Peak635nm Red, 521nm Green, 464nm BlueFeaturesIPx6, IPx8Package / Case6-SMD, J-LeadSupplier Device Package6-PLCCSize / Dimension3.50mm L x 3.50mm WHeight (Max)3.00mm	Voltage - Forward (Vf) (Typ)	2.1V Red, 3V Green, 3V Blue	
Mounting Type	Current - Test	20mA Red, 20mA Green, 20mA Blue	
Wavelength - Dominant 621nm Red, 529nm Green, 470nm Blue Wavelength - Peak 635nm Red, 521nm Green, 464nm Blue Features IPx6, IPx8 Package / Case 6-SMD, J-Lead Supplier Device Package 6-PLCC Size / Dimension 3.50mm L x 3.50mm W Height (Max) 3.00mm	Viewing Angle	115°	
Wavelength - Peak 635nm Red, 521nm Green, 464nm Blue Features IPx6, IPx8 Package / Case 6-SMD, J-Lead Supplier Device Package 6-PLCC Size / Dimension 3.50mm L x 3.50mm W Height (Max) 3.00mm	Mounting Type	-	
Features IPx6, IPx8 Package / Case 6-SMD, J-Lead Supplier Device Package 6-PLCC Size / Dimension 3.50mm L x 3.50mm W Height (Max) 3.00mm	Wavelength - Dominant	621nm Red, 529nm Green, 470nm Blue	
Package / Case 6-SMD, J-Lead Supplier Device Package 6-PLCC Size / Dimension 3.50mm L x 3.50mm W Height (Max) 3.00mm	Wavelength - Peak	635nm Red, 521nm Green, 464nm Blue	
Supplier Device Package 6-PLCC Size / Dimension 3.50mm L x 3.50mm W Height (Max) 3.00mm	Features	IPx6, IPx8	
Size / Dimension 3.50mm L x 3.50mm W Height (Max) 3.00mm	Package / Case	6-SMD, J-Lead	
Height (Max) 3.00mm	Supplier Device Package	6-PLCC	
	Size / Dimension	3.50mm L x 3.50mm W	
Report errors?	Height (Max)	3.00mm	
			Report errors?

### **ASMB-TTB2-0C3A2** Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **ASMB-TTB2-0C3A2** Payment Methods



















## **ASMB-TTB2-0C3A2 Shipping Methods**













If you have any question about ASMB-TTB2-0C3A2, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com