



ASMT-BG20-AS000 Information



For Reference Only

Part Number ASMT-BG20-AS000
Manufacturer Broadcom Limited
Category Optoelectronics

LED Indication - Discrete

Description LED GREEN CLEAR 1209 SMD

Package 1209 (3224 Metric)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ASMT-BG20-AS000 Specifications

Manufacturer Part Number ASMT-BG20-AS000 Manufacturer Broadcom Limited Category Optoelectronics LED Indication - Discrete Package 1209 (3224 Metric) Series - Color Green Configuration - Lens Color Colorless Lens Transparency Clear Millicandela Rating 650mcd Lens Style/Size Round with Domed Top, 1.80mm Voltage - Forward (Vf) (Typ) 2V Current - Test 20mA Viewing Angle 15° Mounting Type Surface Mount Wavelength - Dominant 569nm Wavelength - Peak 565nm Features - Package / Case 1209 (3224 Metric) Supplier Device Package - Size / Dimension 3.20mm L x 2.40mm W Height (Max) 2.40mm	*	
Category Optoelectronics LED Indication - Discrete Package 1209 (3224 Metric) Series - Color Green Configuration - Lens Color Colorless Lens Transparency Clear Millicandela Rating 650mcd Lens Style/Size Round with Domed Top, 1.80mm Voltage - Forward (Vf) (Typ) 2V Current - Test 20mA Viewing Angle 15° Mounting Type Surface Mount Wavelength - Dominant 569nm Wavelength - Peak 565nm Features - Package / Case 1209 (3224 Metric) Supplier Device Package - Size / Dimension 3.20mm L x 2.40mm W Height (Max) 2.40mm	Manufacturer Part Number	ASMT-BG20-AS000
Package 1209 (3224 Metric) Series - Color Green Configuration - Lens Color Colorless Lens Transparency Clear Millicandela Rating 650mcd Lens Style/Size Round with Domed Top, 1.80mm Voltage - Forward (Vf) (Typ) 2V Current - Test 20mA Viewing Angle 15° Mounting Type Surface Mount Wavelength - Dominant 569nm Wavelength - Peak 565nm Features - Package / Case 1209 (3224 Metric) Supplier Device Package - Size / Dimension 3.20mm L x 2.40mm W Height (Max) 2.40mm	Manufacturer	Broadcom Limited
Package 1209 (3224 Metric) Series - Color Green Configuration - Lens Color Colorless Lens Transparency Clear Millicandela Rating 650mcd Lens Style/Size Round with Domed Top, 1.80mm Voltage - Forward (Vf) (Typ) 2V Current - Test 20mA Viewing Angle 15° Mounting Type Surface Mount Wavelength - Dominant 569nm Wavelength - Peak 565nm Features - Package / Case 1209 (3224 Metric) Supplier Device Package - Size / Dimension 3.20mm L x 2.40mm W Height (Max) 2.40mm	Category	Optoelectronics
Series - Color Green Configuration - Lens Color Colorless Lens Transparency Clear Millicandela Rating 650mcd Lens Style/Size Round with Domed Top, 1.80mm Voltage - Forward (Vf) (Typ) 2V Current - Test 20mA Viewing Angle 15° Mounting Type Surface Mount Wavelength - Dominant 569m Wavelength - Peak 565nm Features - Package / Case 1209 (3224 Metric) Supplier Device Package - Size / Dimension 3.20mm L x 2.40mm W Height (Max) 2.40mm		LED Indication - Discrete
Color Green Configuration - Lens Color Colorless Lens Transparency Clear Millicandela Rating 650mcd Lens Style/Size Round with Domed Top, 1.80mm Voltage - Forward (Vf) (Typ) 2V Current - Test 20mA Viewing Angle 15° Mounting Type Surface Mount Wavelength - Dominant 569nm Wavelength - Peak 565nm Features - Package / Case 1209 (3224 Metric) Supplier Device Package - Size / Dimension 3.20mm L x 2.40mm W Height (Max) 2.40mm	Package	1209 (3224 Metric)
Configuration - Lens Color Colorless Lens Transparency Clear Millicandela Rating 650mcd Lens Style/Size Round with Domed Top, 1.80mm Voltage - Forward (Vf) (Typ) 2V Current - Test 20mA Viewing Angle 15° Mounting Type Surface Mount Wavelength - Dominant 569nm Wavelength - Peak 565nm Features - Package / Case 1209 (3224 Metric) Supplier Device Package - Size / Dimension 3.20mm L x 2.40mm W Height (Max) 2.40mm	Series	-
Lens ColorColorlessLens TransparencyClearMillicandela Rating650mcdLens Style/SizeRound with Domed Top, 1.80mmVoltage - Forward (Vf) (Typ)2VCurrent - Test20mAViewing Angle15°Mounting TypeSurface MountWavelength - Dominant569nmWavelength - Peak565nmFeatures-Package / Case1209 (3224 Metric)Supplier Device Package-Size / Dimension3.20mm L x 2.40mm WHeight (Max)2.40mm	Color	Green
Lens TransparencyClearMillicandela Rating650mcdLens Style/SizeRound with Domed Top, 1.80mmVoltage - Forward (Vf) (Typ)2VCurrent - Test20mAViewing Angle15°Mounting TypeSurface MountWavelength - Dominant569nmWavelength - Peak565nmFeatures-Package / Case1209 (3224 Metric)Supplier Device Package-Size / Dimension3.20mm L x 2.40mm WHeight (Max)2.40mm	Configuration	-
Millicandela Rating Lens Style/Size Round with Domed Top, 1.80mm Voltage - Forward (Vf) (Typ) 2V Current - Test 20mA Viewing Angle 15° Mounting Type Surface Mount Wavelength - Dominant 569nm Wavelength - Peak 565nm Features - Package / Case 1209 (3224 Metric) Supplier Device Package Size / Dimension Height (Max) 650mcd Round with Domed Top, 1.80mm 2V 2V 2V 2mA 569mA 569nm 569nm 569nm 565nm 565nm 565nm 5620 (3224 Metric) 500mm L x 2.40mm W 400mm	Lens Color	Colorless
Lens Style/SizeRound with Domed Top, 1.80mmVoltage - Forward (Vf) (Typ)2VCurrent - Test20mAViewing Angle15°Mounting TypeSurface MountWavelength - Dominant569nmWavelength - Peak565nmFeatures-Package / Case1209 (3224 Metric)Supplier Device Package-Size / Dimension3.20mm L x 2.40mm WHeight (Max)2.40mm	Lens Transparency	Clear
Voltage - Forward (Vf) (Typ) Current - Test 20mA Viewing Angle 15° Mounting Type Surface Mount Wavelength - Dominant 569nm Wavelength - Peak 565nm Features - Package / Case 1209 (3224 Metric) Supplier Device Package Size / Dimension Height (Max) 2V 20mA 15° Surface Mount 569nm 569nm 565nm 7 20mA 569nm 565nm 565nm 7 20m	Millicandela Rating	650mcd
Current - Test 20mA Viewing Angle 15° Mounting Type Surface Mount Wavelength - Dominant 569nm Wavelength - Peak 565nm Features - Package / Case 1209 (3224 Metric) Supplier Device Package - Size / Dimension 3.20mm L x 2.40mm W Height (Max) 2.40mm	Lens Style/Size	Round with Domed Top, 1.80mm
Viewing Angle15°Mounting TypeSurface MountWavelength - Dominant569nmWavelength - Peak565nmFeatures-Package / Case1209 (3224 Metric)Supplier Device Package-Size / Dimension3.20mm L x 2.40mm WHeight (Max)2.40mm	Voltage - Forward (Vf) (Typ)	2V
Mounting Type Surface Mount Wavelength - Dominant S69nm Wavelength - Peak 565nm Features - Package / Case 1209 (3224 Metric) Supplier Device Package - Size / Dimension 3.20mm L x 2.40mm W Height (Max) 2.40mm	Current - Test	20mA
Wavelength - Dominant Wavelength - Peak 569nm Features - Package / Case 1209 (3224 Metric) Supplier Device Package - Size / Dimension 3.20mm L x 2.40mm W Height (Max) 2.40mm	Viewing Angle	15°
Wavelength - Peak 565nm Features - Package / Case 1209 (3224 Metric) Supplier Device Package - Size / Dimension 3.20mm L x 2.40mm W Height (Max) 2.40mm	Mounting Type	Surface Mount
Features - Package / Case 1209 (3224 Metric) Supplier Device Package - Size / Dimension 3.20mm L x 2.40mm W Height (Max) 2.40mm	Wavelength - Dominant	569nm
Package / Case 1209 (3224 Metric) Supplier Device Package - Size / Dimension 3.20mm L x 2.40mm W Height (Max) 2.40mm	Wavelength - Peak	565nm
Supplier Device Package - Size / Dimension 3.20mm L x 2.40mm W Height (Max) 2.40mm	Features	-
Size / Dimension 3.20mm L x 2.40mm W Height (Max) 2.40mm	Package / Case	1209 (3224 Metric)
Height (Max) 2.40mm	Supplier Device Package	-
	Size / Dimension	3.20mm L x 2.40mm W
Report errors?	Height (Max)	2.40mm
1		Report errors?

ASMT-BG20-AS000 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ASMT-BG20-AS000 Payment Methods



















ASMT-BG20-AS000 Shipping Methods













If you have any question about ASMT-BG20-AS000, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com