



ASMT-QHB2-FEF0E Information



For Reference Only

Part Number ASMT-QHB2-FEF0E

Manufacturer Broadcom Limited

Category Optoelectronics
LED Lighting - Color

Description LED INDICATOR 0.5W RED/ORN 4PLCC

Package 4-PLCC

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ASMT-QHB2-FEF0E Specifications

Manufacturer Part Number ASMT-QHB2-FEF0E Manufacturer Broadcom Limited Category Optoelectronics LED Lighting - Color Package 4-PLCC Series - Color Red Wavelength 618nm (611nm ~ 625nm) Current - Test 150mA Voltage - Forward (Vf) (Typ) 2.7V Lumens/Watt @ Current - Test 40 lm/W Current - Max 150mA Flux @ Current/Temperature - Test 16 lm (12 lm ~ 20 lm) Temperature - Test 25°C Viewing Angle 120° Mounting Type Surface Mount Package / Case 4-PLCC Supplier Device Package 4-PLCC Size / Dimension 0.126" L x 0.110" W (3.20mm x 2.80mm) Height - Seated (Max) 0.083" (2.10mm)		
Category Optoelectronics LED Lighting - Color Package 4-PLCC Series - Color Red Wavelength 618nm (611nm ~ 625nm) Current - Test 150mA Voltage - Forward (Vf) (Typ) 2.7V Lumens/Watt @ Current - Test 40 lm/W Current - Max 150mA Flux @ Current/Temperature - Test 16 lm (12 lm ~ 20 lm) Temperature - Test 25°C Viewing Angle 120° Mounting Type Surface Mount Package / Case 4-PLCC Supplier Device Package 4-PLCC Size / Dimension 0.126" L x 0.110" W (3.20mm x 2.80mm) Height - Seated (Max) 0.083" (2.10mm)	Manufacturer Part Number	ASMT-QHB2-FEF0E
Package 4-PLCC Series - Color Red Wavelength 618nm (61nm ~ 625nm) Current - Test 150mA Voltage - Forward (Vf) (Typ) 2.7V Lumens/Watt @ Current - Test 40 lm/W Current - Max 150mA Flux @ Current/Temperature - Test 16 lm (12 lm ~ 20 lm) Temperature - Test 25°C Viewing Angle 120° Mounting Type Surface Mount Package / Case 4-PLCC Supplier Device Package 4-PLCC Size / Dimension 0.126" L x 0.110" W (3.20mm x 2.80mm) Height - Seated (Max) 0.083" (2.10mm)	Manufacturer	Broadcom Limited
Package 4-PLCC Series - Color Red Wavelength 618nm (611nm ~ 625nm) Current - Test 150mA Voltage - Forward (Vf) (Typ) 2.7V Lumens/Watt @ Current - Test 40 lm/W Current - Max 150mA Flux @ Current/Temperature - Test 16 lm (12 lm ~ 20 lm) Temperature - Test 25°C Viewing Angle 120° Mounting Type Surface Mount Package / Case 4-PLCC Supplier Device Package 4-PLCC Size / Dimension 0.126" L x 0.110" W (3.20mm x 2.80mm) Height - Seated (Max) 0.083" (2.10mm)	Category	Optoelectronics
Series - Color Red Wavelength 618nm (611nm ~ 625nm) Current - Test 150mA Voltage - Forward (Vf) (Typ) 2.7V Lumens/Watt @ Current - Test 40 lm/W Current - Max 150mA Flux @ Current/Temperature - Test 16 lm (12 lm ~ 20 lm) Temperature - Test 25°C Viewing Angle 120° Mounting Type Surface Mount Package / Case 4-PLCC Supplier Device Package 4-PLCC Size / Dimension 0.126" L x 0.110" W (3.20mm x 2.80mm) Height - Seated (Max) 0.083" (2.10mm)		LED Lighting - Color
Color Red Wavelength 618nm (611nm ~ 625nm) Current - Test 150mA Voltage - Forward (Vf) (Typ) 2.7V Lumens/Watt @ Current - Test 40 lm/W Current - Max 150mA Flux @ Current/Temperature - Test 16 lm (12 lm ~ 20 lm) Temperature - Test 25°C Viewing Angle 120° Mounting Type Surface Mount Package / Case 4-PLCC Supplier Device Package 4-PLCC Size / Dimension 0.126" L x 0.110" W (3.20mm x 2.80mm) Height - Seated (Max) 0.083" (2.10mm)	Package	4-PLCC
Wavelength Current - Test 150mA Voltage - Forward (Vf) (Typ) 2.7V Lumens/Watt @ Current - Test 40 lm/W Current - Max 150mA Flux @ Current/Temperature - Test 16 lm (12 lm ~ 20 lm) Temperature - Test 25°C Viewing Angle 120° Mounting Type Surface Mount Package / Case 4-PLCC Supplier Device Package 4-PLCC Size / Dimension Height - Seated (Max) 0.083" (2.10mm)	Series	-
Current - Test 150mA Voltage - Forward (Vf) (Typ) 2.7V Lumens/Watt @ Current - Test 40 lm/W Current - Max 150mA Flux @ Current/Temperature - Test 16 lm (12 lm ~ 20 lm) Temperature - Test 25°C Viewing Angle 120° Mounting Type Surface Mount Package / Case 4-PLCC Supplier Device Package 4-PLCC Size / Dimension 0.126" L x 0.110" W (3.20mm x 2.80mm) Height - Seated (Max) 0.083" (2.10mm)	Color	Red
Voltage - Forward (Vf) (Typ) Lumens/Watt @ Current - Test 40 lm/W Current - Max 150mA Flux @ Current/Temperature - Test 16 lm (12 lm ~ 20 lm) Temperature - Test 25°C Viewing Angle 120° Mounting Type Surface Mount Package / Case 4-PLCC Supplier Device Package Size / Dimension Height - Seated (Max) 2.7V 40 lm/W 40 lm	Wavelength	618nm (611nm ~ 625nm)
Lumens/Watt @ Current - Test40 lm/WCurrent - Max150mAFlux @ Current/Temperature - Test16 lm (12 lm ~ 20 lm)Temperature - Test25°CViewing Angle120°Mounting TypeSurface MountPackage / Case4-PLCCSupplier Device Package4-PLCCSize / Dimension0.126" L x 0.110" W (3.20mm x 2.80mm)Height - Seated (Max)0.083" (2.10mm)	Current - Test	150mA
Current - Max Flux @ Current/Temperature - Test 16 lm (12 lm ~ 20 lm) Temperature - Test 25°C Viewing Angle 120° Mounting Type Surface Mount Package / Case 4-PLCC Supplier Device Package 4-PLCC Size / Dimension 0.126" L x 0.110" W (3.20mm x 2.80mm) Height - Seated (Max) 0.083" (2.10mm)	Voltage - Forward (Vf) (Typ)	2.7V
Flux @ Current/Temperature - Test 16 lm (12 lm ~ 20 lm) Temperature - Test 25°C Viewing Angle 120° Mounting Type Surface Mount Package / Case 4-PLCC Supplier Device Package 4-PLCC Size / Dimension 0.126" L x 0.110" W (3.20mm x 2.80mm) Height - Seated (Max) 0.083" (2.10mm)	Lumens/Watt @ Current - Test	40 lm/W
Temperature - Test 25°C Viewing Angle 120° Mounting Type Surface Mount Package / Case 4-PLCC Supplier Device Package 4-PLCC Size / Dimension 0.126" L x 0.110" W (3.20mm x 2.80mm) Height - Seated (Max) 0.083" (2.10mm)	Current - Max	150mA
Viewing Angle120°Mounting TypeSurface MountPackage / Case4-PLCCSupplier Device Package4-PLCCSize / Dimension0.126" L x 0.110" W (3.20mm x 2.80mm)Height - Seated (Max)0.083" (2.10mm)	Flux @ Current/Temperature - Test	16 lm (12 lm ~ 20 lm)
Mounting Type Surface Mount Package / Case 4-PLCC Supplier Device Package 4-PLCC Size / Dimension 0.126" L x 0.110" W (3.20mm x 2.80mm) Height - Seated (Max) 0.083" (2.10mm)	Temperature - Test	25°C
Package / Case 4-PLCC Supplier Device Package 4-PLCC Size / Dimension 0.126" L x 0.110" W (3.20mm x 2.80mm) Height - Seated (Max) 0.083" (2.10mm)	Viewing Angle	120°
Supplier Device Package 4-PLCC Size / Dimension 0.126" L x 0.110" W (3.20mm x 2.80mm) Height - Seated (Max) 0.083" (2.10mm)	Mounting Type	Surface Mount
Size / Dimension 0.126" L x 0.110" W (3.20mm x 2.80mm) Height - Seated (Max) 0.083" (2.10mm)	Package / Case	4-PLCC
Height - Seated (Max) 0.083" (2.10mm)	Supplier Device Package	4-PLCC
	Size / Dimension	0.126" L x 0.110" W (3.20mm x 2.80mm)
Report errors?	Height - Seated (Max)	0.083" (2.10mm)
		Report errors?

ASMT-QHB2-FEF0E Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ASMT-QHB2-FEF0E Payment Methods



















ASMT-QHB2-FEF0E Shipping Methods













If you have any question about ASMT-QHB2-FEF0E, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com