

ASTMHTA-50.000MHZ-AR-E-T3

ASTMHTA-50.000MHZ-AR-E-T3 Information



Part NumberASTMHTA-50.000MHZ-AR-E-T3ManufacturerAbracon LLCCategoryCrystals, Oscillators, Resonators
OscillatorsDescriptionOSC MEMS 50MHZ H/LVCMOS SMDPackage4-SMD, No Lead
For the pricing/inventory/lead time, please contact
us
Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



ASTMHTA-50.000MHZ-AR-E-T3 Specifications

Manufacturer Part NumberASTMHTA-50,000MHZ-AR-E-T3ManufacturerAbracon LLCCategoryCrystals, Oscillators, ResonatorsPackageASMD, No LeadSeriesASTMHTSpriesASTMHTTypeMEMS (Silicon)FrequencySoMHzOutputLVCMOSVoltage - Supply2.25 V ~ 3.63 VFrequency Stability-25pmOperating Temperature-40°C ~ 125°CCurrent - Supply(Max)Surface MountAtings-Atings-Auding TypeSurface MountPackage / CaseASMD, No LeadSize / Dimension0.079" L x 0.063" W (2.00mm x 1.60mm)OutputDorgon L outputCorrent - Supply(Max)-Astings-Mounting TypeSurface MountPackage / CaseASMD, No LeadSize / Dimension0.079" L x 0.063" W (2.00mm x 1.60mm)Astingt-Mount-Dire Mount-Dire Mount-<		
CategoryCrystals, Oscillators, ResonatorsOscillatorsPackage4-SMD, No LeadSeriesASTMHTTypeMEMS (Silicon)Frequency50MHzFunctionEnable/DisableOutputLVCMOSVoltage - Supply2.25 V ~ 3.63 VFrequency Stability±25pmOperating Temperature-40°C ~ 125°CCurrent - Supply (Max)-Ratings-Mounting TypeSurface MountPackage / Case4.SMD, No LeadSize / Dimension0.031" (0.80mm)	Manufacturer Part Number	ASTMHTA-50.000MHZ-AR-E-T3
OscillatorsPackage4-SMD, No LeadSeriesASTMHTTypeMEMS (Silicon)Frequency50MHzFunctionEnabe/DisableOutputLVCMOSVoltage - Supply2.25 V ~ 3.63 VPrequency Stability±25pmOperating Temperature-Qurtent - Supply (Max).Ratings-Package / Case4.SMD, No LeadSize / Dimension0.079" L x 0.063"W (2.00mm x 1.60mm)Height - Seated (Max)0.031" (0.80mm)	Manufacturer	Abracon LLC
Package4-SMD, No LeadSeriesASTMHTTypeMEMS (Silicon)Frequency50MHzFunctionEnable/DisableOutputLVCMOSVoltage - Supply2.25 V ~ 3.63 VOperating Temperature-40°C ~ 125°CCurrent - Supply (Max).Ratings-Package / CaseSurface MountPackage / Case0.079" L x 0.063" W (2.00mm x 1.60mm)Height - Seated (Max)0.031" (0.80mm)	Category	Crystals, Oscillators, Resonators
SeriesASTMHTTypeMEMS (Silicon)Frequency50MHzFunctionEnable/DisableOutputLVCMOSVoltage - Supply2.25 V ~ 3.63 VFrequency Stability±25pmOperating Temperature-40°C ~ 125°CCurrent - Supply (Max)-Ratings-Mounting TypeSurface MountPackage / Case4.SMD, No LeadSize / Dimension0.031" (0.80mm)		Oscillators
TypeMEMS (Silicon)Frequency50MHzFunctionEnable/DisableOutputLVCMOSVoltage - Supply2.25 V ~ 3.63 VFrequency Stability±25pmOperating Temperature-40°C ~ 125°CCurrent - Supply (Max)-Ratings-Mounting TypeSurface MountPackage / Case4.SMD, No LeadSize / Dimension0.031" (0.80mm)	Package	4-SMD, No Lead
Frequency50MHzFrequencyEnable/DisableFunctionEnable/DisableOutputLVCMOSVoltage - Supply2.25 V ~ 3.63 VFrequency Stability±25pmOperating Temperature-40°C ~ 125°CCurrent - Supply (Max)-Ratings-Mounting TypeSurface MountPackage / Case4.5MD, No LeadSize / Dimension0.031" (0.80mm)	Series	ASTMHT
FunctionEnable/DisableFunctionEnable/DisableOutputLVCMOSVoltage - Supply2.25 V ~ 3.63 VFrequency Stability±25pmOperating Temperature-40°C ~ 125°CCurrent - Supply (Max)-Ratings-Mounting TypeSurface MountPackage / Case4.SMD, No LeadSize / Dimension0.079" L x 0.063" W (2.00mm x 1.60mm)Height - Seated (Max)0.031" (0.80mm)	Туре	MEMS (Silicon)
OutputLVCMOSVoltage - Supply2.25 V ~ 3.63 VFrequency Stability±25ppmOperating Temperature-40°C ~ 125°CCurrent - Supply (Max)-Ratings-Mounting TypeSurface MountPackage / Case4-SMD, No LeadSize / Dimension0.079" L x 0.063" W (2.00mm x 1.60mm)Height - Seated (Max)0.031" (0.80mm)	Frequency	50MHz
Voltage - Supply 2.25 V ~ 3.63 V Frequency Stability ±25ppm Operating Temperature -40°C ~ 125°C Current - Supply (Max) - Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.079" L x 0.063" W (2.00mm x 1.60mm) Height - Seated (Max) 0.031" (0.80mm)	Function	Enable/Disable
Frequency Stability±25pmOperating Temperature-40°C ~ 125°CCurrent - Supply (Max)-Ratings-Mounting TypeSurface MountPackage / Case4-SMD, No LeadSize / Dimension0.079" L x 0.063" W (2.00mm x 1.60mm)Height - Seated (Max)0.031" (0.80mm)	Output	LVCMOS
Operating Temperature-40°C ~ 125°CCurrent - Supply (Max)-Ratings-Mounting TypeSurface MountPackage / Case4-SMD, No LeadSize / Dimension0.079" L x 0.063" W (2.00mm x 1.60mm)Height - Seated (Max)0.031" (0.80mm)	Voltage - Supply	2.25 V ~ 3.63 V
Current - Supply (Max)-Ratings-Mounting TypeSurface MountPackage / Case4-SMD, No LeadSize / Dimension0.079" L x 0.063" W (2.00mm x 1.60mm)Height - Seated (Max)0.031" (0.80mm)	Frequency Stability	±25ppm
Ratings-Mounting TypeSurface MountPackage / Case4-SMD, No LeadSize / Dimension0.079" L x 0.063" W (2.00mm x 1.60mm)Height - Seated (Max)0.031" (0.80mm)	Operating Temperature	-40°C ~ 125°C
Mounting TypeSurface MountPackage / Case4-SMD, No LeadSize / Dimension0.079" L x 0.063" W (2.00mm x 1.60mm)Height - Seated (Max)0.031" (0.80mm)	Current - Supply (Max)	-
Package / Case 4-SMD, No Lead Size / Dimension 0.079" L x 0.063" W (2.00mm x 1.60mm) Height - Seated (Max) 0.031" (0.80mm)	Ratings	-
Size / Dimension 0.079" L x 0.063" W (2.00mm x 1.60mm) Height - Seated (Max) 0.031" (0.80mm)	Mounting Type	Surface Mount
Height - Seated (Max) 0.031" (0.80mm)	Package / Case	4-SMD, No Lead
	Size / Dimension	0.079" L x 0.063" W (2.00mm x 1.60mm)
	Height - Seated (Max)	0.031" (0.80mm)
Report errors		Report errors?

ASTMHTA-50.000MHZ-AR-E-T3 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about ASTMHTA-50.000MHZ-AR-E-T3, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com