


ASTMUPCFL-33-24.000MHZ-LJ-E-T3 Information



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



ASTMUPCFL-33-24.000MHZ-LJ-E-T3 Specifications

ManufacturerAbracon LLCCategoryCrystals, Oscillators, ResonatorsOscillatorsOscillatorsPackage4-SMD, No LeadSeriesASTMUPCTypeMEMS (Silicon)Frequency24MHzFunctionEnable/DisableOutputLVCMOSVoltage - Supply3.3VFrequency Stability±20ppmOperating Temperature-40°C ~ 85°CCurrent - Supply (Max)36mARatings-Mounting TypeSurface Mount		
CategoryCrystals, Oscillators, ResonatorsOscillatorsPackage4-SMD, No LeadSeriesASTMUPCTypeMEMS (Silicon)Frequency24MHzOutputEnable/DisableVoltage - Supply3.3VFrequency Stability±20pmOperating Temperature40°C ~ 85°CCurrent - Supply (Max)36mARatings-Mounting TypeSurface Mount	Manufacturer Part Number	ASTMUPCFL-33-24.000MHZ-LJ-E-T3
OscillatorsPackage4-SMD, No LeadSeriesASTMUPCTypeMEMS (Silicon)Frequency24MHzFunctionEnable/DisableOutputLVCMOSVoltage - Supply3.3VFrequency Stability±20pmOperating Temperature-40°C ~ 85°CCurrent - Supply (Max)36mARatings-Mounting TypeSurface Mount	Manufacturer	Abracon LLC
Package4-SMD, No LeadSeriesASTMUPCTypeMEMS (Silicon)Frequency24MHzFunctionEnable/DisableOutputLVCMOSVoltage - Supply3.3VFrequency Stability±20ppmOperating Temperature6mACurrent - Supply (Max)36mARatings-Mounting TypeSurface Mount	Category	Crystals, Oscillators, Resonators
SeriesASTMUPCTypeMEMS (Silicon)Frequency24MHzFunctionEnable/DisableOutputLVCMOSVoltage - Supply3.3VFrequency Stability±20ppmOperating Temperature-40°C ~ 85°CCurrent - Supply (Max)36mARatings-Mounting TypeSurface Mount		Oscillators
TypeMEMS (Silicon)Frequency24MHzFunctionEnable/DisableOutputLVCMOSVoltage - Supply3.3VFrequency Stability±20ppmOperating Temperature-40°C ~ 85°CCurrent - Supply (Max)36mARatings-Mounting TypeSurface Mount	Package	4-SMD, No Lead
Frequency24MHzFunctionEnable/DisableOutputLVCMOSVoltage - Supply3.3VFrequency Stability±20ppmOperating Temperature-40°C ~ 85°CCurrent - Supply (Max)36mARatings-Mounting TypeSurface Mount	Series	ASTMUPC
FunctionEnable/DisableOutputLVCMOSVoltage - Supply3.3VFrequency Stability±20ppmOperating Temperature-40°C ~ 85°CCurrent - Supply (Max)36mARatings-Mounting TypeSurface Mount	Туре	MEMS (Silicon)
OutputLVCMOSVoltage - Supply3.3VFrequency Stability±20pmOperating Temperature-40°C ~ 85°CCurrent - Supply (Max)36mARatings-Mounting TypeSurface Mount	Frequency	24MHz
Yoltage - Supply3.3VFrequency Stability±20ppmOperating Temperature-40°C ~ 85°CCurrent - Supply (Max)36mARatings-Mounting TypeSurface Mount	Function	Enable/Disable
Frequency Stability±20ppmOperating Temperature-40°C ~ 85°CCurrent - Supply (Max)36mARatings-Mounting TypeSurface Mount	Output	LVCMOS
Operating Temperature-40°C ~ 85°CCurrent - Supply (Max)36mARatings-Mounting TypeSurface Mount	Voltage - Supply	3.3V
Current - Supply (Max)36mARatings-Mounting TypeSurface Mount	Frequency Stability	±20ppm
Ratings - Mounting Type Surface Mount	Operating Temperature	$-40^{\circ}\mathrm{C} \sim 85^{\circ}\mathrm{C}$
Mounting Type Surface Mount	Current - Supply (Max)	36mA
	Ratings	-
	Mounting Type	Surface Mount
Package / Case 4-SMD, No Lead	Package / Case	4-SMD, No Lead
Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm)	Size / Dimension	0.197" L x 0.126" W (5.00mm x 3.20mm)
Height - Seated (Max) 0.031" (0.80mm)	Height - Seated (Max)	0.031" (0.80mm)
Report errors?		Report errors?

ASTMUPCFL-33-24.000MHZ-LJ-E-T3 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

ASTMUPCFL-33-24.000MHZ-LJ-E-T3 Payment Methods



ASTMUPCFL-33-24.000MHZ-LJ-E-T3 Shipping Methods



If you have any question about ASTMUPCFL-33-24.000MHZ-LJ-E-T3, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com