


ASTX-H11-B-5.000MHZ-T

ASTX-H11-B-5.000MHZ-T Information



Part Number	ASTX-H11-B-5.000MHZ-T	
Manufacturer	Abracon LLC	
Category	Crystals, Oscillators, Resonators Oscillators	
Description	OSC TCXO 5.000MHZ HCMOS SMD	
Package	4-SMD, No Lead	
	For the pricing/inventory/lead time, please contact us	
	Website: https://www.heisener.com	
	E-mail: salesdept@heisener.com	



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



ASTX-H11-B-5.000MHZ-T Specifications

ManufacturerAbracon LLCCategoryCrystals, Oscillators, ResonatorsOscillatorsOscillatorsPackage4-SMD, No LeadSeriesASTX-H11TypeTCXOFrequencySMHzDutputEnable/DisableOutputSUNSOrdge - Supply2.5VFrequency Stability-30°C ~ 75°COperating Temperature-30°C ~ 75°CCurrent - Supply (Maxy)Surface MountAddated Series-Advanting TypeSurface MountPackage / Case4.SMD, No LeadSize / Dimension0.126°L x 0.098°W (3.20mm x 2.50mm)		
CategoryCrystals, Oscillators, ResonatorsOscillatorsPackage4-SMD, No LeadPackageASTX-H11TypeTCXOFrequency5MHzPoutputEnable/DisableVoltage - Supply2.5VPrequency Stability-30°C ~ 75°CPartent - Supply (Max)5Mrace MountArrage - Supply (Max)Surface MountPackage / Case-4-SMD, No LeadBackage / Case0.126" L x 0.098" W (3.20mm x 2.50mm)	Manufacturer Part Number	ASTX-H11-B-5.000MHZ-T
OscillatorsPackage4-SMD, No LeadBackageASTX-H11TypeTCXOFrequency5MHzFunctionEnable/DisableDutputHCMOSVoltage - Supply2.5VFrequency Stability±2.5ppmOperating Temperature-30°C ~ 75°CCurrent - Supply (Max)4mARatings-Advanting TypeSurface MountPackage / Case4.SMD, No LeadSize / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)	Manufacturer	Abracon LLC
Package 4-SMD, No Lead Geries ASTX-H11 Type TCXO Frequency 5MHz Function Enable/Disable Output HCMOS Voltage - Supply 2.5V Frequency Stability ±2.5pm Operating Temperature -30°C ~ 75°C Current - Supply (Max) 4mA Ratings - Package / Case Sufface Mount By Constance 4-SMD, No Lead By Constance 4-SMD, No Lead	Category	Crystals, Oscillators, Resonators
Series ASTX-H11 Type TCXO Frequency 5MHz Function Enable/Disable Dutput HCMOS Voltage - Supply 2.5V Frequency Stability ±2.5ppm Departing Temperature -30°C ~ 75°C Current - Supply (Max) 4mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm)		Oscillators
Fype TCXO Frequency 5MHz Function Enable/Disable Dutput HCMOS Voltage - Supply 2.5V Frequency Stability ±2.5ppm Operating Temperature -30°C ~ 75°C Current - Supply (Max) 4mA Ratings - Addage / Case Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.126°L x 0.098°W (3.20mm x 2.50mm)	Package	4-SMD, No Lead
Frequency5MHzFunctionEnable/DisableDutputHCMOSVoltage - Supply2.5VFrequency Stability±2.5ppmOperating Temperature-30°C ~ 75°CCurrent - Supply (Max)4mARatings-Abunting TypeSurface MountPackage / Case4-SMD, No LeadSize / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)	Series	ASTX-H11
FunctionEnable/DisableDutputHCMOSVoltage - Supply2.5VFrequency Stability±2.5ppmOperating Temperature-30°C ~ 75°CCurrent - Supply (Max)4mARatings-Aounting TypeSurface MountPackage / Case4-SMD, No LeadSize / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)	Туре	TCXO
Dutput HCMOS Voltage - Supply 2.5V Frequency Stability ±2.5ppm Operating Temperature -30°C ~ 75°C Current - Supply (Max) 4mA Ratings - Package / Case Surface Mount Package / Case 0.126" L x 0.098" W (3.20mm x 2.50mm)	Frequency	5MHz
Yoltage - Supply2.5VGrequency Stability±2.5ppmOperating Temperature-30°C ~ 75°CCurrent - Supply (Max)4mARatings-Mounting TypeSurface MountPackage / Case4-SMD, No LeadSize / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)	Function	Enable/Disable
Frequency Stability±2.5ppmOperating Temperature-30°C ~ 75°CCurrent - Supply (Max)4mARatings-Mounting TypeSurface MountPackage / Case4-SMD, No LeadSize / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)	Output	HCMOS
Operating Temperature-30°C ~ 75°CCurrent - Supply (Max)4mARatings-Mounting TypeSurface MountPackage / Case4-SMD, No LeadSize / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)	Voltage - Supply	2.5V
Current - Supply (Max)4mARatings-Mounting TypeSurface MountPackage / Case4-SMD, No LeadSize / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)	Frequency Stability	±2.5ppm
Ratings-Mounting TypeSurface MountPackage / Case4-SMD, No LeadSize / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)	Operating Temperature	-30°C ~ 75°C
Mounting TypeSurface MountPackage / Case4-SMD, No LeadSize / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)	Current - Supply (Max)	4mA
Package / Case4-SMD, No LeadSize / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)	Ratings	-
Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm)	Mounting Type	Surface Mount
	Package / Case	4-SMD, No Lead
Height - Seated (Max) 0.043" (1.10mm)	Size / Dimension	0.126" L x 0.098" W (3.20mm x 2.50mm)
	Height - Seated (Max)	0.043" (1.10mm)
Report errors?		Report errors?

ASTX-H11-B-5.000MHZ-T Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

ASTX-H11-B-5.000MHZ-T Payment Methods



If you have any question about ASTX-H11-B-5.000MHZ-T, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com