

ASVMPLV-BLANK-XR-T

ASVMPLV-BLANK-XR-T Information



For Reference Only

Part Number ASVMPLV-BLANK-XR-T

Manufacturer Abracon LLC

Category Crystals, Oscillators, Resonators

Programmable Oscillators

Description OSC MEMS 7.0X5.0 LVDS BLANK

Package 6-VDFN Exposed Pad

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ASVMPLV-BLANK-XR-T Specifications

Manufacturer Part Number ASVMPLV-BLANK-XR-T Manufacturer Abracon LLC Category Crystals, Oscillators, Resonators Package 6-VDFN Exposed Pad Series Pure Silicon? ASVMP Type MEMS (Silicon) Programmable Type Blank (User Must Program) Available Frequency Range 2.3MHz ~ 460MHz Function Enable/Disable Output LVDS Voltage - Supply 2.25 V ~ 3.6 V Frequency Stability (Total) ±25ppm Operating Temperature 40°C ~ 105°C Spread Spectrum Bandwidth - Current - Supply (Max) 32mA Ratings - Mounting Type Surface Mount Package / Case 6-VDFN Exposed Pad Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.035" (0.90mm)		
Category Crystals, Oscillators, Resonators Package 6-VDFN Exposed Pad Series Pure Silicon? ASVMP Type MEMS (Silicon) Programmable Type Blank (User Must Program) Available Frequency Range 2.3MHz ~ 460MHz Function Enable/Disable Output LVDS Voltage - Supply 2.25 V ~ 3.6 V Frequency Stability - Frequency Stability (Total) ±25ppm Operating Temperature -40°C ~ 105°C Spread Spectrum Bandwidth - Current - Supply (Max) 32mA Ratings - Mounting Type Surface Mount Package / Case 6-VDFN Exposed Pad Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.035" (0.90mm)	Manufacturer Part Number	ASVMPLV-BLANK-XR-T
Package 6-VDFN Exposed Pad Series Pure Silicon? ASVMP Type MEMS (Silicon) Programmable Type Blank (User Must Program) Available Frequency Range 2.3MHz ~ 460MHz Function Enable/Disable Output LVDS Voltage - Supply 2.25 V ~ 3.6 V Frequency Stability - Frequency Stability (Total) ±25ppm Operating Temperature -40°C ~ 105°C Spread Spectrum Bandwidth - Current - Supply (Max) 32mA Ratings - Mounting Type Surface Mount Package / Case 6-VDFN Exposed Pad Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.035" (0.90mm)	Manufacturer	Abracon LLC
Package 6-VDFN Exposed Pad Series Pure Silicon? ASVMP Type MEMS (Silicon) Programmable Type Blank (User Must Program) Available Frequency Range 2.3MHz ~ 460MHz Function Enable/Disable Output LVDS Voltage - Supply 2.25 V ~ 3.6 V Frequency Stability - Frequency Stability (Total) ±25ppm Operating Temperature -40°C ~ 105°C Spread Spectrum Bandwidth - Current - Supply (Max) 32mA Ratings - Mounting Type Surface Mount Package / Case 6-VDFN Exposed Pad Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.035" (0.90mm)	Category	Crystals, Oscillators, Resonators
SeriesPure Silicon? ASVMPTypeMEMS (Silicon)Programmable TypeBlank (User Must Program)Available Frequency Range2.3MHz ~ 460MHzFunctionEnable/DisableOutputLVDSVoltage - Supply2.25 V ~ 3.6 VFrequency Stability-Frequency Stability (Total)±25ppmOperating Temperature-40°C ~ 105°CSpread Spectrum Bandwidth-Current - Supply (Max)32mARatings-Mounting TypeSurface MountPackage / Case6-VDFN Exposed PadSize / Dimension0.276" L x 0.197" W (7.00mm x 5.00mm)Height0.035" (0.90mm)		Programmable Oscillators
Type MEMS (Silicon) Programmable Type Blank (User Must Program) Available Frequency Range 2.3MHz ~ 460MHz Function Enable/Disable Output LVDS Voltage - Supply 2.25 V ~ 3.6 V Frequency Stability - Frequency Stability (Total) ±25ppm Operating Temperature -40°C ~ 105°C Spread Spectrum Bandwidth - Current - Supply (Max) 32mA Ratings - Mounting Type Surface Mount Package / Case 6-VDFN Exposed Pad Size / Dimension 0.035" (0.90mm) MEMS (Silicon) Blank (User Must Program) 2.3MHz ~ 460MHz 4.00C ~ 105°C Spread Spectrum Bandwidth - Current - Supply (Max) 32mA Ratings - Surface Mount	Package	6-VDFN Exposed Pad
Programmable Type Available Frequency Range 2.3MHz ~ 460MHz Function Enable/Disable Output LVDS Voltage - Supply 2.25 V ~ 3.6 V Frequency Stability - Frequency Stability (Total) Operating Temperature -40°C ~ 105°C Spread Spectrum Bandwidth - Current - Supply (Max) Ratings - Mounting Type Surface Mount Package / Case 6-VDFN Exposed Pad Size / Dimension 0.035" (0.90mm)	Series	Pure Silicon? ASVMP
Available Frequency Range 2.3MHz ~ 460MHz Function Enable/Disable Output LVDS Voltage - Supply 2.25 V ~ 3.6 V Frequency Stability - Frequency Stability (Total) 425ppm Operating Temperature -40°C ~ 105°C Spread Spectrum Bandwidth - Current - Supply (Max) Ratings - Mounting Type Surface Mount Package / Case 6-VDFN Exposed Pad Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height	Туре	MEMS (Silicon)
Function Enable/Disable Output LVDS Voltage - Supply 2.25 V ~ 3.6 V Frequency Stability - Frequency Stability (Total) ±25ppm Operating Temperature -40°C ~ 105°C Spread Spectrum Bandwidth - Current - Supply (Max) 32mA Ratings - Mounting Type Surface Mount Package / Case 6-VDFN Exposed Pad Size / Dimension 0.035" (0.90mm)	Programmable Type	Blank (User Must Program)
OutputLVDSVoltage - Supply2.25 V ~ 3.6 VFrequency Stability-Frequency Stability (Total)±25ppmOperating Temperature-40°C ~ 105°CSpread Spectrum Bandwidth-Current - Supply (Max)32mARatings-Mounting TypeSurface MountPackage / Case6-VDFN Exposed PadSize / Dimension0.276" L x 0.197" W (7.00mm x 5.00mm)Height0.035" (0.90mm)	Available Frequency Range	2.3MHz ~ 460MHz
Voltage - Supply 2.25 V ~ 3.6 V Frequency Stability	Function	Enable/Disable
Frequency Stability (Total) Frequency Stability (Total) Operating Temperature -40°C ~ 105°C Spread Spectrum Bandwidth - Current - Supply (Max) Ratings - Mounting Type Surface Mount Package / Case 6-VDFN Exposed Pad Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height - - 0.035" (0.90mm)	Output	LVDS
Frequency Stability (Total) ±25ppm Operating Temperature -40°C ~ 105°C Spread Spectrum Bandwidth - Current - Supply (Max) 32mA Ratings - Mounting Type Surface Mount Package / Case 6-VDFN Exposed Pad Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.035" (0.90mm)	Voltage - Supply	2.25 V ~ 3.6 V
Operating Temperature -40°C ~ 105°C Spread Spectrum Bandwidth - Current - Supply (Max) Ratings - Mounting Type Surface Mount Package / Case 6-VDFN Exposed Pad Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.035" (0.90mm)	Frequency Stability	-
Spread Spectrum Bandwidth Current - Supply (Max) Ratings - Mounting Type Surface Mount Package / Case 6-VDFN Exposed Pad Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.035" (0.90mm)	Frequency Stability (Total)	±25ppm
Current - Supply (Max) Ratings - Mounting Type Surface Mount Package / Case 6-VDFN Exposed Pad Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.035" (0.90mm)	Operating Temperature	-40°C ~ 105°C
Ratings - Mounting Type Surface Mount Package / Case 6-VDFN Exposed Pad Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.035" (0.90mm)	Spread Spectrum Bandwidth	-
Mounting Type Surface Mount Package / Case 6-VDFN Exposed Pad Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.035" (0.90mm)	Current - Supply (Max)	32mA
Package / Case 6-VDFN Exposed Pad Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.035" (0.90mm)	Ratings	-
Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.035" (0.90mm)	Mounting Type	Surface Mount
Height 0.035" (0.90mm)	Package / Case	6-VDFN Exposed Pad
, ,	Size / Dimension	0.276" L x 0.197" W (7.00mm x 5.00mm)
Report errors?	Height	0.035" (0.90mm)
		Report errors?

ASVMPLV-BLANK-XR-T Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ASVMPLV-BLANK-XR-T Payment Methods





















ASVMPLV-BLANK-XR-T Shipping Methods













If you have any question about ASVMPLV-BLANK-XR-T, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com