

### **ASX20003 Information**



For Reference Only

Part Number ASX20003

Manufacturer Panasonic Electric Works

**Category** Relays

Signal Relays, Up to 2 Amps

**Description** RELAY TELECOM DPDT 10MA 3V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **ASX20003 Specifications**

Manufacturer Part Number  Manufacturer  Panasonic Electric Works  Relays  Signal Relays, Up to 2 Amps  Package  - Series  ASX  Relay Type  Telecom  Coil Type  Non Latching  Coil Current  16.7mA  Coil Voltage  3VDC  Contact Form  DPDT (2 Form C)  Contact Rating (Current)  10mA  Switching Voltage  10VDC - Max  Turn On Voltage (Max)  Turn Off Voltage (Min)  Operate Time  Sms  Release Time  Features  Mounting Type  Tennoin Style  Perpent agrees 3  Perpent agrees 3  Perpent agrees 3  Perpent agrees 3  Perpent agrees 3		
CategoryRelaysPackage-SeriesASXRelay TypeTelecomCoil TypeNon LatchingCoil Current16.7mACoil Voltage3VDCContact FormDPDT (2 Form C)Contact Rating (Current)10mASwitching Voltage10VDC - MaxTurn On Voltage (Max)2.4 VDCTurn Off Voltage (Min)0.3 VDCOperate Time5msRelease Time5msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	ASX20003
Package-SeriesASXRelay TypeTelecomCoil TypeNon LatchingCoil Current16.7mACoil Voltage3VDCContact FormDPDT (2 Form C)Contact Rating (Current)10mASwitching Voltage10VDC - MaxTurn On Voltage (Max)2.4 VDCTurn Off Voltage (Min)0.3 VDCOperate Time5msRelease Time5msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Manufacturer	Panasonic Electric Works
Package - Series ASX Relay Type Telecom Coil Type Non Latching Coil Current 16.7mA Coil Voltage 3VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 10mA Switching Voltage 10VDC - Max Turn On Voltage (Max) 2.4 VDC Turn Off Voltage (Min) 0.3 VDC Operate Time 5ms Release Time 5ms Features - Mounting Type Through Hole Termination Style PC Pin	Category	Relays
SeriesASXRelay TypeTelecomCoil TypeNon LatchingCoil Current16.7mACoil Voltage3VDCContact FormDPDT (2 Form C)Contact Rating (Current)10mASwitching Voltage10VDC - MaxTurn On Voltage (Max)2.4 VDCTurn Off Voltage (Min)0.3 VDCOperate Time5msRelease Time5msFeatures-Mounting TypeThrough HoleTermination StylePC Pin		Signal Relays, Up to 2 Amps
Relay TypeTelecomCoil TypeNon LatchingCoil Current16.7mACoil Voltage3VDCContact FormDPDT (2 Form C)Contact Rating (Current)10mASwitching Voltage10VDC - MaxTurn On Voltage (Max)2.4 VDCTurn Off Voltage (Min)0.3 VDCOperate Time5msRelease Time5msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Package	-
Coil TypeNon LatchingCoil Current16.7mACoil Voltage3VDCContact FormDPDT (2 Form C)Contact Rating (Current)10mASwitching Voltage10VDC - MaxTurn On Voltage (Max)2.4 VDCTurn Off Voltage (Min)0.3 VDCOperate Time5msRelease Time5msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Series	ASX
Coil Current 16.7mA 3 3VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 10mA Switching Voltage 10VDC - Max Turn On Voltage (Max) 2.4 VDC Turn Off Voltage (Min) 0.3 VDC Operate Time 5ms Release Time 5ms Features - Mounting Type Through Hole Termination Style PC Pin	Relay Type	Telecom
Coil Voltage 3VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 10mA Switching Voltage 10VDC - Max Turn On Voltage (Max) 2.4 VDC Turn Off Voltage (Min) 0.3 VDC Operate Time 5ms Release Time 5ms Features	Coil Type	Non Latching
Contact Form DPDT (2 Form C)  Contact Rating (Current)  Switching Voltage  10VDC - Max  Turn On Voltage (Max)  2.4 VDC  Turn Off Voltage (Min)  0.3 VDC  Operate Time  Sms  Release Time  Features  -  Mounting Type  Through Hole  Termination Style	Coil Current	16.7mA
Contact Rating (Current)  Switching Voltage  10VDC - Max  Turn On Voltage (Max)  2.4 VDC  Turn Off Voltage (Min)  0.3 VDC  Operate Time  5ms  Release Time  5ms  Features  - Mounting Type  Through Hole  Termination Style	Coil Voltage	3VDC
Switching Voltage 10VDC - Max Turn On Voltage (Max) 2.4 VDC Turn Off Voltage (Min) 0.3 VDC Operate Time 5ms Release Time 5ms Features - Mounting Type Through Hole Termination Style PC Pin	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max)  Turn Off Voltage (Min)  Operate Time  Sms  Release Time  Features  Mounting Type  Through Hole  Termination Style  2.4 VDC  0.3 VDC  5ms  Fend  Through Hole  PC Pin	Contact Rating (Current)	10mA
Turn Off Voltage (Min)  Operate Time  Sms  Release Time  5ms  Features  -  Mounting Type  Through Hole  Termination Style  O.3 VDC  5ms  Through Hole  PC Pin	Switching Voltage	10VDC - Max
Operate Time 5ms Release Time 5ms Features - Mounting Type Through Hole Termination Style PC Pin	Turn On Voltage (Max)	2.4 VDC
Release Time 5ms  Features - Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	0.3 VDC
Features - Mounting Type Through Hole Termination Style PC Pin	Operate Time	5ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	5ms
Termination Style PC Pin	Features	-
	Mounting Type	Through Hole
Panort arrors?	Termination Style	PC Pin
Report errors:		Report errors?

#### **ASX20003 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **ASX20003 Payment Methods**





















## **ASX20003 Shipping Methods**













If you have any question about ASX20003, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com