

ASX200A12 Information



For Reference Only

Part Number ASX200A12

Manufacturer Panasonic Electric Works

Category Relays

Signal Relays, Up to 2 Amps

Description RELAY TELECOM DPDT 10MA 12V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ASX200A12 Specifications

Manufacturer Part Number Manufacturer Panasonic Electric Works Relays Signal Relays, Up to 2 Amps Package		
CategoryRelaysPackage-SeriesASXRelay TypeTelecomCoil TypeNon LatchingCoil Current4.2mACoil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)10mASwitching Voltage10VDC - MaxTurn On Voltage (Max)9.6 VDCTurn Off Voltage (Min)1.2 VDCOperate Time5msRelease Time5msFeatures-Mounting TypeSurface MountTermination StyleGull Wing	Manufacturer Part Number	ASX200A12
Package-SeriesASXRelay TypeTelecomCoil TypeNon LatchingCoil Current4.2mACoil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)10mASwitching Voltage10VDC - MaxTurn On Voltage (Max)9.6 VDCTurn Off Voltage (Min)1.2 VDCOperate Time5msRelease Time5msFeatures-Mounting TypeSurface MountTermination StyleGull Wing	Manufacturer	Panasonic Electric Works
Package-SeriesASXRelay TypeTelecomCoil TypeNon LatchingCoil Current4.2mACoil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)10mASwitching Voltage10VDC - MaxTurn On Voltage (Max)9.6 VDCTurn Off Voltage (Min)1.2 VDCOperate Time5msRelease Time5msFeatures-Mounting TypeSurface MountTermination StyleGull Wing	Category	Relays
SeriesASXRelay TypeTelecomCoil TypeNon LatchingCoil Current4.2mACoil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)10mASwitching Voltage10VDC - MaxTurn On Voltage (Max)9.6 VDCTurn Off Voltage (Min)1.2 VDCOperate Time5msRelease Time5msFeatures-Mounting TypeSurface MountTermination StyleGull Wing		Signal Relays, Up to 2 Amps
Relay TypeTelecomCoil TypeNon LatchingCoil Current4.2mACoil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)10mASwitching Voltage10VDC - MaxTurn On Voltage (Max)9.6 VDCTurn Off Voltage (Min)1.2 VDCOperate Time5msRelease Time5msFeatures-Mounting TypeSurface MountTermination StyleGull Wing	Package	-
Coil TypeNon LatchingCoil Current4.2mACoil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)10mASwitching Voltage10VDC - MaxTurn On Voltage (Max)9.6 VDCTurn Off Voltage (Min)1.2 VDCOperate Time5msRelease Time5msFeatures-Mounting TypeSurface MountTermination StyleGull Wing	Series	ASX
Coil Current 4.2mA Coil Voltage 12VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 10mA Switching Voltage 10VDC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 5ms Release Time 5ms Features Mounting Type Surface Mount Termination Style Gull Wing	Relay Type	Telecom
Coil Voltage Contact Form DPDT (2 Form C) Contact Rating (Current) 10mA Switching Voltage 10VDC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 5ms Release Time 5ms Features	Coil Type	Non Latching
Contact Form DPDT (2 Form C) Contact Rating (Current) Switching Voltage 10VDC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time Sms Release Time Features - Mounting Type Surface Mount Termination Style	Coil Current	4.2mA
Contact Rating (Current) Switching Voltage 10VDC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 5ms Release Time 5ms Features - Mounting Type Surface Mount Termination Style	Coil Voltage	12VDC
Switching Voltage Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 5ms Release Time 5ms Features - Mounting Type Surface Mount Termination Style	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max) 7. Turn Off Voltage (Min) 9.6 VDC 1.2 VDC Operate Time 5ms Release Time 5ms Features - Mounting Type Surface Mount Termination Style Gull Wing	Contact Rating (Current)	10mA
Turn Off Voltage (Min) Operate Time Sms Release Time 5ms Features - Mounting Type Surface Mount Termination Style 1.2 VDC 5ms 5ms 6ms 6ms 6ms 6ms 6ms 6ms	Switching Voltage	10VDC - Max
Operate Time 5ms Release Time 5ms Features - Mounting Type Surface Mount Termination Style Gull Wing	Turn On Voltage (Max)	9.6 VDC
Release Time 5ms Features - Mounting Type Surface Mount Termination Style Gull Wing	Turn Off Voltage (Min)	1.2 VDC
Features - Mounting Type Surface Mount Termination Style Gull Wing	Operate Time	5ms
Mounting Type Surface Mount Termination Style Gull Wing	Release Time	5ms
Termination Style Gull Wing	Features	-
	Mounting Type	Surface Mount
Report errors?	Termination Style	Gull Wing
· ·		Report errors?

ASX200A12 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ASX200A12 Payment Methods



















ASX200A12 Shipping Methods













If you have any question about ASX200A12, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com