



### **ASX2201H Information**



For Reference Only

Part Number ASX2201H

Manufacturer Panasonic Electric Works

**Category** Relays

Signal Relays, Up to 2 Amps

**Description** RELAY TELECOM DPDT 10MA 1.5V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **ASX2201H Specifications**

Manufacturer Part Number  Manufacturer  Panasonic Electric Works  Relays  Signal Relays, Up to 2 Amps  Package  - Series  ASX  Relay Type  Telecom  Coil Type  Latching, Dual Coil  Coil Current  46.7mA  Coil Voltage  1.5VDC  Contact Form  DPDT (2 Form C)  Contact Rating (Current)  10mA  Switching Voltage  10VDC - Max  Turn On Voltage (Max)  Turn Off Voltage (Min)  Operate Time  5ms  Release Time  5ms  Release Time  5ms  Features  Mounting Type  Through Hole  Termination Style		
CategoryRelaysPackage-SeriesASXRelay TypeTelecomCoil TypeLatching, Dual CoilCoil Current46.7mACoil Voltage1.5VDCContact FormDPDT (2 Form C)Contact Rating (Current)10mASwitching Voltage10VDC - MaxTurn On Voltage (Max)1.2 VDCTurn Off Voltage (Min)-Operate Time5msRelease Time5msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	ASX2201H
Package - Series ASX Relay Type Telecom Coil Type Latching, Dual Coil Coil Current 46.7mA Coil Voltage 1.5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 10mA Switching Voltage 10VDC - Max Turn On Voltage (Max) 1.2 VDC Turn Off Voltage (Min) - Operate Time 5ms Release Time 5ms Features - Mounting Type Through Hole Termination Style PC Pin	Manufacturer	Panasonic Electric Works
Package         -           Series         ASX           Relay Type         Telecom           Coil Type         Latching, Dual Coil           Coil Current         46.7mA           Coil Voltage         1.5VDC           Contact Form         DPDT (2 Form C)           Contact Rating (Current)         10mA           Switching Voltage         10VDC - Max           Turn On Voltage (Max)         1.2 VDC           Turn Off Voltage (Min)         -           Operate Time         5ms           Release Time         5ms           Features         -           Mounting Type         Through Hole           Termination Style         PC Pin	Category	Relays
SeriesASXRelay TypeTelecomCoil TypeLatching, Dual CoilCoil Current46.7mACoil Voltage1.5VDCContact FormDPDT (2 Form C)Contact Rating (Current)10mASwitching Voltage10VDC - MaxTurn On Voltage (Max)1.2 VDCTurn Off Voltage (Min)-Operate Time5msRelease Time5msFeatures-Mounting TypeThrough HoleTermination StylePC Pin		Signal Relays, Up to 2 Amps
Relay TypeTelecomCoil TypeLatching, Dual CoilCoil Current46.7mACoil Voltage1.5VDCContact FormDPDT (2 Form C)Contact Rating (Current)10mASwitching Voltage10VDC - MaxTurn On Voltage (Max)1.2 VDCTurn Off Voltage (Min)-Operate Time5msRelease Time5msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Package	-
Coil TypeLatching, Dual CoilCoil Current46.7mACoil Voltage1.5VDCContact FormDPDT (2 Form C)Contact Rating (Current)10mASwitching Voltage10VDC - MaxTurn On Voltage (Max)1.2 VDCTurn Off Voltage (Min)-Operate Time5msRelease Time5msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Series	ASX
Coil Current46.7mACoil Voltage1.5VDCContact FormDPDT (2 Form C)Contact Rating (Current)10mASwitching Voltage10VDC - MaxTurn On Voltage (Max)1.2 VDCTurn Off Voltage (Min)-Operate Time5msRelease Time5msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Relay Type	Telecom
Coil Voltage 1.5VDC  Contact Form DPDT (2 Form C)  Contact Rating (Current) 10mA  Switching Voltage 10VDC - Max  Turn On Voltage (Max) 1.2 VDC  Turn Off Voltage (Min) -  Operate Time 5ms  Release Time 5ms  Features -  Mounting Type Through Hole  Termination Style PC Pin	Coil Type	Latching, Dual Coil
Contact Form DPDT (2 Form C)  Contact Rating (Current)  Switching Voltage  10VDC - Max  Turn On Voltage (Max)  1.2 VDC  Turn Off Voltage (Min)  Operate Time  Sms  Release Time  Features  -  Mounting Type  Through Hole  Termination Style	Coil Current	46.7mA
Contact Rating (Current)  Switching Voltage  10VDC - Max  Turn On Voltage (Max)  1.2 VDC  Turn Off Voltage (Min)  Operate Time  5ms  Release Time  5ms  Features  - Mounting Type  Through Hole  Termination Style	Coil Voltage	1.5VDC
Switching Voltage  Turn On Voltage (Max)  1.2 VDC  Turn Off Voltage (Min)  Operate Time  Sms  Release Time  5ms  Features  -  Mounting Type  Through Hole  Termination Style	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max)  Turn Off Voltage (Min)  Operate Time  Sms  Release Time  5ms  Features  - Mounting Type  Through Hole  Termination Style  1.2 VDC  - Turn Off Voltage (Max)  - Turn On Voltage (Max)  - Turn On Voltage (Max)  - Turn On Voltage (Max)  - Through Hole  PC Pin	Contact Rating (Current)	10mA
Turn Off Voltage (Min)  Operate Time  Sms  Release Time  Features  Mounting Type  Through Hole  Termination Style	Switching Voltage	10VDC - Max
Operate Time 5ms Release Time 5ms Features - Mounting Type Through Hole Termination Style PC Pin	Turn On Voltage (Max)	1.2 VDC
Release Time 5ms  Features -  Mounting Type Through Hole  Termination Style PC Pin	Turn Off Voltage (Min)	-
Features - Mounting Type Through Hole PC Pin	Operate Time	5ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	5ms
Termination Style PC Pin	Features	-
·	Mounting Type	Through Hole
Donort owers?	Termination Style	PC Pin
Report errors?		Report errors?

#### **ASX2201H Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **ASX2201H Payment Methods**



















### **ASX2201H Shipping Methods**













If you have any question about ASX2201H, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com