


AT0603DRD0710R5L

AT0603DRD0710R5L Information



Part Number	AT0603DRD0710R5L
Manufacturer	Yageo
Category	Resistors Chip Resistor - Surface Mount
Description	RES SMD 10.5 OHM 0.5% 1/10W 0603
Package	0603 (1608 Metric)
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



Request a Quote

AT0603DRD0710R5L Specifications

Manufacturer Part Number AT0603DRD0710R5L Manufacturer Yageo Category Resistors Category Resistor - Surface Mount Package 0603 (1608 Metric) Series AT Resistance 10.5 Ohms Tolerance ±0.5% Power (Watts) 0.1W, 1/10W Composition Thin Film Features Anti-Sulfur, Automotive AEC-Q200, Moisture Resistant Operating Temperature 6003 (1608 Metric) Supplier Device Package 0603 (1608 Metric) Number of Terminations 0.022" (0.55mm) Number of Terminations 2 Failure Rate -		
CategoryResistorsCategoryResistor - Surface MountPackage0603 (1608 Metric)PackageATResistance10.5 OhmsTolerance±0.5%Power (Watts)0.1W, 1/10WCompositionThin FilmFeaturesAnti-Sulfur, Automotive AEC-Q200, Moisture ResistantTemperature Coefficient±25pm/°COperating Temperature0603 (1608 Metric)Supplier Device Package0603 (1608 Metric)Supplier Device Package0603 (1608 Metric)Supplier Device Package0.2" (0.55mm)Height - Seated (Max)0.22" (0.55mm)Number of Terminations2Failure Rate-	Manufacturer Part Number	AT0603DRD0710R5L
IntegryChip Resistor - Surface MountPackage0603 (1608 Metric)SeriesATResistance10.5 OhmsTolerance±0.5%Power (Watts)0.1W, 1/10WCompositionThin FilmFeaturesAnti-Sulfur, Automotive AEC-Q200, Moisture ResistantTemperature Coefficient±25pm/°COperating Temperature6603 (1608 Metric)Supplier Device Package0603Size / Dimension0.063" L x 0.032" W (1.60mm x 0.80mm)Height - Seated (Max)2Failure Rate-	Manufacturer	Yageo
Package 0603 (1608 Metric) Series AT Resistance 10.5 Ohms Tolerance ±0.5% Power (Watts) 0.1W, 1/10W Composition Thin Film Features Anti-Sulfur, Automotive AEC-Q200, Moisture Resistant Temperature Coefficient ±25ppm/°C Operating Temperature -55°C ~ 155°C Package / Case 0603 (1608 Metric) Supplier Device Package 0603 (1608 Metric) Size / Dimension 0.063" L x 0.032" W (1.60mm x 0.80mm) Height - Seated (Max) 0.022" (0.55mm) Number of Terminations 2 Failure Rate -	Category	Resistors
SeriesATResistance10.5 OhmsTolerance $\pm 0.5\%$ Power (Watts)0.1W, 1/10WCompositionThin FilmFeaturesAnti-Sulfur, Automotive AEC-Q200, Moisture ResistantTemperature Coefficient $\pm 25 pm/^{\circ}C$ Operating Temperature $-55^{\circ}C \sim 155^{\circ}C$ Package / Case0603 (1608 Metric)Supplier Device Package0603Size / Dimension0.063" L x 0.032" W (1.60mm x 0.80mm)Height - Seated (Max)2Number of Terminations2Failure Rate-		Chip Resistor - Surface Mount
Resistance10.5 OhmsTolerance±0.5%Power (Watts)0.1W, 1/10WCompositionThin FilmFeaturesAnti-Sulfur, Automotive AEC-Q200, Moisture ResistantTemperature Coefficient±25ppm/°COperating Temperature-55°C ~ 155°CPackage / Case0603 (1608 Metric)Supplier Device Package0603Size / Dimension0.023" W (1.60mm x 0.80mm)Height - Seated (Max)0.22" (0.55mm)Number of Terminations2Failure Rate-	Package	0603 (1608 Metric)
Tolerance ±0.5% Power (Watts) 0.1W, 1/10W Composition Thin Film Features Anti-Sulfur, Automotive AEC-Q200, Moisture Resistant Temperature Coefficient ±25ppm/°C Operating Temperature -55°C ~ 155°C Package / Case 0603 (1608 Metric) Supplier Device Package 0603 Size / Dimension 0.063" L x 0.032" W (1.60mm x 0.80mm) Height - Seated (Max) 0.022" (0.55mm) Number of Terminations 2 Failure Rate -	Series	AT
Power (Watts)0.1W, 1/10WCompositionThin FilmFeaturesAnti-Sulfur, Automotive AEC-Q200, Moisture ResistantTemperature Coefficient±25pm/°COperating Temperature-55°C ~ 155°CPackage / Case0603 (1608 Metric)Supplier Device Package0603Size / Dimension0.063" L x 0.032" W (1.60mm x 0.80mm)Height - Seated (Max)0.022" (0.55mm)Number of Terminations2Failure Rate-	Resistance	10.5 Ohms
CompositionThin FilmFeaturesAnti-Sulfur, Automotive AEC-Q200, Moisture ResistantTemperature Coefficient $\pm 25 pm/^{\circ}C$ Operating Temperature $-55^{\circ}C \sim 155^{\circ}C$ Package / Case0603 (1608 Metric)Supplier Device Package0603Size / Dimension0.063" L x 0.032" W (1.60mm x 0.80mm)Height - Seated (Max)0.022" (0.55mm)Number of Terminations2Failure Rate-	Tolerance	$\pm 0.5\%$
FeaturesAnti-Sulfur, Automotive AEC-Q200, Moisture ResistantTemperature Coefficient±25pm/°COperating Temperature-55°C ~ 155°CPackage / Case0603 (1608 Metric)Supplier Device Package0603Size / Dimension0.063" L x 0.032" W (1.60mm x 0.80mm)Height - Seated (Max)0.022" (0.55mm)Number of Terminations2Failure Rate-	Power (Watts)	0.1W, 1/10W
Temperature Coefficient ±25pm/°C Operating Temperature -55°C ~ 155°C Package / Case 0603 (1608 Metric) Supplier Device Package 0603 Size / Dimension 0.063" L x 0.032" W (1.60mm x 0.80mm) Height - Seated (Max) 0.022" (0.55mm) Number of Terminations 2 Failure Rate -	Composition	Thin Film
Operating Temperature -55°C ~ 155°C Package / Case 0603 (1608 Metric) Supplier Device Package 0603 Size / Dimension 0.063" L x 0.032" W (1.60mm x 0.80mm) Height - Seated (Max) 0.022" (0.55mm) Number of Terminations 2 Failure Rate -	Features	Anti-Sulfur, Automotive AEC-Q200, Moisture Resistant
Package / Case0603 (1608 Metric)Supplier Device Package0603Size / Dimension0.063" L x 0.032" W (1.60mm x 0.80mm)Height - Seated (Max)0.022" (0.55mm)Number of Terminations2Failure Rate-	Temperature Coefficient	±25ppm/°C
Supplier Device Package0603Size / Dimension0.063" L x 0.032" W (1.60mm x 0.80mm)Height - Seated (Max)0.022" (0.55mm)Number of Terminations2Failure Rate-	Operating Temperature	-55°C ~ 155°C
Size / Dimension 0.063" L x 0.032" W (1.60mm x 0.80mm) Height - Seated (Max) 0.022" (0.55mm) Number of Terminations 2 Failure Rate -	Package / Case	0603 (1608 Metric)
Height - Seated (Max)0.022" (0.55mm)Number of Terminations2Failure Rate-	Supplier Device Package	0603
Number of Terminations2Failure Rate-	Size / Dimension	0.063" L x 0.032" W (1.60mm x 0.80mm)
Failure Rate -	Height - Seated (Max)	0.022" (0.55mm)
	Number of Terminations	2
Report errors?	Failure Rate	-
		Report errors?

AT0603DRD0710R5L Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

AT0603DRD0710R5L Payment Methods



If you have any question about AT0603DRD0710R5L, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com