

AT0603DRD072K61L

AT0603DRD072K61L Information



Part Number	AT0603DRD072K61L
Manufacturer	Yageo
Category	Resistors Chip Resistor - Surface Mount
Description	RES SMD 2.61KOHM 0.5% 1/10W 0603
Package	0603 (1608 Metric)
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



AT0603DRD072K61L Specifications

Manufacturer Part NumberAT0603DRD072K61LManufacturerYageoCategoryResistorsCategoryChip Resistor - Surface MountPackage0603 (1608 Metric)SeriesATResistance2.61 kOhmsTolerance±0.5%Power (Watts)0.1W, 1/10WCompositionThin FilmFeaturesAnti-Sulfar, Automotive AEC-Q200, Moisture ResistantToperature Coefficient±25pm/°CPackage / Case0603 (1608 Metric)Supplier Device Package0.03(1608 Metric)Size / Dimension0.02° (0.55mm)Height - Seated (Max)0.22° (0.55mm)Number of Terminations2Failure Rate.			
CategoryResistorsPackage6003 (1608 Metric)Package6003 (1608 Metric)SeriesATResistance2.61 kOhmsTolerance±0.5%Power (Watts)0.1W, 1/10WCompositionThin FilmFeaturesAnti-Sulfur, Automotive AEC-Q200, Moisture ResistantTemperature Coefficient±25ppm/°COperating Temperature6003 (1608 Metric)Supplier Device Package0603Size / Dimension0.022" (0.55mm)Height - Seated (Max)0.22" (0.55mm)Number of Terminations2Failure Rate-	Manufacturer Part Number	AT0603DRD072K61L	
Chip Resistor - Surface MountPackage0603 (1608 Metric)SeriesATResistance2.61 kOhmsTolerance±0.5%Power (Watts)0.1W, 1/10WCompositionThin FilmFeaturesAnti-Sulfur, Automotive AEC-Q200, Moisture ResistantTolerance±25pm/°COperating Temperature-55°C ~ 155°CPackage / Case0603 (1608 Metric)Supplier Device Package0603Size / Dinension0.063" L x 0.032" W (1.60mm x 0.80mm)Height - Seated (Max)2Number of Terminations2Failure Rate-	Manufacturer	Yageo	
Package003 (1608 Metric)SeriesATResistance2.61 kOhmsTolerance±0.5%Power (Watts)0.1W, 1/10WCompositionThin FilmFeaturesAnti-Sulfur, Automotive AEC-Q200, Moisture ResistantTemperature Coefficient±25ppm/°COperating Temperature6603 (1608 Metric)Package / Case0603 (1608 Metric)Supplier Device Package0.063" L x 0.032" W (1.60mm x 0.80mm)Height - Seated (Max)0.22" (0.55mm)Number of Terminations2Failure Rate-	Category	Resistors	
Series AT Resistance 2.61 kOhms Tolerance ±0.5% Power (Watts) 0.1W, 1/10W Composition Thin Film Features Anti-Sulfur, Automotive AEC-Q200, Moisture Resistant Temperature Coefficient ±25pm/°C Operating Temperature -55°C ~ 155°C Package / Case 0603 (1608 Metric) Supplier Device Package 0603 Size / Dimension 0.063" L x 0.032" W (1.60mm x 0.80mm) Height - Seated (Max) 2 Number of Terminations 2 Failure Rate -		Chip Resistor - Surface Mount	
Resistance2.61 kOhmsResistance2.61 kOhmsTolerance±0.5%Power (Watts)0.1W, 1/10WCompositionThin FilmFeaturesAnti-Sulfur, Automotive AEC-Q200, Moisture ResistantTemperature Coefficient±25ppm/°COperating Temperature-55°C ~ 155°CPackage / Case0603 (1608 Metric)Supplier Device Package0603Size / Dimension0.063" L x 0.032" W (1.60mm x 0.80mm)Height - Seated (Max)0.022" (0.55mm)Number of Terminations2Failure Rate-	Package	0603 (1608 Metric)	
Tolerance±0.5%Power (Watts)0.1W, 1/10WCompositionThin FilmFeaturesAnti-Sulfur, Automotive AEC-Q200, Moisture ResistantTemperature Coefficient±25pm/°COperating Temperature-55°C ~ 155°CPackage / Case0603 (1608 Metric)Supplier Device Package0603Size / Dimension0.063" L x 0.032" W (1.60mm x 0.80mm)Height - Seated (Max)0.22" (0.55mm)Number of Terminations2Failure Rate-	Series	AT	
Power (Watts)0.1W, 1/10WCompositionThin FilmFeaturesAnti-Sulfur, Automotive AEC-Q200, Moisture ResistantTemperature Coefficient±25ppm/°COperating Temperature-55°C ~ 155°CPackage / Case0603 (1608 Metric)Supplier Device Package0603Size / Dimension0.063" L x 0.032" W (1.60mm x 0.80mm)Height - Seated (Max)0.022" (0.55mm)Number of Terminations2Failure Rate-	Resistance	2.61 kOhms	
CompositionThin FilmFeaturesAnti-Sulfur, Automotive AEC-Q200, Moisture ResistantTemperature Coefficient $\pm 25pm^{\circ}C$ Operating Temperature $-55^{\circ}C \sim 155^{\circ}C$ Package / Case0603 (1608 Metric)Supplier Device Package0603Size / Dimension0.063" L x 0.032" W (1.60mm x 0.80mm)Height - Seated (Max)0.022" (0.55mm)Number of Terminations2Failure Rate-	Tolerance	$\pm 0.5\%$	
FeaturesAnti-Sulfur, Automotive AEC-Q200, Moisture ResistantTemperature Coefficient±25ppm/°COperating Temperature-55°C ~ 155°CPackage / Case0603 (1608 Metric)Supplier Device Package0603Size / Dimension0.063" L x 0.032" W (1.60mm x 0.80mm)Height - Seated (Max)0.022" (0.55mm)Number of Terminations2Failure Rate-	Power (Watts)	0.1W, 1/10W	
Temperature Coefficient±25pm/°COperating Temperature-55°C ~ 155°CPackage / Case0603 (1608 Metric)Supplier Device Package0603Size / Dimension0.063" L x 0.032" W (1.60mm x 0.80mm)Height - Seated (Max)0.022" (0.55mm)Number of Terminations2Failure Rate-	Composition	Thin Film	
Operating Temperature -55°C ~ 155°C Package / Case 0603 (1608 Metric) Supplier Device Package 0603 Size / Dimension 0.063" L x 0.032" W (1.60mm x 0.80mm) Height - Seated (Max) 0.022" (0.55mm) Number of Terminations 2 Failure Rate -	Features	Anti-Sulfur, Automotive AEC-Q200, Moisture Resistant	
Package / Case0603 (1608 Metric)Supplier Device Package0603Size / Dimension0.063" L x 0.032" W (1.60mm x 0.80mm)Height - Seated (Max)0.022" (0.55mm)Number of Terminations2Failure Rate-	Temperature Coefficient	±25ppm/°C	
Supplier Device Package0603Size / Dimension0.063" L x 0.032" W (1.60mm x 0.80mm)Height - Seated (Max)0.022" (0.55mm)Number of Terminations2Failure Rate-	Operating Temperature	-55°C ~ 155°C	
Size / Dimension0.063" L x 0.032" W (1.60mm x 0.80mm)Height - Seated (Max)0.022" (0.55mm)Number of Terminations2Failure Rate-	Package / Case	0603 (1608 Metric)	
Height - Seated (Max)0.022" (0.55mm)Number of Terminations2Failure Rate-	Supplier Device Package	0603	
Number of Terminations2Failure Rate-	Size / Dimension	0.063" L x 0.032" W (1.60mm x 0.80mm)	
Failure Rate -	Height - Seated (Max)	0.022" (0.55mm)	
	Number of Terminations	2	
	Failure Rate	-	
Report errors?			Report errors?

AT0603DRD072K61L Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

AT0603DRD072K61L Payment Methods



If you have any question about AT0603DRD072K61L, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com