


# AT0603DRD0773R2L

#### AT0603DRD0773R2L Information



| Part Number  | AT0603DRD0773R2L   |  |
|--------------|--|--|
| Manufacturer | Yageo  |  |
| Category     | Resistors<br>Chip Resistor - Surface Mount   |  |
| Description  | RES SMD 73.2 OHM 0.5% 1/10W 0603   |  |
| Package      | 0603 (1608 Metric)   |  |
|              | For the pricing/inventory/lead time, please contact<br>us<br>Website: https://www.heisener.com<br>E-mail: salesdept@heisener.com |  |



### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



Request a Quote

## AT0603DRD0773R2L Specifications

| Manufacturer Part Number AT0603DRD0773R2L   Manufacturer Yageo   Category Resistors   Chip Resistor - Surface Mount O603 (1608 Metric)   Package 0603 (1608 Metric)   Series AT   Resistance 73.2 Ohms   Tolerance ±0.5%   Power (Watts) 0.1W, 1/10W   Composition Thin Film   Features Anti-Sulfur, Automotive AEC-Q200, Moisture Resistant   Power (Vatts) .55°C ~ 155°C   Operating Temperature 6003 (1608 Metric)   Supplier Device Package 0603 (1608 Metric)   Number of Terminations 0.22" (0.55mm)   Number of Terminations 2   Failure Rate - |                          |  |
|---|--------------------------|--|
| CategoryResistorsCategoryResistor - Surface MountPackage0603 (1608 Metric)PackageATResistance73.2 OhmsTolerance±0.5%Power (Watts)0.1W, 1/10WCompositionThin FilmFeaturesAnti-Sulfur, Automotive AEC-Q200, Moisture ResistantTemperature Coefficient±25pm/°COperating Temperature0603 (1608 Metric)Supplier Device Package0603 (1608 Metric)Size / Dimension0.02" (0.55mm)Height - Seated (Max)0.022" (0.55mm)Number of Terminations2Failure Rate-   | Manufacturer Part Number | AT0603DRD0773R2L                                     |
| InterformerChip Resistor - Surface MountPackage0603 (1608 Metric)SeriesATResistance73.2 OhmsTolerance±0.5%Power (Watts)0.1W, 1/10WCompositionThin FilmFeaturesAnti-Sulfur, Automotive AEC-Q200, Moisture ResistantTolerance±25ppm/°COperating Temperature0603 (1608 Metric)Supplier Device Package0603 (1608 Metric)Size / Dimension0.063" L x 0.032" W (1.60mm x 0.80mm)Height + Seated (Max)0.022" (0.55mm)Number of Terminations2Failure Rate-   | Manufacturer             | Yageo  |
| Package 0603 (1608 Metric)   Series AT   Resistance 73.2 Ohms   Tolerance ±0.5%   Power (Watts) 0.1W, 1/10W   Composition Thin Film   Features Anti-Sulfur, Automotive AEC-Q200, Moisture Resistant   Temperature Coefficient ±25ppm/°C   Operating Temperature -55°C ~ 155°C   Package / Case 0603 (1608 Metric)   Supplier Device Package 0603 (1608 Metric)   Size / Dimension 0.063" L x 0.032" W (1.60mm x 0.80mm)   Height - Seated (Max) 0.022" (0.55mm)   Number of Terminations 2   Failure Rate -   | Category                 | Resistors  |
| SeriesATResistance73.2 OhmsTolerance±0.5%Power (Watts)0.1W, 1/10WCompositionThin FilmFeaturesAnti-Sulfur, Automotive AEC-Q200, Moisture ResistantTemperature Coefficient±25pm/°COperating Temperature-55°C ~ 155°CPackage / Case0603 (1608 Metric)Supplier Device Package0603Size / Dimension0.063" L x 0.032" W (1.60mm x 0.80mm)Height - Seated (Max)2Number of Terminations2Failure Rate-  |                          | Chip Resistor - Surface Mount                        |
| Resistance73.2 OhmsTolerance±0.5%Power (Watts)0.1W, 1/10WCompositionThin FilmFeaturesAnti-Sulfur, Automotive AEC-Q200, Moisture ResistantTemperature Coefficient±25ppm/°COperating Temperature-55°C ~ 155°CPackage / Case0603 (1608 Metric)Supplier Device Package0603Size / Dimension0.063" L x 0.032" W (1.60mm x 0.80mm)Height - Seated (Max)2Number of Terminations2Failure Rate-   | Package                  | 0603 (1608 Metric)                                   |
| Tolerance±0.5%Power (Watts)0.1W, 1/10WCompositionThin FilmFeaturesAnti-Sulfur, Automotive AEC-Q200, Moisture ResistantTemperature Coefficient±25ppm/°COperating Temperature-55°C ~ 155°COperating Temperature0603 (1608 Metric)Supplier Device Package0603Size / Dimension0.063" L x 0.032" W (1.60mm x 0.80mm)Height - Seated (Max)0.022" (0.55mm)Number of Terminations2Failure Rate-   | Series                   | AT   |
| Power (Watts)0.1W, 1/10WCompositionThin FilmFeaturesAnti-Sulfur, Automotive AEC-Q200, Moisture ResistantTemperature Coefficient±25pm/°COperating Temperature-55°C ~ 155°CPackage / Case0603 (1608 Metric)Supplier Device Package0603Size / Dimension0.063" L x 0.032" W (1.60mm x 0.80mm)Height - Seated (Max)0.022" (0.55mm)Number of Terminations2Failure Rate-   | Resistance               | 73.2 Ohms  |
| CompositionThin FilmFeaturesAnti-Sulfur, Automotive AEC-Q200, Moisture ResistantTemperature Coefficient $\pm 25 pm/^{\circ}C$ Operating Temperature $-55^{\circ}C \sim 155^{\circ}C$ Package / Case0603 (1608 Metric)Supplier Device Package0603Size / Dimension0.063" L x 0.032" W (1.60mm x 0.80mm)Height - Seated (Max)0.022" (0.55mm)Number of Terminations2Failure Rate-   | Tolerance                | $\pm 0.5\%$  |
| FeaturesAnti-Sulfur, Automotive AEC-Q200, Moisture ResistantTemperature Coefficient±25pm/°COperating Temperature-55°C ~ 155°CPackage / Case0603 (1608 Metric)Supplier Device Package0603Size / Dimension0.063" L x 0.032" W (1.60mm x 0.80mm)Height - Seated (Max)0.022" (0.55mm)Number of Terminations2Failure Rate-   | Power (Watts)            | 0.1W, 1/10W  |
| Temperature Coefficient±25pm/°COperating Temperature-55°C ~ 155°CPackage / Case0603 (1608 Metric)Supplier Device Package0603Size / Dimension0.063" L x 0.032" W (1.60mm x 0.80mm)Height - Seated (Max)0.022" (0.55mm)Number of Terminations2Failure Rate-   | Composition              | Thin Film  |
| Operating Temperature -55°C ~ 155°C   Package / Case 0603 (1608 Metric)   Supplier Device Package 0603   Size / Dimension 0.063" L x 0.032" W (1.60mm x 0.80mm)   Height - Seated (Max) 0.022" (0.55mm)   Number of Terminations 2   Failure Rate -   | Features                 | Anti-Sulfur, Automotive AEC-Q200, Moisture Resistant |
| Package / Case0603 (1608 Metric)Supplier Device Package0603Size / Dimension0.063" L x 0.032" W (1.60mm x 0.80mm)Height - Seated (Max)0.022" (0.55mm)Number of Terminations2Failure Rate-  | Temperature Coefficient  | ±25ppm/°C  |
| Supplier Device Package0603Size / Dimension0.063" L x 0.032" W (1.60mm x 0.80mm)Height - Seated (Max)0.022" (0.55mm)Number of Terminations2Failure Rate-  | Operating Temperature    | -55°C ~ 155°C  |
| Size / Dimension0.063" L x 0.032" W (1.60mm x 0.80mm)Height - Seated (Max)0.022" (0.55mm)Number of Terminations2Failure Rate-   | Package / Case           | 0603 (1608 Metric)                                   |
| Height - Seated (Max)0.022" (0.55mm)Number of Terminations2Failure Rate-  | Supplier Device Package  | 0603   |
| Number of Terminations2Failure Rate-  | Size / Dimension         | 0.063" L x 0.032" W (1.60mm x 0.80mm)                |
| Failure Rate -  | Height - Seated (Max)    | 0.022" (0.55mm)                                      |
|   | Number of Terminations   | 2  |
| Report errors?  | Failure Rate             | -  |
|   |                          | Report errors?                                       |

#### AT0603DRD0773R2L Guarantees



**Quality Guarantees** 

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE BUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### AT0603DRD0773R2L Payment Methods



If you have any question about AT0603DRD0773R2L, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com