

AT29C256-70JI Information



For Reference Only

Part Number AT29C256-70JI

Manufacturer Microchip Technology

Category Integrated Circuits (ICs)

Memory

Description IC FLASH 256KBIT 70NS 32PLCC

Package 32-LCC (J-Lead)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









AT29C256-70JI Specifications

Manufacturer Part Number AT29C256-70JI Manufacturer Microchip Technology Category Integrated Circuits (ICs) Memory Memory Package 32-LCC (J-Lead) Series - Memory Type Non-Volatile Memory Format FLASH Technology FLASH Memory Size 256Kb (32K x 8) Memory Interface Parallel Clock Frequency - Write Cycle Time - Word, Page 10ms Access Time 70ns Voltage - Supply 4.5 V ~ 5.5 V Operating Temperature -40°C ~ 85°C (TC) Mounting Type Surfaces Package / Case 32-LCC (J-Lead) Surplier Davis or Backers 32 B CCC	•	
Category Integrated Circuits (ICs) Memory Memory Package 32-LCC (J-Lead) Series - Memory Type Non-Volatile Memory Format FLASH Technology FLASH Memory Size 256Kb (32K x 8) Memory Interface Parallel Clock Frequency - Write Cycle Time - Word, Page 10ms Access Time 70ns Voltage - Supply 4.5 V ~ 5.5 V Operating Temperature -40°C ~ 85°C (TC) Mounting Type Surface Mount Package / Case 32-LCC (J-Lead)	Manufacturer Part Number	AT29C256-70JI
Memory Package 32-LCC (J-Lead) Series - Memory Type Non-Volatile Memory Format FLASH Technology FLASH Memory Size 256Kb (32K x 8) Memory Interface Parallel Clock Frequency - Write Cycle Time - Word, Page 10ms Access Time 70ns Voltage - Supply 4.5 V ~ 5.5 V Operating Temperature -40°C ~ 85°C (TC) Mounting Type Surface Mount Package / Case 32-LCC (J-Lead)	Manufacturer	Microchip Technology
Package 32-LCC (J-Lead) Series - Memory Type Non-Volatile Memory Format FLASH Technology FLASH Memory Size 256Kb (32K x 8) Memory Interface Parallel Clock Frequency - Write Cycle Time - Word, Page 10ms Access Time 70ns Voltage - Supply 4.5 V ~ 5.5 V Operating Temperature -40°C ~ 85°C (TC) Mounting Type Surface Mount Package / Case 32-LCC (J-Lead)	Category	Integrated Circuits (ICs)
Series - Memory Type Non-Volatile Memory Format FLASH Technology FLASH Memory Size 256Kb (32K x 8) Memory Interface Parallel Clock Frequency - Write Cycle Time - Word, Page 10ms Access Time 70ns Voltage - Supply 4.5 V ~ 5.5 V Operating Temperature -40°C ~ 85°C (TC) Mounting Type Surface Mount Package / Case 32-LCC (J-Lead)		Memory
Memory TypeNon-VolatileMemory FormatFLASHTechnologyFLASHMemory Size256Kb (32K x 8)Memory InterfaceParallelClock Frequency-Write Cycle Time - Word, Page10msAccess Time70nsVoltage - Supply4.5 V ~ 5.5 VOperating Temperature-40°C ~ 85°C (TC)Mounting TypeSurface MountPackage / Case32-LCC (J-Lead)	Package	32-LCC (J-Lead)
Memory FormatFLASHTechnologyFLASHMemory Size256Kb (32K x 8)Memory InterfaceParallelClock Frequency-Write Cycle Time - Word, Page10msAccess Time70nsVoltage - Supply4.5 V ~ 5.5 VOperating Temperature-40°C ~ 85°C (TC)Mounting TypeSurface MountPackage / Case32-LCC (J-Lead)	Series	-
Technology FLASH Memory Size 256Kb (32K x 8) Memory Interface Parallel Clock Frequency - Write Cycle Time - Word, Page 10ms Access Time 70ns Voltage - Supply Operating Temperature 4.5 V ~ 5.5 V Operating Temperature Mounting Type Surface Mount Package / Case 32-LCC (J-Lead)	Memory Type	Non-Volatile
Memory Size256Kb (32K x 8)Memory InterfaceParallelClock Frequency-Write Cycle Time - Word, Page10msAccess Time70nsVoltage - Supply4.5 V ~ 5.5 VOperating Temperature-40°C ~ 85°C (TC)Mounting TypeSurface MountPackage / Case32-LCC (J-Lead)	Memory Format	FLASH
Memory InterfaceParallelClock Frequency-Write Cycle Time - Word, Page10msAccess Time70nsVoltage - Supply4.5 V ~ 5.5 VOperating Temperature-40°C ~ 85°C (TC)Mounting TypeSurface MountPackage / Case32-LCC (J-Lead)	Technology	FLASH
Clock Frequency Write Cycle Time - Word, Page 10ms Access Time 70ns Voltage - Supply 4.5 V ~ 5.5 V Operating Temperature -40°C ~ 85°C (TC) Mounting Type Surface Mount Package / Case 32-LCC (J-Lead)	Memory Size	256Kb (32K x 8)
Write Cycle Time - Word, Page Access Time 70ns Voltage - Supply 4.5 V ~ 5.5 V Operating Temperature -40°C ~ 85°C (TC) Mounting Type Surface Mount Package / Case 32-LCC (J-Lead)	Memory Interface	Parallel
Access Time 70ns Voltage - Supply $4.5 \text{ V} \sim 5.5 \text{ V}$ Operating Temperature $-40 ^{\circ}\text{C} \sim 85 ^{\circ}\text{C}$ (TC)Mounting TypeSurface MountPackage / Case 32-LCC (J-Lead)	Clock Frequency	-
Voltage - Supply $4.5 \text{ V} \sim 5.5 \text{ V}$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C (TC)}$ Mounting Type Surface Mount Package / Case 32-LCC (J-Lead)	Write Cycle Time - Word, Page	10ms
Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ (TC) Mounting Type Surface Mount Package / Case 32-LCC (J-Lead)	Access Time	70ns
Mounting Type Surface Mount Package / Case 32-LCC (J-Lead)	Voltage - Supply	4.5 V ~ 5.5 V
Package / Case 32-LCC (J-Lead)	Operating Temperature	-40°C ~ 85°C (TC)
	Mounting Type	Surface Mount
Sumplier Davies Peaks as	Package / Case	32-LCC (J-Lead)
Supplier Device rackage 32-PLCC	Supplier Device Package	32-PLCC
Report errors?		Report errors?

AT29C256-70JI Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

AT29C256-70JI Payment Methods





















AT29C256-70JI Shipping Methods













If you have any question about AT29C256-70JI, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com