

## ATSAM4SA16BB-AN

### **ATSAM4SA16BB-AN Information**



For Reference Only

Part NumberATSAM4SA16BB-ANManufacturerMicrochip TechnologyCategoryIntegrated Circuits (ICs)<br/>Embedded - Microcontrollers

**Description** FLASH,160K SRAM

Package 64-LQFP

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **ATSAM4SA16BB-AN Specifications**

| ATSAM4SA16BB-AN                                                |                                                                                                                                                                                                                                                                                                                                 |
|----------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Microchip Technology                                           |                                                                                                                                                                                                                                                                                                                                 |
| Integrated Circuits (ICs)                                      |                                                                                                                                                                                                                                                                                                                                 |
| Embedded - Microcontrollers                                    |                                                                                                                                                                                                                                                                                                                                 |
| 64-LQFP                                                        |                                                                                                                                                                                                                                                                                                                                 |
| SAM4S                                                          |                                                                                                                                                                                                                                                                                                                                 |
| ARM® Cortex®-M4                                                |                                                                                                                                                                                                                                                                                                                                 |
| 32-Bit                                                         |                                                                                                                                                                                                                                                                                                                                 |
| 120MHz                                                         |                                                                                                                                                                                                                                                                                                                                 |
| I <sup>2</sup> C, IrDA, Memory Card, SPI, SSC, UART/USART, USB |                                                                                                                                                                                                                                                                                                                                 |
| Brown-out Detect/Reset, DMA, POR, PWM, WDT                     |                                                                                                                                                                                                                                                                                                                                 |
| 47                                                             |                                                                                                                                                                                                                                                                                                                                 |
| 1MB (1M x 8)                                                   |                                                                                                                                                                                                                                                                                                                                 |
| FLASH                                                          |                                                                                                                                                                                                                                                                                                                                 |
| -                                                              |                                                                                                                                                                                                                                                                                                                                 |
| 160K x 8                                                       |                                                                                                                                                                                                                                                                                                                                 |
| 1.62 V ~ 3.6 V                                                 |                                                                                                                                                                                                                                                                                                                                 |
| A/D 11x12b, D/A 2x12b                                          |                                                                                                                                                                                                                                                                                                                                 |
| Internal                                                       |                                                                                                                                                                                                                                                                                                                                 |
| -40°C ~ 105°C (TA)                                             |                                                                                                                                                                                                                                                                                                                                 |
| -                                                              |                                                                                                                                                                                                                                                                                                                                 |
| 64-LQFP                                                        |                                                                                                                                                                                                                                                                                                                                 |
| 64-LQFP (10x10)                                                |                                                                                                                                                                                                                                                                                                                                 |
|                                                                | Report errors?                                                                                                                                                                                                                                                                                                                  |
|                                                                | Microchip Technology Integrated Circuits (ICs) Embedded - Microcontrollers 64-LQFP SAM4S ARM® Cortex®-M4 32-Bit 120MHz I²C, IrDA, Memory Card, SPI, SSC, UART/USART, USB Brown-out Detect/Reset, DMA, POR, PWM, WDT 47 1MB (1M x 8) FLASH - 160K x 8 1.62 V ~ 3.6 V A/D 11x12b, D/A 2x12b Internal -40°C ~ 105°C (TA) - 64-LQFP |

### **ATSAM4SA16BB-AN Guarantees**



#### **Ouality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **ATSAM4SA16BB-AN Payment Methods**



















## **ATSAM4SA16BB-AN Shipping Methods**













If you have any question about ATSAM4SA16BB-AN, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com