

ATSAM4SD32BB-MNR

ATSAM4SD32BB-MNR Information



For Reference Only

Part Number ATSAM4SD32BB-MNR

Manufacturer Microchip Technology

Category Integrated Circuits (ICs)
Embedded - Microcontrollers

DescriptionFLASH,160K SRAMPackage64-VFQFN Exposed Pad

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ATSAM4SD32BB-MNR Specifications

Manufacturer Part Number Manufacturer Microchip Technology Integrated Circuits (ICs) Embedded - Microcontrollers Package 64-VFQFN Exposed Pad Series SAM4S Core Processor ARM® Cortex®-M4 Core Size 32-Bit Speed 120MHz Connectivity PC, IrDA, Memory Card, SPI, SSC, UART/USART, USB Peripherals Brown-out Detect/Reset, DMA, POR, PWM, WDT Number of I/O Program Memory Size Program Memory Type FLASH EEPROM Size Voltage - Supply (Vcc/Vdd) Data Converters A/D 11x12b, D/A 2x12b
Category Integrated Circuits (ICs) Embedded - Microcontrollers Package 64-VFQFN Exposed Pad Series SAM4S Core Processor ARM® Cortex®-M4 Core Size 32-Bit Speed 120MHz Connectivity I°C, IrDA, Memory Card, SPI, SSC, UART/USART, USB Peripherals Brown-out Detect/Reset, DMA, POR, PWM, WDT Number of I/O 47 Program Memory Size 2MB (2M x 8) Program Memory Type FLASH EEPROM Size RAM Size Voltage - Supply (Vcc/Vdd) 1.62 V ~ 3.6 V Data Converters A/D 11x12b, D/A 2x12b
Embedded - Microcontrollers Package 64-VFQFN Exposed Pad Series SAM4S Core Processor ARM® Cortex®-M4 Core Size 32-Bit Speed 120MHz Connectivity PC, IrDA, Memory Card, SPI, SSC, UART/USART, USB Peripherals Brown-out Detect/Reset, DMA, POR, PWM, WDT Number of I/O 47 Program Memory Size 2MB (2M x 8) Program Memory Type FLASH EEPROM Size - RAM Size 160K x 8 Voltage - Supply (Vcc/Vdd) 1.62 V ~ 3.6 V Data Converters A/D 11x12b, D/A 2x12b
Package 64-VFQFN Exposed Pad Series SAM4S Core Processor ARM® Cortex®-M4 Core Size 32-Bit Speed 120MHz Connectivity PC, IrDA, Memory Card, SPI, SSC, UART/USART, USB Peripherals Brown-out Detect/Reset, DMA, POR, PWM, WDT Number of I/O 47 Program Memory Size 2MB (2M x 8) Program Memory Type FLASH EEPROM Size - RAM Size 160K x 8 Voltage - Supply (Vcc/Vdd) 1.62 V ~ 3.6 V Data Converters A/D 11x12b, D/A 2x12b
$\begin{array}{cccccccccccccccccccccccccccccccccccc$
Core Processor ARM® Cortex®-M4 Core Size 32-Bit Speed 120MHz Connectivity I²C, IrDA, Memory Card, SPI, SSC, UART/USART, USB Peripherals Brown-out Detect/Reset, DMA, POR, PWM, WDT Number of I/O 47 Program Memory Size 2MB (2M x 8) Program Memory Type FLASH EEPROM Size - RAM Size 160K x 8 Voltage - Supply (Vcc/Vdd) 1.62 V ~ 3.6 V Data Converters A/D 11x12b, D/A 2x12b
$ \begin{array}{cccccccccccccccccccccccccccccccccccc$
Speed 120MHz Connectivity IPC, IrDA, Memory Card, SPI, SSC, UART/USART, USB Peripherals Brown-out Detect/Reset, DMA, POR, PWM, WDT Number of I/O 47 Program Memory Size 2MB (2M x 8) Program Memory Type FLASH EEPROM Size - RAM Size 160K x 8 Voltage - Supply (Vcc/Vdd) 1.62 V ~ 3.6 V Data Converters A/D 11x12b, D/A 2x12b
Connectivity I ² C, IrDA, Memory Card, SPI, SSC, UART/USART, USB Peripherals Brown-out Detect/Reset, DMA, POR, PWM, WDT Number of I/O 47 Program Memory Size 2MB (2M x 8) Program Memory Type FLASH EEPROM Size - RAM Size 160K x 8 Voltage - Supply (Vcc/Vdd) 1.62 V ~ 3.6 V Data Converters A/D 11x12b, D/A 2x12b
Peripherals Brown-out Detect/Reset, DMA, POR, PWM, WDT Number of I/O 47 Program Memory Size 2MB (2M x 8) Program Memory Type FLASH EEPROM Size - RAM Size 160K x 8 Voltage - Supply (Vcc/Vdd) Data Converters Brown-out Detect/Reset, DMA, POR, PWM, WDT 47 2MB (2M x 8) FLASH EEPROM Size - RAM Size 160K x 8 Voltage - Supply (Vcc/Vdd) A/D 11x12b, D/A 2x12b
Number of I/O47Program Memory Size $2MB (2M \times 8)$ Program Memory Type $FLASH$ EEPROM Size-RAM Size $160K \times 8$ Voltage - Supply (Vcc/Vdd) $1.62 \text{ V} \sim 3.6 \text{ V}$ Data Converters $A/D 11x12b, D/A 2x12b$
Program Memory Size $2MB (2M \times 8)$ Program Memory TypeFLASHEEPROM Size-RAM Size $160K \times 8$ Voltage - Supply (Vcc/Vdd) $1.62 \text{ V} \sim 3.6 \text{ V}$ Data ConvertersA/D $11\times12b$, D/A $2\times12b$
Program Memory Type FLASH EEPROM Size - RAM Size $160K \times 8$ Voltage - Supply (Vcc/Vdd) $1.62 \text{ V} \sim 3.6 \text{ V}$ Data Converters $A/D 11x12b, D/A 2x12b$
EEPROM Size - RAM Size $160K \times 8$ Voltage - Supply (Vcc/Vdd) $1.62 \text{ V} \sim 3.6 \text{ V}$ Data Converters $A/D 11x12b, D/A 2x12b$
RAM Size $160K \times 8$ Voltage - Supply (Vcc/Vdd) $1.62 \text{ V} \sim 3.6 \text{ V}$ Data Converters $A/D 11x12b, D/A 2x12b$
Voltage - Supply (Vcc/Vdd) $1.62 \text{ V} \sim 3.6 \text{ V}$ Data Converters $A/D 11x12b, D/A 2x12b$
Data Converters A/D 11x12b, D/A 2x12b
Oscillator Type Internal
Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C} \text{ (TA)}$
Mounting Type -
Package / Case 64-VFQFN Exposed Pad
Supplier Device Package 64-QFN (9x9)
Report error

ATSAM4SD32BB-MNR Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ATSAM4SD32BB-MNR Payment Methods





















ATSAM4SD32BB-MNR Shipping Methods













If you have any question about ATSAM4SD32BB-MNR, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com