



ATTA2R Information

Part Number ATTA2R

Manufacturer Amphenol PCD

Category Heisener.com

Connectors, Interconnects Terminal Blocks - Din Rail, Channel

Description

CONN TERM BLK FEED THRU 12-24AWG

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ATTA2R Specifications

For Reference Only

Manufacturer Part Number ATTA2R Manufacturer Amphenol PCD Category Connectors, Interconnects Terminal Blocks - Din Rail, Channel Package - Series ATT Type Feed Through, Isolated Disconnect Type - Number of Positions 4 Number of Levels 3 Terminal - Width 6.0mm Termination Style Screw Current - IEC 24A Voltage - IEC 400V Current - UL 25A Voltage - UL 300V Wire Gauge or Range - AWG 12-24 AWG Wire Gauge or Range - mm² 0.5-2.5mm² Features - Color Red		
Category Connectors, Interconnects Package - Series ATT Type Feed Through, Isolated Disconnect Type - Number of Positions 4 Number of Levels 3 Terminal - Width 6.0mm Termination Style Screw Current - IEC 24A Voltage - IEC 400V Current - UL 25A Voltage - UL 300V Wire Gauge or Range - AWG 12-24 AWG Wire Gauge or Range - mm² 0.5-2.5mm² Features - Color Red	Manufacturer Part Number	ATTA2R
Package - Series ATT Type Feed Through, Isolated Disconnect Type - Number of Positions 4 Number of Levels 3 Terminal - Width 6.0mm Termination Style Screw Current - IEC 24A Voltage - IEC 400V Current - UL 25A Voltage - UL 300V Wire Gauge or Range - AWG 12-24 AWG Wire Gauge or Range - mm² 0.5-2.5mm² Features - Color Red	Manufacturer	Amphenol PCD
Package - Series ATT Type Feed Through, Isolated Disconnect Type - Number of Positions 4 Number of Levels 3 Terminal - Width 6.0mm Termination Style Screw Current - IEC 24A Voltage - IEC 400V Current - UL 25A Voltage - UL 300V Wire Gauge or Range - AWG 12-24 AWG Wire Gauge or Range - mm² 0.5-2.5mm² Features - Color Red	Category	Connectors, Interconnects
SeriesATTTypeFeed Through, IsolatedDisconnect Type-Number of Positions4Number of Levels3Terminal - Width6.0mmTermination StyleScrewCurrent - IEC24AVoltage - IEC400VCurrent - UL25AVoltage - UL300VWire Gauge or Range - AWG12-24 AWGWire Gauge or Range - mm²0.5-2.5mm²Features-ColorRed		Terminal Blocks - Din Rail, Channel
Type Feed Through, Isolated Disconnect Type - Number of Positions 4 Number of Levels 3 Terminal - Width 6.0mm Termination Style Screw Current - IEC 24A Voltage - IEC 400V Current - UL 25A Voltage - UL 300V Wire Gauge or Range - AWG 12-24 AWG Wire Gauge or Range - mm² 0.5-2.5mm² Features - Color Red	Package	-
Disconnect Type - Number of Positions 4 Number of Levels 3 Terminal - Width 6.0mm Termination Style Screw Current - IEC 24A Voltage - IEC 400V Current - UL 25A Voltage - UL 300V Wire Gauge or Range - AWG 12-24 AWG Wire Gauge or Range - mm² 0.5-2.5mm² Features - Color Red	Series	ATT
Number of Positions4Number of Levels3Terminal - Width6.0mmTermination StyleScrewCurrent - IEC24AVoltage - IEC400VCurrent - UL25AVoltage - UL300VWire Gauge or Range - AWG12-24 AWGWire Gauge or Range - mm²0.5-2.5mm²Features-ColorRed	Type	Feed Through, Isolated
Number of Levels Terminal - Width 6.0mm Termination Style Screw Current - IEC 24A Voltage - IEC 400V Current - UL 25A Voltage - UL Wire Gauge or Range - AWG Wire Gauge or Range - awG Wire Gauge or Range - mm² Features Color Red	Disconnect Type	-
Terminal - Width Termination Style Screw Current - IEC 24A Voltage - IEC 400V Current - UL 25A Voltage - UL 300V Wire Gauge or Range - AWG Wire Gauge or Range - mm² Features - Color Red	Number of Positions	4
Termination Style Current - IEC 24A Voltage - IEC 400V Current - UL 25A Voltage - UL 300V Wire Gauge or Range - AWG Wire Gauge or Range - mm² Features - Color Red	Number of Levels	3
Current - IEC 24A Voltage - IEC 400V Current - UL 25A Voltage - UL 300V Wire Gauge or Range - AWG 12-24 AWG Wire Gauge or Range - mm² 0.5-2.5mm² Features - Color Red	Terminal - Width	6.0mm
Voltage - IEC Current - UL 25A Voltage - UL 300V Wire Gauge or Range - AWG Wire Gauge or Range - mm² 0.5-2.5mm² Features - Color Red	Termination Style	Screw
Current - UL 25A Voltage - UL 300V Wire Gauge or Range - AWG 12-24 AWG Wire Gauge or Range - mm² 0.5-2.5mm² Features - Color Red	Current - IEC	24A
Voltage - UL300VWire Gauge or Range - AWG12-24 AWGWire Gauge or Range - mm²0.5-2.5mm²Features-ColorRed	Voltage - IEC	400V
Wire Gauge or Range - AWG Wire Gauge or Range - mm² O.5-2.5mm² Features Color Red	Current - UL	25A
Wire Gauge or Range - mm ² Features Color Red 0.5-2.5mm ² - Red	Voltage - UL	300V
Features - Color Red	Wire Gauge or Range - AWG	12-24 AWG
Color Red	Wire Gauge or Range - mm ²	0.5-2.5mm ²
	Features	-
Report errors?	Color	Red
		Report errors?

ATTA2R Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ATTA2R Payment Methods





















ATTA2R Shipping Methods













If you have any question about ATTA2R, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com