

ATV251

ote

ATV251 Information

| Containance cano her | Part Number Manufacturer Category Description Package | ATV251 Artesyn Embedded Technologies Power Supplies - External/Internal (Off-Board) AC DC Converters AC/DC CONVERTER 5V 2X12V 20W - For the pricing/inventory/lead time, please contact | |
|----------------------|---|---|---------------|
| For Reference Only | | us Website: https://www.heisener.com E-mail: salesdept@heisener.com | Request a Quo |

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



ATV251 Specifications

| ManufacturerArtesyn Embedded TechnologiesCategoryPower Supplies - External/Internal (Off-Board)Ac DC ConvertersPackage-PackageATVStriesATVTypeLinearNumber of Outputs3Voltage - Input100 ~ 240 VACVoltage - Output 15VVoltage - Output 212VVoltage - Output 312VVoltage - Output 4-Current - Output (Max)2A, 400mA, 400mAPower (Watts)20WApplicationsITE (Commercial)Voltage - Isolation-Efficiency0°C ~ 70°C (With Derating)Operating TemperatureO°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input Capable, Remote SenseMounting TypeChasis MountSize / Dimension6:0°L x 4.00° W x 1.62° H (165.0mm x 102.0mm x 41.5mm) | | | | |
|--|--------------------------|--|----------------|--|
| Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package Series ATV Spries Mumber of Outputs 3 Voltage - Input 100 ~ 240 VAC Voltage - Output 1 5V Voltage - Output 2 12V Voltage - Output 3 12V Voltage - Output 4 - Current - Output (Max) 20W Applications TE (Commercial) Voltage - Isolation - Efficiency 40% Operating Temperature 0°C ~ 70°C (With Derating) Peatures Adjustable Output, DC Input Capable, Remote Sense Mounting Type Size / Dimension | Manufacturer Part Number | ATV251 | | |
| AC DC Converters Package - Series ATV Type Linear Number of Outputs 3 Voltage - Input 100 ~ 240 VAC Voltage - Output 1 5V Voltage - Output 2 12V Voltage - Output 3 12V Voltage - Output 4 - Current - Output 4 - Current - Output 4 - Power (Watts) 20W Applications ITE (Commercial) Voltage - Isolation - Efficiency 40% Operating Temperature 0°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Remote Sense Mounting Type Chassis Mount Size / Dimension 6.50° L x 4.00° W x 1.62° H (165.0mm x 102.0mm x 41.5mm) | Manufacturer | Artesyn Embedded Technologies | | |
| Package-SeriesATVTypeLinearNumber of Outputs3Voltage - Input100 ~ 240 VACVoltage - Output 15VVoltage - Output 212VVoltage - Output 312VVoltage - Output 4-Current - Output (Max)2A, 400mA, 400mAPower (Watts)20WApplicationsITE (Commercial)Voltage - Isolation-Efficiency0°C ~ 70°C (With Derating)PeaturesAjustable Output, DC Input Capable, Remote SenseMounting TypeChasis MountSize / Dimension6.50" L x 4.00" W x 1.62" H (165.0mm x 102.0mm x 41.5mm) | Category | Power Supplies - External/Internal (Off-Board) | | |
| Series ATV Type Linear Number of Outputs 3 Voltage - Input 100 ~ 240 VAC Voltage - Output 1 5V Voltage - Output 2 12V Voltage - Output 3 12V Voltage - Output 4 - Current - Output (Max) 2A, 400mA, 400mA Power (Watts) 20W Applications ITE (Commercial) Voltage - Isolation - Efficiency 40% Operating Temperature O°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Remote Sense Mounting Type Chassis Mount Size / Dimension 5.0° L x 4.00° W x 1.62° H (165.0mm x 102.0mm x 41.5mm) | | AC DC Converters | | |
| Type Linear Number of Outputs 3 Voltage - Input 100 ~ 240 VAC Voltage - Output 1 5V Voltage - Output 2 12V Voltage - Output 3 12V Voltage - Output 4 - Current - Output (Max) 2A, 400mA, 400mA Power (Watts) 20W Applications ITE (Commercial) Voltage - Isolation - Efficiency 0°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Remote Sense Mounting Type Chassis Mount Size / Dimension 50° L x 4.00° W x 1.62° H (165.0mm x 102.0mm x 41.5mm) | Package | - | | |
| Number of Outputs 3 Number of Outputs 100 ~ 240 VAC Voltage - Output 1 5V Voltage - Output 2 12V Voltage - Output 3 12V Voltage - Output 4 - Current - Output (Max) 2A, 400mA, 400mA Power (Watts) 20W Applications ITE (commercial) Voltage - Isolation - Efficiency 40% Operating Temperature 0°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Remote Sense Mounting Type Chassis Mount Size / Dimension 6.50" L x 4.00" W x 1.62" H (165.0mm x 102.0mm x 41.5mm) | Series | ATV | | |
| Voltage - Input 100 ~ 240 VAC Voltage - Output 1 5V Voltage - Output 2 12V Voltage - Output 3 12V Voltage - Output 4 - Current - Output (Max) 2A, 400mA, 400mA Power (Watts) 20W Voltage - Isolation - Efficiency 40% Operating Temperature 0°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Remote Sense Mounting Type 6.50" L x 4.00" W x 1.62" H (165.0mm x 102.0mm x 41.5mm) | Туре | Linear | | |
| Voltage - Output 1 5V Voltage - Output 2 12V Voltage - Output 3 12V Voltage - Output 4 - Current - Output (Max) 2A, 400mA, 400mA Power (Watts) 20W Applications ITE (Commercial) Voltage - Isolation - Efficiency 0°C ~ 70°C (With Derating) Peatures Adjustable Output, DC Input Capable, Remote Sense Mounting Type Chassis Mount Size / Dimension 6.50" L x 4.00" W x 1.62" H (165.0mm x 102.0mm x 41.5mm) | Number of Outputs | 3 | | |
| Voltage - Output 212VVoltage - Output 312VVoltage - Output 4-Current - Output (Max)2A, 400mA, 400mAPower (Watts)20WApplicationsITE (Commercial)Voltage - Isolation-Efficiency40%Operating Temperature0°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input Capable, Remote SenseMounting TypeChassis MountSize / Dimension6.50" L x 4.00" W x 1.62" H (165.0mm x 102.0mm x 41.5mm) | Voltage - Input | 100 ~ 240 VAC | | |
| Voltage - Output 312VVoltage - Output 4-Current - Output (Max)2A, 400mA, 400mAPower (Watts)20WApplicationsITE (Commercial)Voltage - Isolation-Efficiency40%Operating Temperature0°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input Capable, Remote SenseMounting TypeChassis MountSize / Dimension6.50" L x 4.00" W x 1.62" H (165.0mm x 102.0mm x 41.5mm) | Voltage - Output 1 | 5V | | |
| Voltage - Output 4-Current - Output (Max)2A, 400mA, 400mAPower (Watts)20WApplicationsITE (Commercial)Voltage - Isolation-Efficiency40%Operating Temperature0°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input Capable, Remote SenseMounting TypeChassis MountSize / Dimension6.50" L x 4.00" W x 1.62" H (165.0mm x 102.0mm x 41.5mm) | Voltage - Output 2 | 12V | | |
| Current - Output (Max)2A, 400mA, 400mAPower (Watts)20WApplicationsITE (Commercial)Voltage - Isolation-Efficiency40%Operating Temperature0°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input Capable, Remote SenseMounting TypeChassis MountSize / Dimension6.50" L x 4.00" W x 1.62" H (165.0mm x 102.0mm x 41.5mm) | Voltage - Output 3 | 12V | | |
| Power (Watts)20WApplicationsITE (Commercial)Voltage - Isolation-Efficiency40%Operating Temperature0°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input Capable, Remote SenseMounting TypeChassis MountSize / Dimension6.50" L x 4.00" W x 1.62" H (165.0mm x 102.0mm x 41.5mm) | Voltage - Output 4 | - | | |
| ApplicationsITE (Commercial)Voltage - Isolation-Efficiency40%Operating Temperature0°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input Capable, Remote SenseMounting TypeChassis MountSize / Dimension6.50" L x 4.00" W x 1.62" H (165.0mm x 102.0mm x 41.5mm) | Current - Output (Max) | 2A, 400mA, 400mA | | |
| Voltage - Isolation-Efficiency40%Operating Temperature0°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input Capable, Remote SenseMounting TypeChassis MountSize / Dimension6.50" L x 4.00" W x 1.62" H (165.0mm x 102.0mm x 41.5mm) | Power (Watts) | 20W | | |
| Efficiency40%Operating Temperature0°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input Capable, Remote SenseMounting TypeChassis MountSize / Dimension6.50" L x 4.00" W x 1.62" H (165.0mm x 102.0mm x 41.5mm) | Applications | ITE (Commercial) | | |
| Operating Temperature0°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input Capable, Remote SenseMounting TypeChassis MountSize / Dimension6.50" L x 4.00" W x 1.62" H (165.0mm x 102.0mm x 41.5mm) | Voltage - Isolation | - | | |
| FeaturesAdjustable Output, DC Input Capable, Remote SenseMounting TypeChassis MountSize / Dimension6.50" L x 4.00" W x 1.62" H (165.0mm x 102.0mm x 41.5mm) | Efficiency | 40% | | |
| Mounting Type Chassis Mount Size / Dimension 6.50" L x 4.00" W x 1.62" H (165.0mm x 102.0mm x 41.5mm) | Operating Temperature | 0° C ~ 70° C (With Derating) | | |
| Size / Dimension 6.50" L x 4.00" W x 1.62" H (165.0mm x 102.0mm x 41.5mm) | Features | Adjustable Output, DC Input Capable, Remote Sense | | |
| | Mounting Type | Chassis Mount | | |
| Report errors? | Size / Dimension | 6.50" L x 4.00" W x 1.62" H (165.0mm x 102.0mm x 41.5mm) | | |
| | | | Report errors? | |

ATV251 Guarantees



If you have any question about ATV251, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com