

ATX25G Information

Heisener.com

Part Number ATX25G

Manufacturer Amphenol PCD

Category Connectors, Interconnects

Terminal Blocks - Din Rail, Channel

Description CONN TERM BLK FEED THRU 2-14 AWG

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ATX25G Specifications

Manufacturer ATX25G Manufacturer Amphenol PCD Category Connectors, Interconnects Terminal Blocks - Din Rail, Channel Package - Series ATX Type Feed Through Disconnect Type - Number of Positions 2 Number of Levels 1 Terminal - Width 12.0mm Termination Style Screw Current - IEC 101A Voltage - IEC 800V Current - UL 115A Voltage - UL 600V Wire Gauge or Range - AWG 2-14 AWG Wire Gauge or Range - mm² 6-25mm² Features Explosion Proof, Harsh Environment Color Green		
Category Connectors, Interconnects Terminal Blocks - Din Rail, Channel Package - Series ATX Type Feed Through Disconnect Type - Number of Positions 2 Number of Levels 1 Terminal - Width 12.0mm Termination Style Screw Current - IEC 101A Voltage - IEC 800V Current - UL 115A Voltage - UL 600V Wire Gauge or Range - AWG 2-14 AWG Wire Gauge or Range - mm² 6-25mm² Features Explosion Proof, Harsh Environment Color Green	Manufacturer Part Number	ATX25G
Package - Series ATX Type Feed Through Disconnect Type - Number of Positions 2 Number of Levels 1 Terminal - Width 12.0mm Termination Style Screw Current - IEC 101A Voltage - IEC 800V Current - UL 115A Voltage - UL 600V Wire Gauge or Range - AWG 2-14 AWG Wire Gauge or Range - mm² 6-25mm² Features Explosion Proof, Harsh Environment Color Green	Manufacturer	Amphenol PCD
Package - Series ATX Type Feed Through Disconnect Type - Number of Positions 2 Number of Levels 1 Terminal - Width 12.0mm Termination Style Screw Current - IEC 101A Voltage - IEC 800V Current - UL 115A Voltage - UL 600V Wire Gauge or Range - AWG 2-14 AWG Wire Gauge or Range - mm² 6-25mm² Features Explosion Proof, Harsh Environment Color Green	Category	Connectors, Interconnects
Series ATX Type Feed Through Disconnect Type - Number of Positions 2 Number of Levels 1 Terminal - Width 12.0mm Termination Style Screw Current - IEC 101A Voltage - IEC 800V Current - UL 115A Voltage - UL 600V Wire Gauge or Range - AWG 2-14 AWG Wire Gauge or Range - mm² 6-25mm² Features Explosion Proof, Harsh Environment Color Green		Terminal Blocks - Din Rail, Channel
Type Feed Through Disconnect Type - Number of Positions 2 Number of Levels 1 Terminal - Width 12.0mm Termination Style Screw Current - IEC 101A Voltage - IEC 800V Current - UL 115A Voltage - UL 600V Wire Gauge or Range - AWG 2-14 AWG Wire Gauge or Range - mm² 6-25mm² Features Explosion Proof, Harsh Environment Color Green	Package	-
Disconnect Type - Number of Positions 2 Number of Levels 1 Terminal - Width 12.0mm Termination Style Screw Current - IEC 101A Voltage - IEC 800V Current - UL 115A Voltage - UL 600V Wire Gauge or Range - AWG 2-14 AWG Wire Gauge or Range - mm² 6-25mm² Features Explosion Proof, Harsh Environment Color Green	Series	ATX
Number of Positions 2 Number of Levels 1 Terminal - Width 12.0mm Termination Style Screw Current - IEC 101A Voltage - IEC 800V Current - UL 115A Voltage - UL 600V Wire Gauge or Range - AWG 2-14 AWG Wire Gauge or Range - mm² 6-25mm² Features Explosion Proof, Harsh Environment Color Green	Туре	Feed Through
Number of Levels 1 Terminal - Width 12.0mm Termination Style Screw Current - IEC 101A Voltage - IEC 800V Current - UL 115A Voltage - UL 600V Wire Gauge or Range - AWG 2-14 AWG Wire Gauge or Range - mm² 6-25mm² Features Explosion Proof, Harsh Environment Color Green	Disconnect Type	-
Terminal - Width Termination Style Screw Current - IEC 101A Voltage - IEC 800V Current - UL 115A Voltage - UL 600V Wire Gauge or Range - AWG Wire Gauge or Range - mm² Features Explosion Proof, Harsh Environment Color Green	Number of Positions	2
Termination Style Current - IEC 101A Voltage - IEC 800V Current - UL 115A Voltage - UL 600V Wire Gauge or Range - AWG Wire Gauge or Range - mm² 6-25mm² Features Explosion Proof, Harsh Environment Color Green	Number of Levels	1
Current - IEC 101A Voltage - IEC 800V Current - UL 115A Voltage - UL 600V Wire Gauge or Range - AWG 2-14 AWG Wire Gauge or Range - mm² 6-25mm² Features Explosion Proof, Harsh Environment Color Green	Terminal - Width	12.0mm
Voltage - IEC 800V Current - UL 115A Voltage - UL 600V Wire Gauge or Range - AWG 2-14 AWG Wire Gauge or Range - mm² 6-25mm² Features Explosion Proof, Harsh Environment Color Green	Termination Style	Screw
Current - UL 115A Voltage - UL 600V Wire Gauge or Range - AWG 2-14 AWG Wire Gauge or Range - mm² 6-25mm² Features Explosion Proof, Harsh Environment Color Green	Current - IEC	101A
Voltage - UL Wire Gauge or Range - AWG Wire Gauge or Range - mm² 6-25mm² Features Explosion Proof, Harsh Environment Color Green	Voltage - IEC	800V
Wire Gauge or Range - AWG Wire Gauge or Range - mm ² Features Explosion Proof, Harsh Environment Color Green	Current - UL	115A
Wire Gauge or Range - mm ² Features Color 6-25mm ² Explosion Proof, Harsh Environment Green	Voltage - UL	600V
Features Explosion Proof, Harsh Environment Color Green	Wire Gauge or Range - AWG	2-14 AWG
Color Green	Wire Gauge or Range - mm ²	6-25mm ²
	Features	Explosion Proof, Harsh Environment
Domont organic	Color	Green
Report errors?		Report errors?

ATX25G Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ATX25G Payment Methods





















ATX25G Shipping Methods













If you have any question about ATX25G, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com