

## **ATX25W Information**

Heisener.com

Part Number ATX25W

Manufacturer Amphenol PCD

Category Connectors, Interconnects

Terminal Blocks - Din Rail, Channel

**Description** CONN TERM BLK FEED THRU 2-14 AWG

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **ATX25W Specifications**

Manufacturer Part Number       ATX25W         Manufacturer       Amphenol PCD         Category       Connectors, Interconnects         Terminal Blocks - Din Rail, Channel         Package       -         Series       ATX         Type       Feed Through         Disconnect Type       -         Number of Positions       2         Number of Levels       1         Terminal - Width       12.0mm         Termination Style       Screw         Current - IEC       101A         Voltage - IEC       800V         Current - UL       115A         Voltage - UL       600V         Wire Gauge or Range - AWG       2-14 AWG         Wire Gauge or Range - mm²       6-25mm²         Features       Explosion Proof, Harsh Environment         Color       White		
Category         Connectors, Interconnects           Package         -           Series         ATX           Type         Feed Through           Disconnect Type         -           Number of Positions         2           Number of Levels         1           Terminal - Width         12.0mm           Termination Style         Screw           Current - IEC         101A           Voltage - IEC         800V           Current - UL         115A           Voltage - UL         600V           Wire Gauge or Range - AWG         2-14 AWG           Wire Gauge or Range - mm²         6-25mm²           Features         Explosion Proof, Harsh Environment           Color         White	Manufacturer Part Number	ATX25W
Package         -           Series         ATX           Type         Feed Through           Disconnect Type         -           Number of Positions         2           Number of Levels         1           Terminal - Width         12.0mm           Termination Style         Screw           Current - IEC         101A           Voltage - IEC         800V           Current - UL         115A           Voltage - UL         600V           Wire Gauge or Range - AWG         2-14 AWG           Wire Gauge or Range - mm²         6-25mm²           Features         Explosion Proof, Harsh Environment           Color         White	Manufacturer	Amphenol PCD
Package         -           Series         ATX           Type         Feed Through           Disconnect Type         -           Number of Positions         2           Number of Levels         1           Terminal - Width         12.0mm           Termination Style         Screw           Current - IEC         101A           Voltage - IEC         800V           Current - UL         115A           Voltage - UL         600V           Wire Gauge or Range - AWG         2-14 AWG           Wire Gauge or Range - mm²         6-25mm²           Features         Explosion Proof, Harsh Environment           Color         White	Category	Connectors, Interconnects
Series ATX Type Feed Through Disconnect Type - Number of Positions 2 Number of Levels 1 Terminal - Width 12.0mm Termination Style Screw Current - IEC 101A Voltage - IEC 800V Current - UL 115A Voltage - UL 600V Wire Gauge or Range - AWG 2-14 AWG Wire Gauge or Range - mm² 6-25mm² Features Explosion Proof, Harsh Environment Color White		Terminal Blocks - Din Rail, Channel
Type Feed Through  Disconnect Type - Number of Positions 2 Number of Levels 1 Terminal - Width 12.0mm  Termination Style Screw  Current - IEC 101A  Voltage - IEC 800V  Current - UL 115A  Voltage - UL 600V  Wire Gauge or Range - AWG 2-14 AWG  Wire Gauge or Range - mm² 6-25mm²  Features Explosion Proof, Harsh Environment  Color White	Package	-
Disconnect Type  Number of Positions  2  Number of Levels  1  Terminal - Width  12.0mm  Termination Style  Screw  Current - IEC  101A  Voltage - IEC  800V  Current - UL  115A  Voltage - UL  600V  Wire Gauge or Range - AWG  Wire Gauge or Range - mm²  Features  Explosion Proof, Harsh Environment  Color	Series	ATX
Number of Positions2Number of Levels1Terminal - Width12.0mmTermination StyleScrewCurrent - IEC101AVoltage - IEC800VCurrent - UL115AVoltage - UL600VWire Gauge or Range - AWG2-14 AWGWire Gauge or Range - mm²6-25mm²FeaturesExplosion Proof, Harsh EnvironmentColorWhite	Туре	Feed Through
Number of Levels         1           Terminal - Width         12.0mm           Termination Style         Screw           Current - IEC         101A           Voltage - IEC         800V           Current - UL         115A           Voltage - UL         600V           Wire Gauge or Range - AWG         2-14 AWG           Wire Gauge or Range - mm²         6-25mm²           Features         Explosion Proof, Harsh Environment           Color         White	Disconnect Type	-
Terminal - Width  Termination Style  Screw  Current - IEC  101A  Voltage - IEC  800V  Current - UL  115A  Voltage - UL  600V  Wire Gauge or Range - AWG  Wire Gauge or Range - mm²  Features  Explosion Proof, Harsh Environment  Color  White	Number of Positions	2
Termination Style  Current - IEC  101A  Voltage - IEC  800V  Current - UL  115A  Voltage - UL  600V  Wire Gauge or Range - AWG  Wire Gauge or Range - mm²  6-25mm²  Features  Explosion Proof, Harsh Environment  Color  White	Number of Levels	1
Current - IEC 101A  Voltage - IEC 800V  Current - UL 115A  Voltage - UL 600V  Wire Gauge or Range - AWG 2-14 AWG  Wire Gauge or Range - mm² 6-25mm²  Features Explosion Proof, Harsh Environment  Color White	Terminal - Width	12.0mm
Voltage - IEC  Current - UL  115A  Voltage - UL  600V  Wire Gauge or Range - AWG  Wire Gauge or Range - mm²  6-25mm²  Features  Explosion Proof, Harsh Environment  Color  White	Termination Style	Screw
Current - UL  Voltage - UL  600V  Wire Gauge or Range - AWG  Wire Gauge or Range - mm²  6-25mm²  Features  Explosion Proof, Harsh Environment  Color  White	Current - IEC	101A
Voltage - UL  Wire Gauge or Range - AWG  Wire Gauge or Range - mm²  6-25mm²  Features  Explosion Proof, Harsh Environment  White	Voltage - IEC	800V
Wire Gauge or Range - AWG  Wire Gauge or Range - mm²  6-25mm²  Features  Explosion Proof, Harsh Environment  Color  White	Current - UL	115A
Wire Gauge or Range - mm <sup>2</sup> Features  Explosion Proof, Harsh Environment  Color  White	Voltage - UL	600V
Features Explosion Proof, Harsh Environment Color White	Wire Gauge or Range - AWG	2-14 AWG
Color White	Wire Gauge or Range - mm <sup>2</sup>	6-25mm²
	Features	Explosion Proof, Harsh Environment
Report errors?	Color	White
		Report errors?

### **ATX25W Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **ATX25W Payment Methods**





















## **ATX25W Shipping Methods**













If you have any question about ATX25W, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com