



ATX2BG Information

Heisener.com

Part Number ATX2BG

Manufacturer Amphenol PCD

Category Connectors, Interconnects

Terminal Blocks - Din Rail, Channel

Description CONN TERM BLK FEED THRU 14-24AWG

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ATX2BG Specifications

Manufacturer Part Number ATX2BG Manufacturer Amphenol PCD Category Connectors, Interconnects Terminal Blocks - Din Rail, Channel Package - Series ATX Type Feed Through Disconnect Type - Number of Positions 2 Number of Levels 1 Terminal - Width 5.0mm Termination Style Screw Current - IEC 24A Voltage - IEC 800V Current - UL 20A Voltage - UL 600V Wire Gauge or Range - AWG 14-24 AWG Wire Gauge or Range - mm² 0.5-2.5mm² Features Explosion Proof, Harsh Environment Color Beige		
Category Connectors, Interconnects Terminal Blocks - Din Rail, Channel Package - Series ATX Type Feed Through Disconnect Type - Number of Positions 2 Number of Levels 1 Terminal - Width 5.0mm Termination Style Screw Current - IEC 24A Voltage - IEC 800V Current - UL 20A Voltage - UL 600V Wire Gauge or Range - AWG 14-24 AWG Wire Gauge or Range - mm² 0.5-2.5mm² Features Explosion Proof, Harsh Environment Color Beige	Manufacturer Part Number	ATX2BG
Package Series ATX Type Feed Through Disconnect Type - Number of Positions 2 Number of Levels 1 Terminal - Width Some Termination Style Screw Current - IEC Voltage - IEC Somo Voltage - UL Voltage - UL Wire Gauge or Range - AWG Wire Gauge or Range - mm² Features Color Peed Through Feed Thr	Manufacturer	Amphenol PCD
Package - Series ATX Type Feed Through Disconnect Type - Number of Positions 2 Number of Levels 1 Terminal - Width 5.0mm Termination Style Screw Current - IEC 24A Voltage - IEC 800V Current - UL 20A Voltage - UL 600V Wire Gauge or Range - AWG 14-24 AWG Wire Gauge or Range - mm² 0.5-2.5mm² Features Explosion Proof, Harsh Environment Color Beige	Category	Connectors, Interconnects
Series ATX Type Feed Through Disconnect Type - Number of Positions 2 Number of Levels 1 Terminal - Width 5.0mm Termination Style Screw Current - IEC 24A Voltage - IEC 800V Current - UL 20A Voltage - UL 600V Wire Gauge or Range - AWG 14-24 AWG Wire Gauge or Range - mm² 0.5-2.5mm² Features Explosion Proof, Harsh Environment Color Beige		Terminal Blocks - Din Rail, Channel
Type Feed Through Disconnect Type - Number of Positions 2 Number of Levels 1 Terminal - Width 5.0mm Termination Style Screw Current - IEC 24A Voltage - IEC 800V Current - UL 20A Voltage - UL 600V Wire Gauge or Range - AWG 14-24 AWG Wire Gauge or Range - mm² 0.5-2.5mm² Features Explosion Proof, Harsh Environment Color Beige	Package	-
Disconnect Type - Number of Positions 2 Number of Levels 1 Terminal - Width 5.0mm Termination Style Screw Current - IEC 24A Voltage - IEC 800V Current - UL 20A Voltage - UL 600V Wire Gauge or Range - AWG 14-24 AWG Wire Gauge or Range - mm² 0.5-2.5mm² Features Explosion Proof, Harsh Environment Color Beige	Series	ATX
Number of Positions2Number of Levels1Terminal - Width5.0mmTermination StyleScrewCurrent - IEC24AVoltage - IEC800VCurrent - UL20AVoltage - UL600VWire Gauge or Range - AWG14-24 AWGWire Gauge or Range - mm²0.5-2.5mm²FeaturesExplosion Proof, Harsh EnvironmentColorBeige	Туре	Feed Through
Number of Levels Terminal - Width 5.0mm Termination Style Screw Current - IEC 24A Voltage - IEC 800V Current - UL 20A Voltage - UL Wire Gauge or Range - AWG Wire Gauge or Range - mm² Features Explosion Proof, Harsh Environment Color Beige	Disconnect Type	-
Terminal - Width Termination Style Screw Current - IEC 24A Voltage - IEC 800V Current - UL 20A Voltage - UL 600V Wire Gauge or Range - AWG Wire Gauge or Range - mm² Features Explosion Proof, Harsh Environment Color Beige	Number of Positions	2
Termination Style Current - IEC 24A Voltage - IEC 800V Current - UL 20A Voltage - UL 600V Wire Gauge or Range - AWG Wire Gauge or Range - mm² Features Explosion Proof, Harsh Environment Color Screw 24A 800V 800V 600V 600V Features Explosion Proof, Harsh Environment Beige	Number of Levels	1
Current - IEC 24A Voltage - IEC 800V Current - UL 20A Voltage - UL 600V Wire Gauge or Range - AWG 14-24 AWG Wire Gauge or Range - mm² 0.5-2.5mm² Features Explosion Proof, Harsh Environment Color Beige	Terminal - Width	5.0mm
Voltage - IEC Current - UL 20A Voltage - UL 600V Wire Gauge or Range - AWG Wire Gauge or Range - mm² 0.5-2.5mm² Features Explosion Proof, Harsh Environment Color Beige	Termination Style	Screw
Current - UL 20A Voltage - UL 600V Wire Gauge or Range - AWG 14-24 AWG Wire Gauge or Range - mm² 0.5-2.5mm² Features Explosion Proof, Harsh Environment Color Beige	Current - IEC	24A
Voltage - UL Wire Gauge or Range - AWG Wire Gauge or Range - mm² O.5-2.5mm² Features Explosion Proof, Harsh Environment Color Beige	Voltage - IEC	800V
Wire Gauge or Range - AWG Wire Gauge or Range - mm² 0.5-2.5mm² Explosion Proof, Harsh Environment Color Beige	Current - UL	20A
Wire Gauge or Range - mm ² Features Color 0.5-2.5mm ² Explosion Proof, Harsh Environment Beige	Voltage - UL	600V
Features Explosion Proof, Harsh Environment Color Beige	Wire Gauge or Range - AWG	14-24 AWG
Color Beige	Wire Gauge or Range - mm ²	0.5-2.5mm ²
	Features	Explosion Proof, Harsh Environment
Report errors?	Color	Beige
		Report errors?

ATX2BG Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ATX2BG Payment Methods



















ATX2BG Shipping Methods













If you have any question about ATX2BG, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com