



ATX4F Information

Heisener.com

Part Number ATX4F

Manufacturer Amphenol PCD

Category Connectors, Interconnects

Terminal Blocks - Din Rail, Channel

Description CONN TERM BLK FEED THRU 10-22AWG

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ATX4F Specifications

Manufacturer Part Number ATX4F Manufacturer Amphenol PCD Category Connectors, Interconnects Terminal Blocks - Din Rail, Channel Package - Series ATX Type Feed Through Disconnect Type - Number of Positions 2 Number of Levels 1 Terminal - Width 6.0mm Termination Style Screw Current - IEC 32A Voltage - IEC 800V Current - UL 35A Voltage - UL 600V Wire Gauge or Range - AWG 10-22 AWG Wire Gauge or Range - mm² 0.5-4mm² Features Explosion Proof, Harsh Environment Color Orange		
Category Connectors, Interconnects Package - Series ATX Type Feed Through Disconnect Type - Number of Positions 2 Number of Levels 1 Terminal - Width 6.0mm Termination Style Screw Current - IEC 32A Voltage - IEC 800V Current - UL 35A Voltage - UL 600V Wire Gauge or Range - AWG 10-22 AWG Wire Gauge or Range - mm² 0.5-4mm² Features Explosion Proof, Harsh Environment Color Orange	Manufacturer Part Number	ATX4F
Package-SeriesATXTypeFeed ThroughDisconnect Type-Number of Positions2Number of Levels1Terminal - Width6.0mmTermination StyleScrewCurrent - IEC32AVoltage - IEC800VCurrent - UL35AVoltage - UL600VWire Gauge or Range - AWG10-22 AWGWire Gauge or Range - mm²0.5-4mm²FeaturesExplosion Proof, Harsh EnvironmentColorOrange	Manufacturer	Amphenol PCD
Package - Series ATX Type Feed Through Disconnect Type - Number of Positions 2 Number of Levels 1 Terminal - Width 6.0mm Termination Style Screw Current - IEC 32A Voltage - IEC 800V Current - UL 35A Voltage - UL 600V Wire Gauge or Range - AWG 10-22 AWG Wire Gauge or Range - mm² 0.5-4mm² Features Explosion Proof, Harsh Environment Color Orange	Category	Connectors, Interconnects
SeriesATXTypeFeed ThroughDisconnect Type-Number of Positions2Number of Levels1Terminal - Width6.0mmTermination StyleScrewCurrent - IEC32AVoltage - IEC800VCurrent - UL35AVoltage - UL600VWire Gauge or Range - AWG10-22 AWGWire Gauge or Range - mm²0.5-4mm²FeaturesExplosion Proof, Harsh EnvironmentColorOrange		Terminal Blocks - Din Rail, Channel
Type Feed Through Disconnect Type - Number of Positions 2 Number of Levels 1 Terminal - Width 6.0mm Termination Style Screw Current - IEC 32A Voltage - IEC 800V Current - UL 35A Voltage - UL 600V Wire Gauge or Range - AWG 10-22 AWG Wire Gauge or Range - mm² 0.5-4mm² Features Explosion Proof, Harsh Environment Color Orange	Package	-
Disconnect Type Number of Positions 2 Number of Levels 1 Terminal - Width 6.0mm Termination Style Screw Current - IEC 32A Voltage - IEC 800V Current - UL 35A Voltage - UL 600V Wire Gauge or Range - AWG Wire Gauge or Range - mm² Peatures Explosion Proof, Harsh Environment Color Orange	Series	ATX
Number of Positions2Number of Levels1Terminal - Width6.0mmTermination StyleScrewCurrent - IEC32AVoltage - IEC800VCurrent - UL35AVoltage - UL600VWire Gauge or Range - AWG10-22 AWGWire Gauge or Range - mm²0.5-4mm²FeaturesExplosion Proof, Harsh EnvironmentColorOrange	Type	Feed Through
Number of Levels1Terminal - Width6.0mmTermination StyleScrewCurrent - IEC32AVoltage - IEC800VCurrent - UL35AVoltage - UL600VWire Gauge or Range - AWG10-22 AWGWire Gauge or Range - mm²0.5-4mm²FeaturesExplosion Proof, Harsh EnvironmentColorOrange	Disconnect Type	-
Terminal - Width Termination Style Screw Current - IEC 32A Voltage - IEC 800V Current - UL 35A Voltage - UL 600V Wire Gauge or Range - AWG Wire Gauge or Range - mm² Features Explosion Proof, Harsh Environment Color Orange	Number of Positions	2
Termination Style Current - IEC 32A Voltage - IEC 800V Current - UL 35A Voltage - UL 600V Wire Gauge or Range - AWG Wire Gauge or Range - mm² Features Explosion Proof, Harsh Environment Color Orange	Number of Levels	1
Current - IEC 32A Voltage - IEC 800V Current - UL 35A Voltage - UL 600V Wire Gauge or Range - AWG 10-22 AWG Wire Gauge or Range - mm² 0.5-4mm² Features Explosion Proof, Harsh Environment Color Orange	Terminal - Width	6.0mm
Voltage - IEC Current - UL 35A Voltage - UL 600V Wire Gauge or Range - AWG Wire Gauge or Range - mm² 0.5-4mm² Features Explosion Proof, Harsh Environment Color Orange	Termination Style	Screw
Current - UL 35A Voltage - UL 600V Wire Gauge or Range - AWG 10-22 AWG Wire Gauge or Range - mm² 0.5-4mm² Features Explosion Proof, Harsh Environment Color Orange	Current - IEC	32A
Voltage - UL Wire Gauge or Range - AWG 10-22 AWG Wire Gauge or Range - mm² 0.5-4mm² Features Explosion Proof, Harsh Environment Color Orange	Voltage - IEC	800V
Wire Gauge or Range - AWG Wire Gauge or Range - mm² O.5-4mm² Explosion Proof, Harsh Environment Color Orange	Current - UL	35A
Wire Gauge or Range - mm ² Features Color 0.5-4mm ² Explosion Proof, Harsh Environment Orange	Voltage - UL	600V
Features Explosion Proof, Harsh Environment Color Orange	Wire Gauge or Range - AWG	10-22 AWG
Color Orange	Wire Gauge or Range - mm ²	0.5-4mm ²
-	Features	Explosion Proof, Harsh Environment
Report errors?	Color	Orange
		Report errors?

ATX4F Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ATX4F Payment Methods





















ATX4F Shipping Methods













If you have any question about ATX4F, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com