

AVE224M50B12T-F

AVE224M50B12T-F Information



AVE224M50B12T-F
Cornell Dubilier Electronics (CDE)
Capacitors Aluminum Electrolytic Capacitors
CAP ALUM 0.22UF 20% 50V SMD
Radial, Can - SMD
For the pricing/inventory/lead time, please contact
us
Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



AVE224M50B12T-F Specifications

Manufacturer Part NumberAVE224M50B12T-FManufacturerCornell Dubilier Electronics (CDE)CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - SMDSeriesAVECapacitance0.22µFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)753.56 Ohm @ 120HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeRiple Current - Low Frequency5mA @ 120HzRiple Current - High Frequency-Size / Dimension0.157" Dia (4.00mm)Height - Seated (Max)0.209" (5.30mm)Surdace Mount Land Size0.169" L x 0.169" W (4.30mm x 4.30mm)Routing TypeBarda SundRouting TypeSurface MountRouting TypeSurface Mount		
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - SMDSeriesAVECapacitance0.22µFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)73.56 Ohm @ 120HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeRipple Current - Low Frequency5mA @ 120HzRipple Current - High Frequency5mA @ 100HzImpedance-Liad Spacing5.57 Dine (100Hz)Star / Dimension0.157" Dia (4.00mm)Height - Seated (Max)0.209" (5.30mm)Surface Mount Land Size0.169" L x 0.169" W (4.30mm x 4.30mm)	Manufacturer Part Number	AVE224M50B12T-F
Aluminum Electrolytic CapacitorsPackageRadial, Can - SMDSeriesAVECapacitance0.22µFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)753.56 Ohm @ 120HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeRipple Current - Low Frequency5mA @ 120HzRipple Current - High Frequency5mA @ 120HzImpedance-Liad Spacing5.5mA @ 100HzSiz / Dimension0.157" Dia (4.00mm)Height - Seated (Max)0.209" (5.30mm)Surface Mount Land Size0.169" L x 0.169" W (4.30mm x 4.30mm)	Manufacturer	Cornell Dubilier Electronics (CDE)
PackageRadial, Can - SMDSeriesAVECapacitance0.22µFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)753.56 Ohm @ 120HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationFolarApplicationsGeneral PurposeRiple Curren - High Frequency5mA @ 120HzInpedance-Lad Spacing5mA @ 10kHzLiad Spacing0.157" Dia (4.00mm)Height - Seated (Max)0.209" (5.30mm)Surface Mount Land Size0.169" L x 0.169" W (4.30mm x 4.30mm)Mounting TypeSurface Mount	Category	Capacitors
SeriesAVECapacitance0.22µFTolerance±20%Voltage Rated50VESR (Equivalent Series Resistance)733.56 Ohm @ 120HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency5mA @ 120HzInpedance-Lead Spacing5.5mA @ 10kHzSize / Dimension0.157" Dia (4.00mm)Height - Seated (Max)0.209" (5.30mm)Surface Mount Land Size0.169" L x 0.169" W (4.30mm x 4.30mm)Mounting TypeSurface Mount		Aluminum Electrolytic Capacitors
Capacitance0.22µFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)753.56 Ohm @ 120HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency5mA @ 120HzImpedance-Lead Spacing0.157" Dia (4.00mm)Height - Seated (Max)0.209" (5.30mm)Surface Mount Land Size0.169" L x 0.169" W (4.30mm x 4.30mm)Mounting TypeSurface Mount	Package	Radial, Can - SMD
Tolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)753.56 Ohm @ 120HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency5mA @ 120HzNipple Current - High Frequency7.5mA @ 10kHzImpedance-Lead Spacing0.157" Dia (4.00mm)Height - Seated (Max)0.209" (5.30mm)Surface Mount Land Size0.169" L x 0.169" W (4.30mm x 4.30mm)Mounting TypeSurface Mount	Series	AVE
Voltage - RatedSolvESR (Equivalent Series Resistance)753.56 Ohm @ 120HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency5mA @ 120HzImpedance-Lead Spacing-Size / Dimension0.157" Dia (4.00mm)Height - Seated (Max)0.209" (5.30mm)Surface Mount Land Size0.169" L x 0.169" W (4.30mm x 4.30mm)Mounting TypeSurface Mount	Capacitance	0.22µF
ESR (Equivalent Series Resistance)753.56 Ohm @ 120HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency5mA @ 120HzNippedance-Lead Spacing-Size / Dimension0.157" Dia (4.00mm)Height - Seated (Max)0.209" (5.30mm)Surface Mount Land Size0.169" L x 0.169" W (4.30mm x 4.30mm)Mounting TypeSurface Mount	Tolerance	±20%
Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency5mA @ 120HzRipple Current - High Frequency7.5mA @ 10kHzImpedance-Lead Spacing-Size / Dimension0.157" Dia (4.00mm)Height - Seated (Max)0.209" (5.30mm)Surface Mount Land Size0.169" L x 0.169" W (4.30mm x 4.30mm)Mounting TypeSurface Mount	Voltage - Rated	50V
Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency SmA @ 120Hz Ripple Current - High Frequency 7.5mA @ 10kHz Impedance - Lead Spacing - Size / Dimension 0.157" Dia (4.00mm) Height - Seated (Max) 0.209" (5.30mm) Surface Mount Land Size 0.169" L x 0.169" W (4.30mm x 4.30mm)	ESR (Equivalent Series Resistance)	753.56 Ohm @ 120Hz
PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency5mA @ 120HzRipple Current - High Frequency7.5mA @ 10kHzImpedance-Lead Spacing-Size / Dimension0.157" Dia (4.00mm)Height - Seated (Max)0.209" (5.30mm)Surface Mount Land Size0.169" L x 0.169" W (4.30mm x 4.30mm)Mounting TypeSurface Mount	Lifetime @ Temp.	2000 Hrs @ 85°C
ApplicationsGeneral PurposeRipple Current - Low Frequency5mA @ 120HzRipple Current - High Frequency7.5mA @ 10kHzImpedance-Lead Spacing-Size / Dimension0.157" Dia (4.00mm)Height - Seated (Max)0.209" (5.30mm)Surface Mount Land Size0.169" L x 0.169" W (4.30mm x 4.30mm)Mounting TypeSurface Mount	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low FrequencySmA @ 120HzRipple Current - High Frequency7.5mA @ 10kHzImpedance-Lead Spacing-Size / Dimension0.157" Dia (4.00mm)Height - Seated (Max)0.209" (5.30mm)Surface Mount Land Size0.169" L x 0.169" W (4.30mm x 4.30mm)Mounting TypeSurface Mount	Polarization	Polar
Ripple Current - High Frequency 7.5mA @ 10kHz Impedance - Lead Spacing - Size / Dimension 0.157" Dia (4.00mm) Height - Seated (Max) 0.209" (5.30mm) Surface Mount Land Size 0.169" L x 0.169" W (4.30mm x 4.30mm) Mounting Type Surface Mount	Applications	General Purpose
Impedance-Lead Spacing-Size / Dimension0.157" Dia (4.00mm)Height - Seated (Max)0.209" (5.30mm)Surface Mount Land Size0.169" L x 0.169" W (4.30mm x 4.30mm)Mounting TypeSurface Mount	Ripple Current - Low Frequency	5mA @ 120Hz
Lead Spacing - Size / Dimension 0.157" Dia (4.00mm) Height - Seated (Max) 0.209" (5.30mm) Surface Mount Land Size 0.169" L x 0.169" W (4.30mm x 4.30mm) Mounting Type Surface Mount	Ripple Current - High Frequency	7.5mA @ 10kHz
Size / Dimension 0.157" Dia (4.00mm) Height - Seated (Max) 0.209" (5.30mm) Surface Mount Land Size 0.169" L x 0.169" W (4.30mm x 4.30mm) Mounting Type Surface Mount	Impedance	-
Height - Seated (Max) 0.209" (5.30mm) Surface Mount Land Size 0.169" L x 0.169" W (4.30mm x 4.30mm) Mounting Type Surface Mount	Lead Spacing	-
Surface Mount Land Size0.169" L x 0.169" W (4.30mm x 4.30mm)Mounting TypeSurface Mount	Size / Dimension	0.157" Dia (4.00mm)
Mounting Type Surface Mount	Height - Seated (Max)	0.209" (5.30mm)
	Surface Mount Land Size	0.169" L x 0.169" W (4.30mm x 4.30mm)
Package / Case Padial Can SMD	Mounting Type	Surface Mount
Radial, Call - Sivid	Package / Case	Radial, Can - SMD
Report errors?		Report errors?

AVE224M50B12T-F Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

AVE224M50B12T-F Payment Methods





If you have any question about AVE224M50B12T-F, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com